the seal has been broken, the container cannot be resealed and will leak. Do n store previously opened containers in your vehicle. Clean up spills immediately

92

This diesel fuel additive complies with the federal low sulfur content requirements for use in diesel motor vehicles and nonroad engines.

DANGER: COMBUSTIBLE. HARMFUL OR FATAL IF SWALLOWED OR INHALED. HARMFUL IF ABSORBED THROUGH THE SKIN, MAY CAUSE SKIN, RESPIRATORY AND SERIOUS EYE IRRITATION. Use only in well-ventilated area. Keep away from heat and flame. Do not swallow. Do not breathe vapors. Avoid contact with eyes, skin and clothing. Wear protective gloves. FIRST AID: If swallowed, do not induce vomiting. Call physician immediately. If inhaled, move person to fresh air. If on skin, wash thoroughly with soap and water. Remove and wash contaminated clothing before reuse. If in eyes, rinse slowly and gently with water for 15-20 minutes, removing contact lenses, if present, after the first 5 minutes. If irritation persists for any exposure, call a physician. Contains hydroxy alkoxylate, petroleum distillates and aromatic hydrocarbons. AWARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov. KEEP OUT OF REACH OF CHILDREN.

> Go to powerservice.com to learn more about our year-round maintenance schedule.

the second second second

Fuel Tank Hygiene

Part No. 9225 POWER SERVICE PRODUCTS, INC. Weatherford, TX 76086 v.www.powerservice.com © 2018 Power Service Products, Inc.