

# GEN SELECT

5 Kelvin Options, All in One Fixture.



As with each generation of our low-profile LED downlights, Gen Select offers a domed, polycarbonate diffuser, all-in-one integrated LED, and easy-on/easy-off installation plus 5-in-1 color temperature selection built-in. This color selection allows you to choose between five hues of white light, all in one fixture, reducing the guess work when planning. To select the best white light for your space, simply remove the diffuser to access the switch, and select the desired color temperature for the room. This transitional style downlight features a surface mount design, making it perfect for any setting.



- 5 Kelvin options in one fixture 2700K, 3000K, 3500K, 4000K and 5000K.
- Color temperature selection can be changed after installation by removing the diffuser.
- Domed, polycarbonate diffuser lens delivers even light distribution.
- Installs to an array of 3" and 4" J-box options, including a pancake box, for optimal placement flexibility, including in smaller spaces.
- Provides a wider input range of 108VAC-132VAC for better power regulation and improved LED consistency.
- Installs quickly and easily, creating a cleaner completed look.
- Prevents air escape with close-to-ceiling seal to help keep heating and cooling efforts inside.
- Aluminum construction allows for installation in an indoor shower or outdoor covered ceilings.
- Enhanced surge protection (2.5KV) to protect the core components of the fixture.
- All-in-one, integrated LED energy efficient fixtures means one fixture to order, track and install.



### 43849WH5CCT

Bulk Pack	<b>43849WH5CCTB</b> (24-Count Bulk Pack)
Light Source	LED
Kelvin Temp (Selectable)	2700K, 3000K, 3500K, 4000K, 5000K
Diameter	7.3"
Height	1.19" from ceiling
Lumen Output	1000lm (3000K)
Watts	15
Efficacy	67 lm/W (3000K)
Dimmable For recommended dimmers, visit <a href="http://Kichler.com/dimming">Kichler.com/dimming</a>	Yes - down to 10%
Finish Options	White - WH
Safety Rating	Wet
Installation Requirements	Wet indoor ceiling applications (showers), Damp outdoor ceiling applications (covered porches)
Energy Star	No
Title 24 Compliant (JA-8)	Yes
FCC Compliant	Yes
J-box type	An array of 3" and 4" J-box options, including a pancake box
Color Rendering Index (CRI)	90+



**Backed by Kichler Lighting's 5-year warranty.** For details, visit [Kichler.com/warranty](http://Kichler.com/warranty)

See the complete line of Kichler Downlights at [Kichler.com/downlights](http://Kichler.com/downlights)