

Anker Power Stations									
Product Name	Anker SOLIX C200X DC Portable Power Station	Anker C200X Portable Power Station	Anker C300X Portable Power Station	Anker SOLIX C800X Portable Power Station	Anker SOLIX C1000X Gen 2 Portable Power Station	Anker SOLIX F1500 Portable Power Station	Anker SOLIX F2600 Portable Power Station	Anker SOLIX F3800 Portable Power Station	Anker SOLIX F3000 Portable Power Station
Capacity	192Wh	230.4Wh	288Wh	768Wh	1,024Wh	1,536Wh	2,560Wh	3,840Wh	3,072Wh
AC Output Power	N/A	300W	300W	1,200W	2,000W	1,800W	2,400W	6,000W	3,600W
USB-A Ports	2 x 12W	1 x 12W	1 x 12W	2 x 12W	1 x 12W	4 x 12W	2 x 12W	2 x 12W	2 x 12W
USB-C Ports	1 x 15W 1 x 100W 1 x 140W	1 x 15W 2 x 140W	1 x 15W 2 x 140W	1 x 30W 1 x 100W	1 x 15W 2 x 140W	1 x 60W 1 x 100W	3 x 100W	3 x 100W	2 x 100W
Car Socket	N/A	1 x 120W	1 x 120W	1 x 120W	1 x 120W	1 x 120W	2 x 120W	1 x 120W	1 x 120W
Max AC Input Power	N/A	285W	330W	1,100W	1,600W	1,000W	1,440W	1,800W	3,600W
Solar Input Power (MPPT)	100W	100W	100W	300W	600W	600W	1,000W	2,400W	2,400W
EV Charger Input Power	N/A	N/A	N/A	N/A	N/A	N/A	N/A	120V/240V~ 25A Max, 60Hz, 6000W Max	120V~ 30A Max (< 3 Hr), 3,600W Max, 24A (Continuous), 60Hz, L+N+PE (TT-30 Charging Cable + EV Charging Adapter) 240V~ 15A Max, 3,600W Max, 60Hz, L+N+PE (EV Charging Adapter)
Battery Lifecycle	80% of Battery Capacity After 3,000 Cycles	80% of Battery Capacity After 3,000 Cycles	80% of Battery Capacity After 3,000 Cycles	80% of Battery Capacity After 3,000 Cycles	80% of Battery Capacity After 4,000 Cycles	80% of Battery Capacity After 3,000 Cycles	80% of Battery Capacity After 3,000 Cycles	80% of Battery Capacity After 3,000 Cycles	80% of Battery Capacity After 4,000 Cycles
Battery Type	LifePO4	LifePO4	LifePO4	LifePO4	LifePO4	LifePO4	LifePO4	LifePO4	LifePO4
Weight	4.2 lb / 1.9 kg	8.8 lb / 4 kg	9.1 lb / 4.13 kg	24.03 lb / 10.9 kg	24.9 lb / 11.3 kg	43.7 lb / 19.8 kg	69.7 lb / 31.6 kg	132.3 lb / 60 kg	91.5 lb / 41.5 kg
Dimension	3.94 x 4.33 x 7.28 in 100 x 110 x 185 mm	6.46 x 6.34 x 9.45 in 164 x 161 x 240 mm	6.46 x 6.34 x 9.45 in 164 x 161 x 240 mm	14.61 x 8.07 x 9.96 in 371 x 205 x 253 mm	15.12 x 8.19 x 9.61 in 384 x 208 x 244 mm	18.2 x 11.3 x 9.3 in 463 x 288 x 237 mm	20.7x 9.8x 15.5 in (without wheels) 525x 250 x 394 mm (without wheels) 20.8x 10.6x 15.6 in (with wheels)	27.6 x 15.3 x 15.6 (with wheels 2.56 in) 702 x 388 x 395 (with wheels 65 mm)	25.6 x 11.8 x 14.8 in 651 x 300 x 377 mm
HyperFlash Technology	yes	yes	yes	yes	yes	yes	yes	yes	yes
UPS Function	N/A	10 ms	10 ms	20 ms	10 ms	20 ms	20 ms	20 ms	20 ms
LCD Display	yes	yes	yes	yes	yes	yes	yes	yes	yes
Ambient Light Bar	no	yes	yes	yes	no	yes	yes	yes	yes
RV Plug(AC port)	N/A	3 x 300W Standard AC Socket	3 x 300W Standard AC Socket	5 x 1,200W Standard AC Socket	5 x 2,000W Standard AC Socket	6x 1,800W Standard AC Socket	4 x 2,400W Standard AC Socket 1 x 120V 2,400W TT-30R	1 x 240V 6,000W L14-50R 1 x 240V 6,000W L14-30R 6x 2,400W Standard AC Socket	5 x 1,800W Standard AC Socket 1 x 3,600W TT-30
Smart App Control	yes	yes	yes	yes	yes	yes	yes	yes	yes
Self-Consumption (App Function)	no	no	no	no	yes	no	no	yes* work with Home Power Panel	yes* work with Inlet Box
Time of Use (App Function)	no	no	no	no	yes	no	no	yes* work with Home Power Panel	yes* work with Inlet Box
Severe Weather Mode (App Function)	no	no	no	no	yes	no	no	yes* work with Home Power Panel	yes* work with Inlet Box
Manual Backup Power (App Function)	no	no	no	no	yes	no	no	yes	yes* work with Inlet Box
Fast Charge	no	no	no	no	yes	no	no	no	no