
MOUNTING AND WIRING

Improper installation may cause electrical shock, fire, or equipment damage.

The person performing the installation must be familiar with the construction

WARNING:



Wire Connection Diagram:



Please proceed in an alphabetical order:

- HH.Existing Elextrical BOX AA.Crossbar BB.Crossbar Screws ZZ.Ground Wire CC.Canopy XX.Wire UU.Junction Caps
- attach the crossbar(AA)to the existing electrical box(HH) using the two crossbar screws(BB)which are not supplied and should already in your box.
- Pass the main wire(XX)and ground wire(ZZ)through the canopy(CC)and the crossbar(AA)until the end of the main wire(XX)reaches the electrical box (HH)where you can wire use electrician connections.Be sure when connecting the wire use electrician approved junction caps(UU) stow the excess wire in the electrical box(HH).raise the canopy(CC),attach canopy(CC)to ceiling, and hold the canopy(CC).


Installation Instructions Manufacturer Part Number: M095/M096

Customer Service Number: (832) 478-8866 Customer Service Email: WeCareWeFix@gmail.com

Please include your name, contact methods, product name, and model number in the email.

IMPORTANT SAFETY INSTRUCTIONS:

- Please read through all the instructions carefully and completely before beginning assembly and installation
- This product must be installed in accordance with installation instructions and all safety and building codes. It is strongly suggested that all direct wired fixtures be installed by a licensed electrician
- Be sure the electricity to the wires you are working on is shut off; either the fuse is removed or the circuit breaker is turned off. Turning the power off using the light switch is not sufficient to prevent electrical shock



WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer or birth defects or other reproductive harm. For more infomation go to www.P65Warnings.ca.gov

