





Capella® lures you—a quiet corner of restoration in a hectic schedule. A place to be alone with your thoughts—a task made easy by Jacuzzi's quiet pumping system, and made better by customizable, electronic massage control. All you'll hear is the rise and gentle burst of a million bubbles. All you'll feel is deepest relaxation.

#### features:

- Sculpted armrest
- Contoured backrest
- 600 watt heated air blower
- 360° Balanced AirFlow System
- Safely use salts and aromatic oils
- Slip-resistant bottom
- TLC: Thermal Lumbar Comfort area
- Tru-Level<sup>™</sup> self-leveling base system

### capella 60 pure air Il bath

model number: BE60

exterior dimensions:

60" long x 60" wide x  $20\frac{1}{2}$ " high

interior dimensions: 50" long x 34" wide(mid)

operating gallons: **65 gallons** 

**Detail:** The Capella® pure air® II bath features integral neck and backrests, and Jacuzzi's exclusive TLC system.





# Capella® 60" Corner Pure Air II™ Bath

Model: BE60

## **Ordering Information**

Product Code: BE60 Capella® 60" Corner Pure Air II™ Bath Right Hand

- Center Drain Location
- · Accessories / Hardware:

Trim Kit Rotary: #BN21

• Trim Kit Finishes Available:

(827) - Chrome

(898) - Brushed Chrome

(815) - Satin Nickel

(829) - Bright Brass

(805) - Platinum

(826) - Brushed Nickel

(849) - Oil Rubbed Bronze

### Installation Notes

Refer to installation instructions included with fixture before beginning installation. Please confirm product availability and specifications before commencing with any installation work.

PRODUCT SPECIFICATIONS AND AVAILABILITY ARE SUBJECT TO CHANGE WITHOUT NOTICE.

### **Technical Specifications**

#### **Dimensions**

60" L x 60" W x 20-1/2" H (1524 mm) L x (1524 mm) W x (521 mm) H

#### **Drain/Overflow**

A: 18" (457 mm) B: 12-1/8" (308 mm)

#### Cutout

See Illustration Below

#### **Total Weight**

966 lb (439 kg) / 39 lb/sq. ft. (190 kg/m<sup>2</sup>)

### **Operating Gallonage**

65 U.S. gal (246 liters)

### **Product Weight**

175 lb (80 kg)

### **Skirt Mounting**


Optional

### **Electrical Specifications**


Requires a dedicated GFCI protected separate circuit.


Blower: 120 VAC, 15 AMP, 60 Hz.


No water heater is available on this unit. Blower has integral air heater.



\* Measurements inside unit represent cutout in floor to allow for drain/overflow.







DRAIN/OVERFLOW