

TIPS

- **IMPORTANT:** Shake well before and frequently during spraying
- Cover surrounding areas to protect from over spray
- Dispense a quick burst on scrap material to activate pressure
- Practice spraying on scrap material before applying
- Spray using intermittent bursts

FEATURES & BENEFITS

- Excellent texture match
- 30 Minute paint ready time depending on temperature, humidity & amount applied
- Sag-resistant formula
- No priming required
- Control grip trigger
- Low odor
- Easy water clean-up

INSTRUCTIONS

SAFETY FIRST! PRODUCT IS EXTREMELY FLAMMABLE WHEN DISPENSING. Before using, read and understand all health and safety/product use instructions. Always point spray tip down and away from people.

SURFACE PREPARATION: Surface must be clean, dry, structurally sound and free of all foreign material. Make any necessary repairs to surface and ensure it is smooth and dry prior to applying spray texture.



- 1 SHAKE** can upside down vigorously for more than a minute after hearing mixing marble moving freely in the can.
- 2 TEAR OFF** top safety tab by pulling tab from front to back of top of nozzle. This safety tab is not reusable and it is meant to be broken off. **IMPORTANT:** Dispense a quick burst of material on scrap materials to activate before applying to surface.
- 3 ADJUST** texture for medium to heavy texture spray without straw insert. For heavier texture, overlap texture sprays. Adjust distance to the wall as needed. For finer texture, firmly insert straw into nozzle tip. **IMPORTANT:** Practice using scrap material before applying onto the wall.
- 4 SPRAY** holding can approximately 12 to 18 inches away from surface using intermittent bursts. For optimal blending, use different stroke motions like up and down, or left to right. Apply texture in overlapping passes to avoid gaps or uneven spots. If not satisfied, scrape-off and reapply. **IMPORTANT:** Be sure that the area is well ventilated and proper safety gear is worn.
- 5 PAINT:** Allow texture to dry for 30 minutes prior to painting. Dry time may be longer in cooler/humid conditions or with thicker applications. Follow paint manufacturer's instructions for best results. For exterior applications, use an exterior grade paint.
- 6 CLEAN-UP** straw, nozzle, tools and area with towel and warm water. Be sure to remove any texture build up from tip/nozzle to prevent material drying on nozzle. Insert straw into the top of nozzle. Spray a quick burst onto a disposable surface.



ORANGE PEEL

WALL TEXTURE

Textura de la pared

WATER-BASED
LOW ODOR • EASY CLEAN-UP

ADJUSTABLE FOR
EXCELLENT TEXTURE MATCH



STRONG ADHESION
Sag-Resistant Formula

TEXTURE & PRIME IN ONE STEP
Easy Application

PRO RESULTS
FROM THE #1 WALL REPAIR BRAND*

DANGER! EXTREMELY FLAMMABLE. VAPORS MAY CAUSE FLASH FIRE. IRRITANT. CONTENTS UNDER PRESSURE. Read back panel carefully for cautions.

¡PELIGRO! EXTREMADAMENTE INFLAMABLE. LOS VAPORES PUEDEN CAUSAR COMBUSTIÓN ESPONTÁNEA

Contains crystalline silica, calcium carbonate and dimethyl ether. May irritate eye, skin and lung. May cause sensitization by inhalation or skin contact. Individuals with lung or breathing problems such as asthma must not be exposed to vapor. Use only with adequate ventilation. Do not breathe vapor. Ensure fresh air entry during application and drying. Avoid contact with skin & eyes. Wear protective clothing, protective gloves & eye protection. Vapor may ignite explosively. Keep away from heat, sparks & flame. Do not smoke. Extinguish all flames & pilot lights. Turn off stoves, heaters, electrical motors, & other sources of ignition during use & until vapor is gone. Do not puncture, strike or incinerate can. Do not expose to heat or store at temperature above 120°F. Harmful if swallowed. Do not ingest. **FIRST AID:** SKIN: Wash thoroughly with soap and water. EYE: Remove Immediately with a clean dry rag. Get medical attention. INHALATION: Remove to fresh air. INGESTION: DO NOT INDUCE VOMITING. Get medical attention immediately. **For emergencies,** call your Poison Control Center at 800-222-1222. See Safety Data Sheet (SDS) at dap.com for additional information. **KEEP OUT OF REACH OF CHILDREN.**

Contiene sílice cristalina, carbonato de calcio y éter dimetilico. Puede irritar los ojos, la piel y los pulmones. Puede causar sensibilización por inhalación o contacto con la piel. Utilícelo solamente con ventilación adecuada. No respire el vapor. Garantice la entrada de aire fresco durante la aplicación y el curado. Evite el contacto con la piel y los ojos. Use ropa y guantes protectores y protección para los ojos. El vapor se puede encender explosivamente. Manténgalo alejado del calor, chispas y llamas. No fume. Apague todas las llamas, incluso las llamas del piloto. Apague las estufas, calentadores, motores eléctricos y otras fuentes de ignición durante el uso y hasta que el vapor se haya disipado. No perfore, golpee ni incinere la lata. No exponga al calor ni almacene a temperaturas superiores a 49°C (120°F). Nocivo si se traga. No lo ingiera. **PRIMEROS AUXILIOS:** PIEL: Lávese muy bien con agua y jabón. OJOS: Retire inmediatamente con un paño limpio y seco. Obtenga atención médica. INHALACIÓN: Lleve hacia el aire fresco. INGESTIÓN: NO INDUZCA EL VÓMITO. Obtenga atención médica de inmediato. **Para emergencias** llame a su Centro de control de envenenamientos al 800-222-1222. Consulte la Hoja de datos de seguridad (SDS) en dap.com para más información. **MANTÉNGASE FUERA DEL ALCANCE DE LOS NIÑOS.**

WARNING Cancer / ADVERTENCIA Cáncer –
www.P65Warnings.ca.gov

VOC: 14 wt/wt% (351 g/L)

LIMITED WARRANTY: If product fails to perform when used as directed within one year of date of purchase, call 1-888-888-DAP-TIPS with your sales receipt and product & finish container available, for replacement product or sales price less the 100% refund. DAP Global Inc. will not be responsible for consequential damages.

*Based on independent hardware and lumber channel dollar sales in the Wall Repair category.

QUESTIONS? / ¿PREGUNTAS? Call/Llame al 888-DAP-TIPS or visit/visite dap.com & click on/ y pulse en "Ask the Expert."

Para obtener las instrucciones y garantía en