




















































<div></div> <div>Sikaflex[®] Repair Sealants</div>		Joint Movement	Max Width	Max Depth	Tack-Free Time	Vertical & Overhead	Horizontal Applications	Paintable & Stainable	Available Colors	Packaging Sizes	Applications/ Where to use?
<div></div> <div>Sikaflex[®] + Concrete Fix Non-sag concrete crack repair sealant<ul style="list-style-type: none">■ Remains permanently elastic after cure■ Exceptional cut and tear resistance■ Excellent resistance to aging/ weathering</div>		± 35%	1 ½ in	½ In.	3-6 Hrs.	■	■	■	 Limestone	10.1 oz	<div><ul style="list-style-type: none">■ Non-sag applications■ Vertical & horizontal crack repair■ Concrete crack repairs■ Driveway / Walkway / Patio / Slab Wall / Foundation</div>
<div></div> <div>Sikaflex[®] + Mortar Fix Textured mortar joint repair sealant<ul style="list-style-type: none">■ Textured to blend easily with rough surfaces■ Hides imperfections from tooling■ Remains permanently elastic after cure</div>		± 25%	1 ½ in	½ In.	3-6 Hrs.	■	■	■	 Limestone	10.1 oz	<div><ul style="list-style-type: none">■ Non-sag applications■ Repair damaged mortar■ Tuckpointing brick mortar joints■ Masonry, brickwork & blockwork</div>
<div></div> <div>Sikaflex[®] + Construction Sealant All purpose, non-sag sealant<ul style="list-style-type: none">■ Non-sag for vertical and overhead applications■ Superior adhesion and durability■ Smooth finish</div>		± 35%	1 ½ in	½ In.	3-6 Hrs.	■	■	■	 White  Limestone  Capitol Tan  Dark Bronze  Aluminum Gray  Black	10.1 oz	<div><ul style="list-style-type: none">■ Non-sag applications■ Sealing window + door perimeters■ Sealing Joints + Gaps: Walls / Floors / Trim / Siding / Flashing</div>
<div></div> <div>Sikaflex[®] + Self-Leveling Sealant Self-leveling sealant for horizontal joints<ul style="list-style-type: none">■ For non-sloped surfaces■ Accelerated curing capacity■ Remains permanently elastic after cure</div>		± 25%	1 ½ in	½ In.	1-2 Hrs.	■	■	■	 Gray  Sandstone	10.1 oz 29 oz	<div><ul style="list-style-type: none">■ Horizontal expansion joints■ Driveways / Garages■ Sidewalks / Patios■ Balconies / Terraces</div>
<div></div> <div>Sikaflex[®] + Crack Flex Sealant Self-Leveling, textured sealant for concrete<ul style="list-style-type: none">■ Able to fill horizontal cracks in concrete up to 1 in. wide■ Remains permanently elastic to allow for movement■ Textured sealant blends with existing concrete</div>		± 25%	1 in	½ In.	1-2 Hrs.	■	■	■	 Gray	10.1 oz	<div><ul style="list-style-type: none">■ Cracks in horizontal concrete surfaces■ Driveway crack repair■ Concrete steps■ Garage floor crack repair■ Concrete sidewalks</div>
<div></div> <div>Sikaflex[®] Asphalt Sealant Self-Leveling sealant for cracks in asphalt<ul style="list-style-type: none">■ Easy application, self-levels■ Excellent adhesion, bonds to asphalt & concrete■ Cures to a matte black finish to blend with asphalt</div>		± 25%	1 ½ in	½ In.	< 1 Hr.	■	■	■	 Black	9 oz	<div><ul style="list-style-type: none">■ Horizontal crack repair■ Cracks in asphalt■ Joint & Crack Sealing■ Driveways / Pavements■ Blacktop / Roadways</div>
<div></div> <div>Sikaflex[®] Insulation Sealant Insulation boards/wraps - Hard to bond surfaces<ul style="list-style-type: none">■ Seals gaps/voids around penetrations■ Basement Insulation/Masonry/CMU Block■ No burn through</div>		± 12.5 %	1 ½ in	½ In.	30-90 Mins.	■	■	■	 White  Dark Bronze	9 oz	<div><ul style="list-style-type: none">■ Air sealing of liquid applied weather barriers■ Termination & transition seals■ Edge lap seals■ Seal around exterior window & door frames■ Adhering foam insulation boards</div>
<div></div> <div>Sikaflex[®] Hybrid Self-Lev. Sealant One-component, hybrid sealant & crack filler<ul style="list-style-type: none">■ Non-sloped horizontal applications■ Sealing cracks & joints in concrete / asphalt■ Self-leveling, no tooling required</div>		± 25%	1 in	½ In.	≈ 45 Mins.	■	■	■	 Black	10.1 oz	<div><ul style="list-style-type: none">■ For use on control joints & expansion joints■ Eco friendly: solvent & isocyanate free■ Remains permanently elastic■ Excellent resistance to aging & weathering■ Roadways / Driveways / Walkways / Garage / Patio / Pavements / Floor Slabs</div>