

QC CL-7000 RF

QuietCool Original Classic Line

QC CL-7000 RF Specifications

Airflow	Hi: 6,924 CFM / Low: 5,518 CFM	
HVI-916 Airflow (for CA Title 24 New Construction)	Hi: 5,300 CFM / Low: 4,100 CFM	
Recommended SQFT Coverage @ 2-3 CFM per SQFT	Covers 2,308 SQFT to 3,462 SQFT	
Energy Use	Hi: 1,147 Watts / Low: 794 Watts	
Amps	Hi: 9.61 / Low: 7.12	
Motor Voltage	120 VAC, 60 Hz	
# of Speeds	2	
dBA	Hi: 54.3 / Low: 47.4	
Minimum Attic Clearance	44"	
Duct Diameter	24"	
Duct Length	9 feet	
Motor Head Diameter	24 1/2"	
Motor Head Length	13 1/2"	
Dampers	Barometric Pressurized R5 Dampers	
Controls	Included IT-36003 QuietCool Wireless RF Control Kit with Glass Wireless RF Switch	
Warranty	10 Years	
Framing	None Required	
Joist Cutting	None Required; fits 16" or 24" on center	
Minimum Suggested Attic Venting	9.24 SQ FT net free area	
Ceiling Rough Opening	14 1/4" x 36 1/4"	
Removable Grille Outside Dimension	16" x 38"	
Shipping Weight	95 lbs.	
Box Dimensions	41" x 28" x 39"	
In The Box	-QC CL-7000 Motorhead -Ceiling Grille -Cut-out Template -Window Locks -Damper Box -9 Foot Duct -Accessory Bag -Wireless RF Control Kit	



For more information, visit our website at:
QUIETCOOLSYSTEMS.COM