

Pergo DuraCraft + WetProtect Locking Luxury Vinyl Tile - Care and Maintenance

Care and Cleaning

Place felt floor protectors under legs of moveable furniture. Chair casters should be rubber — not plastic or metal. Place walk-off mats at entrances. Floor protectors should be at least one inch in diameter. Dust mop as primary cleaning method. Occasionally wet mop with water only, using a well wrung-out mop; **DO NOT** pour liquid directly on floor or use an excessively wet mop that will puddle or leave moisture standing on the floor. If needed, use a solution bleach of 1:80 ratio of standard household bleach to water (1/4 cup bleach to 1 gallon water). Never mix with anything other than water, follow manufacturer of the bleach on recommendations for safety. **DO NOT** use detergents, abrasive cleaners, soaps, waxes or polishes. A residential steam mop may be used, provided the steam is applied to a microfiber pad and not applied directly to the floor. Make sure to set the temperature of the steam mop to the lowest setting. Steam mop in the length direction of the planks only. Use correct hard surface vacuum tools. **DO NOT** use rotating beater bars, floor scrubbers, jet mops or similar products. Wipe up spills immediately. **DO NOT allow topical moisture to remain on the floor longer than the time specified in the product warranty.**

WARNING:

- The products in this carton **DO NOT** contain asbestos or crystalline silica.
- **DO NOT MECHANICALLY CHIP OR PULVERIZE EXISTING RESILIENT FLOORING, BACKING, LINING FELT, ASPHALTIC “CUTBACK” ADHESIVES OR OTHER ADHESIVES.**
- **DO NOT** sand existing resilient tile, sheet flooring, backing or felt linings. These products may contain asbestos fibers that are not readily identifiable. Inhalation of asbestos dust can cause asbestosis or other serious bodily harm. Check with local, state and federal laws for handling hazardous material before attempting the removal of these floors.

Warranty Conditions

The owner/installer assumes all responsibility for final inspection of product quality. Examine flooring for color, finish and style **prior to installation**. If material is unacceptable, contact the seller immediately. Installer should work from minimum of 3 cartons at the same time to ensure good color and shade blend. The installer must use reasonable selectivity and hold out or cut off piece with deficiencies. **DO NOT** install undesirable pieces. Flooring warranties **DO NOT** cover materials with visible defects once they are installed. Installation is acceptance of product quality.

It is the responsibility of the installer and owner to ensure that jobsite, environmental, subfloor and subsurface conditions involved meet or exceed all requirements as outlined in installation instructions prior to installation. Manufacturer declines all responsibility for product performance or installation failure due to subfloor, substrate or environmental deficiencies or jobsite conditions.

For service under the warranty please contact your local Lowe's store. Describe the problem, and in many cases, they can provide you with a solution.

For installation, maintenance and technical questions please call 1-800-33-PERGO (1-800-337-3746) or visit www.pergo.com.