STAFFORD[™]

FP8274 Ceiling Fan**



Net Hanging Weight: 23.19 lbs

Floor

	Α	В
Fan w/4.5" downrod	15.59″	11″
Fan w/12" downrod	23.09″	18.5″
Fan w/18" downrod	29.09″	24.5″
Fan w/24" downrod	35.09″	30.5″
Fan w/36" downrod	47.09″	42.5″
Fan w/48" downrod	59.09″	54.5″
Fan w/60" downrod	71.09″	66.5″
Fan w/72" downrod	83.09″	78.5″

Available Finishes					
Fan / Housing Assembly					
DZ	Dark Bronze with Dark Walnut / Cherry Blade				
BN	Brushed Nickel with Dark Walnut / Cherry Blade				
GR	Matte Grelge with Weathered Wood Blade				
BN	Brushed Nickel with Dark Walnut / Cherry Blade				

INSTALLATION REQUIREMENTS:

Ceiling fan attaches to electrical junction box securely anchored and capable of withstanding a load of at least 35 lbs.

ELECTRICAL REQUIREMENTS:

Ceiling fan requires a grounded electrical supply line of 120 vo AC, 60 Hz, 15 amp circuit.

MOTOR SPECS:

172 x 17 AC motor is designed for optimal performance with this fan.

BLADE SETS:

A set of five 20" reversible Plywood blades is included.

CONTROL OPTIONS:

TR500 hand-held remote control is included. Push button remote control with variable fan speeds, infinite light levels and off button. Optional WC2WH and WR501WH wall controls and WFR50 receiver are available--sold separately. Instructions are provided with each control.

Airtiow / Energy Efficiency Into (120V)					
Fan Speed	Max RPM	CFM	CFM / Watts	Amps	Watts
High	156	5039	80	0.53	63
Med	105	3174	109	0.37	29
Low	49	1426	168	0.19	8

L.f. (400)/

	Energy Guide FTC						
Power Total Air Delivery (W _{ave}) (CFM _{ave})		Estimated Yearly Energy Cost (\$)	Ceiling Fan Efficiency (CFM/W)				
39	3346	11	85				

Light Bulb Information (120V)						
Bulb Socket	Bulb Type	Watts	QTY	Lumens Amount	Color Temp	CRI
E12	LED	4	3	900	2700	90%

LIGHTING OPTIONS:

Three 4-watt LED bulbs included.

DOWNROD OPTIONS:

Fan comes with 1" dia. x 4.5" long downrod (DR1-45). Optional downrods available in 12", 18", 24", 36", 48", 60", and 72" lengths. A downrod coupler is available for installations requiring a downrod longer than 72". The fan can be mounted on a sloped ceiling up to 27°. Optional sloped ceiling ball kits (SCB1-52) are available for slope angles greater than 27° and up to 42°. Optional close-to-ceiling kit is available as well—sold separately. Call technical support for more information.

LOCATION USE:

Fan is rated for dry location only.

	Airflow / Energy Efficiency							
olts	Fan Speed	Max RPM	CFM	CFM / W				
	High	156	5039	80				
	Med	105	317/	100				