



# RUST-OLEUM® LOW ODOR SPRAY PAINT

## DESCRIPTION AND USES

Rust-Oleum® LOW ODOR spray paint is a water-based formulation designed to minimize odor while spraying. It can be used on wood, metal, most plastics, wicker and more. The low odor formula provides a long-lasting durable finish, making it suitable for both indoor and outdoor projects.

Rust-Oleum's comfort tip reduces finger fatigue, while the fan spray pattern provides greater control to minimize runs and drips. The spray anyway system allows for spraying at any angle, even upside down.

**TIP:** Some plastics made of polyethylene such as plastic storage containers are manufactured in a way that may hinder maximum paint adhesion. Test paint in a hidden area first.

## PRODUCTS

SKU	DESCRIPTION (11 oz. Aerosol)
388273	Matte Dusty Rose
388279	Matte Blackout
388280	Matte Dolphin Gray
388281	Matte Timeless Red
388282	Matte In The Green
388283	Matte Moss Green
388284	Matte Daydreaming
388285	Matte Deep Sea
388286	Matte Snow White
398630	Matte Autumn Spice
398632	Matte Oatmeal
398634	Matte Vintage Teal
398635	Matte Tulip
398628	Gloss Eggplant
398629	Gloss Hunter Green
398636	Gloss Ivory
388245	Gloss Blackout
388246	Gloss Anchor Gray
388247	Gloss Ladybug Red
388268	Gloss Orange Soda
388269	Gloss Daisy Yellow
388270	Gloss Lucky Green
388271	Gloss Navy Blue
388272	Gloss Blueberry
388274	Gloss Snow White
388275	Gloss Seashell

## PRODUCT APPLICATION

### READ ALL DIRECTIONS BEFORE BEGINNING PROJECT

#### SURFACE PREPARATION

Remove all dirt, grease, oil, salt and chemical contaminants by washing the surface with a commercial detergent, or other suitable cleaning method. Rinse with fresh water and allow to thoroughly dry. Remove loose paint and rust with a wire brush or sandpaper. Previously coated surfaces must be sound and in good condition. Smooth, hard, or glossy finishes should be scarified by sanding to create a surface profile.

## PRODUCT APPLICATION (cont.)

### SURFACE PREPARATION (cont.)

**WARNING!** If you scrape, sand or remove old paint from any surface, you may release lead paint dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

### PRIMING

Use of Rust-Oleum LOW ODOR Primer provides superior adhesion and hiding and is especially recommended for bare wood and metal.

398590	White Primer
398591	Gray Primer

### APPLICATION

Use outdoors or in a well-ventilated area such as an open garage. Use when temperature is between 50°F (10°C) and 90°F (32°C) and humidity is below 65% to ensure proper drying. Do not apply to surfaces that, when heated, exceed 200°F (93°C) or galvanized metal. Avoid spraying in very windy, dusty conditions. Cover surrounding area to protect from spray mist.

Shake can vigorously for one minute after mixing ball begins to rattle. If mixing ball fails to rattle, DO NOT STRIKE CAN. Contact Rust-Oleum. Shake often during use. Hold can upright 10-16" from surface and spray in a steady back-and-forth motion, slightly overlapping each stroke. Keep the can the same distance from the surface. Keep the can in motion while spraying. Apply 2 or more light coats a few minutes apart.

### DRY AND RECOAT TIMES

Based on 70°F – 50% relative humidity. Allow more time at cooler temperatures. Dries to the touch in one hour, to handle in 2-4 hours and fully dry in 24 hours. Apply a second coat at any time. For added durability, apply clear topcoat after 2 hours. Apply clear in 2-3 light coats a few minutes apart.

**NOTE** On plastic maximum paint adhesion and durability is achieved in 5-7 days.

### CLEAN UP

Wipe off tip before storing. Clean up wet paint with soap and water. Throw away empty can in trash pickup. Do not burn or place in home trash compactor.

### CLOGGING

If valve clogs, twist and pull off spray tip and rinse it in a warm soapy water. Do not stick pin or other object into the stem.



**RUST-OLEUM® LOW ODOR  
SPRAY PAINT**

**PHYSICAL PROPERTIES**

		<b>WATER-BASED SPRAY FINISHES</b>
<b>Resin Type</b>		Alkyd
<b>Pigment Type</b>		Varies with color
<b>MIR</b>		Matte - 0.80 MAX Gloss – 0.95 MAX
<b>Fill Weight</b>		11 ounces
<b>Recommended Dry Film Thickness (DFT) Per Coat</b>		0.17 – 0.35mils (4.3 - 8.6µ)
<b>Practical Coverage at Recommended DFT (assumes 15% material loss)</b>		10 - 13 sq. ft./can (0.92-1.2 m <sup>2</sup> /can)
<b>Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity</b>	<b>Touch</b>	1 hour
	<b>Handle</b>	2 - 4 hours
	<b>Recoat</b>	Anytime
<b>Dry Heat Resistance</b>		200°F (93°C)
<b>Shelf Life</b>		2 years
<b>Flash Point</b>		-42°F (-104°C)
<b>Safety Information</b>		For additional information, see SDS

Calculated values are shown and may vary from the actual manufactured material.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.