

**Features**

- Solid brass body
- Ceramic disk cartridge
- Single lever handle
- 180 degree swivel spout
- Installation in a 1-3/8" hole
- 1-1/2" maximum deck thickness
- High arc flexible steel spring spout with pull-down spray head
- Single function brass pull-down spray head - aerated spray
- Quick release support arm secures spray head when not in use
- 1.8 gpm max. (6.8L/min) @ 60psi - saves 20% more water
- Flexible supply lines with 3/8" compression fittings

**Optional Accessories**

- T3600 soap dispenser.

**Warranty**

- Lifetime Limited Warranty for residential use
- 5 Year Limited Warranty for commercial use



**Specified Model**

Model	<b>T3550</b>
Faucet Height	21 1/16" (535 mm)
Spout Reach	7 7/8" (200 mm)
Deck to Aerator	8 1/2" (216 mm)
Flow Rate	1.8 gpm max (6.8L/min) @ 60 psi
Shipping Weight	9 lbs.
Material	brass construction
Installation	deck mount, single hole

**To Be Specified:**

	Finish
<input type="checkbox"/>	PC Polished Chrome
<input type="checkbox"/>	LS Luxe Stainless

**Codes/Standards**

Certified to CUPC  
 Certified to AB1953  
 Certified to NSF/ANSI 61  
 Complies with Federal Lead Plumbing Law as certified with IAMPO R&T inc.  
 ADA compliant for lever handle



**Notes**

Install this product according to the installation instructions.

