

# Safety Data Sheet

# 1. Identification

Product Information. 521014 & 521015

Product Name: Totalboat Spray Thinner 101 Quart & Gallon

Recommended Use. Paints

Uses advised against. Read label instructions and SDS

Supplier. TOTALBOAT LLC

17 Peckham Drive

Bristol, Rhode Island 02809

1-800-497-0010

Emergency telephone number. Infotrac: +1-800-535-5053 USA

Infotrac: +1 352-323-3500 ex-USA

24 hrs./day, 7 days/week

# 2. Hazards Identification

#### GHS Classification in accordance with 29 CFR 1910.1200

Acute Toxicity, Inhalation, category 4
Aspiration Hazard, category 1
Carcinogenicity, category 1A
Flammable Liquid, category 2
Germ Cell Mutagenicity, category 1B
Reproductive Toxicity, category 2
Skin Irritation, category 2

STOT, repeated exposure, category 2

## **GHS Pictograms**







## Signal Word

Danger

## **Unknown Acute Toxicity**

6.3% of the mixture consists of ingredient(s) of unknown acute toxicity

# HAZARD STATEMENTS

Highly flammable liquid and vapour.

May be fatal if swallowed and enters airways.

Causes skin irritation.

Harmful if inhaled.

May cause genetic defects.

May cause cancer.

Suspected of damaging fertility or the unborn child.

May cause damage to organs through prolonged or repeated exposure.

## Precautionary Statements - Prevention.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/ vapors/spray.

Wash face and hands and any exposed skin thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection

#### Precautionary Statements - Response.

If swallowed: Immediately call a poison center/doctor.

If on skin: Wash with plenty of water.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If inhaled: Remove person to fresh air and keep comfortable for breathing.

If exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Specific treatment (If applicable, see label for any additional instructions).

Do NOT induce vomiting.

If skin irritation occurs: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

In case of fire: Use CO<sub>2</sub> dry chemical or foam to extinguish.

## Precautionary Statements - Storage.

Store in a well-ventilated place. Keep cool.

Store locked up.

## Precautionary Statements - Disposal.

Dispose of contents in accordance with local/regional/national/international regulations.

# 3. Composition/Information on Ingredients

Chemical Name	CAS-No.	<u>Wt. %</u>
Xylene	1330-20-7	50-75
Ethyl Benzene	100-41-4	10-25
Toluene	108-88-3	2.5-10
Naphthalene	91-20-3	1.0-2.5
1,2,4-TRIMETHYLBENZENE	95-63-6	1.0-2.5
Benzene, (1-methylethyl)-	98-82-8	1.0-2.5
Nonane	111-84-2	1.0-2.5
Trimethylbenzene, mixed isomers	25551-13-7	1.0-2.5
Benzene	71-43-2	0.1-1.0

The exact percentage (concentration) of composition has been withheld as a trade secret.

# 4. First-aid Measures

# Description of first-aid measures.

## General advice.

Move victim to a safe isolated area. When symptoms persist or in all cases of doubt seek medical advice. Call a poison control center or doctor for treatment advice.

#### Inhalation.

Move to fresh air. Apply artificial respiration if victim is not breathing. Call a poison control center or doctor for treatment advice.

## Skin contact.

Wash off immediately with soap and plenty of water. Remove all contaminated clothes and shoes. Remove and wash contaminated clothing before re-use. Call a poison control center or doctor for treatment advice.

#### Eve contact.

Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Call a poison control center or doctor for treatment advice.

#### Ingestion.

Do not induce vomiting unless directed to do so by a physician or poison control center. Never give anything by mouth to an unconscious person. If swallowed, call a poison control center or doctor immediately.

#### Symptoms.

See Section 2 and Section 11, Toxicological effects for description of potential symptoms.

# Notes to physician.

Treat symptomatically.

# 5. Fire-fighting Measures

#### Extinguishing media.

## Suitable extinguishing media.

Use:. Dry powder. Alcohol-resistant foam. Carbon dioxide (CO<sub>2</sub>). Water may be used to cool and prevent the rupture of containers that are exposed to the heat from a fire.

# Extinguishing media which shall not be used for safety reasons.

Water may be unsuitable for extinguishing fires.

#### Special hazards arising from the substance or mixture.

Vapors may travel to areas away from work site before igniting/flashing back to vapor source. Thermal decomposition can lead to release of irritating and toxic gases and vapors. Most vapors are heavier than air. Vapors may spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapors may travel to source of ignition and flash back. Air/vapor mixtures may explode when ignited. Containers may explode when heated.

#### Advice for firefighters.

Evacuate personnel to safe areas. As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## Accidental Release Measures

# Personal precautions, protective equipment and emergency procedures.

## Personal precautions.

Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas. All equipment used when handling the product must be grounded. Eliminate all ignition sources (no smoking, flares, sparks or flames in immediate area). Wear protective gloves/clothing and eye/face protection. Stop all work that requires a naked flame, stop all vehicles, stop all machines and equipment that may cause sparks or flames. Do not breathe vapors or spray mist. Avoid exceeding of the given occupational exposure limits (see section 8). Thoroughly decontaminate all protective equipment after use.

#### Advice for emergency responders.

Refer to protective measures listed in sections 7 and 8. Use personal protection recommended in Section 8.

## Environmental precautions.

Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent entry into waterways, sewers, basements or confined areas. See Section 12 for additional Ecological information.

# Methods and materials for containment and cleaning up.

#### Methods for Containment.

Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Prevent further leakage or spillage if safe to do so. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly. Ground and bond containers when transferring material. Take precautionary measures against static discharges. Use personal protective equipment. Remove all sources of ignition.

# Methods for cleaning up.

Prevent further leakage or spillage if safe to do so. Keep away from open flames, hot surfaces and sources of ignition. Keep in suitable and closed containers for disposal. All equipment used when handling the product must be grounded. Keep combustibles (wood, paper, oil, etc) away from spilled material. Ventilate the area. Use personal protective equipment as required. Shut off ignition sources; including electrical equipment and flames. Clean contaminated objects and areas thoroughly while observing environmental regulations. Never return spills in original containers for re-use.

# Reference to other sections.

See section 8 for more information.

# 7. Handling and Storage

# Conditions for safe storage, including any incompatibilities.

## Advice on safe handling.

Avoid contact with skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice. Keep away from open flames, hot surfaces and sources of ignition. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose container to heat, flame, sparks, static electricity, or other sources of ignition. Wash hands before breaks and immediately after handling the product. All equipment used when handling the product must be grounded. Take precautionary measures against static discharges. Do not breathe vapors or spray mist. Use according to package label instructions. Ground and bond containers when transferring material.

#### Hygiene measures.

Handle in accordance with good industrial hygiene and safety practice for diagnostics. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing before re-use. Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

## Storage Conditions.

Keep container closed when not in use. Keep in properly labeled containers. Keep containers tightly closed in a dry, cool and well-ventilated place. Store in accordance with local regulations. Keep from freezing. Keep away from food, drink and animal feedingstuffs. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

# 8. Exposure Controls/Personal Protection

Ingredients with Occupational Exposure Limits

Chemical Name	ACGIH TLV-TWA	ACGIH-TLV STEL	OSHA PEL-TWA	OSHA PEL-CEILING
Xylene	100 ppm	150 ppm	100 ppm	N.E.
Ethyl Benzene	20 ppm	N.E.	100 ppm	N.E.
Toluene	20 ppm	N.E.	200 ppm	300 ppm
Naphthalene	10 ppm	N.E.	10 ppm	N.E.
Benzene, (1-methylethyl)-	5 ppm	N.E.	50 ppm	N.E.
Nonane	200 ppm	N.E.	N.E.	N.E.
Trimethylbenzene, mixed isomers	25 ppm	N.E.	N.E.	N.E.
Benzene	0.5 ppm	2.5 ppm	10 ppm	25 ppm

TLV = Threshold Limit Value TWA = Time Weighted Average PEL = Permissible Exposure Limit STEL = Short-Term Exposure Limit N.E. = Not Established

#### **Engineering Measures.**

Ensure adequate ventilation, especially in confined areas. Apply technical measures to comply with the occupational exposure limits.

## Personal protective equipment.

#### Eye/Face Protection.

If splashes are likely to occur, wear:. Face-shield. Safety glasses with side-shields. Tightly fitting safety goggles.

# Skin and body protection.

Use: Long sleeved clothing. Protective shoes or boots. Solvent-resistant gloves. Solvent-resistant apron and boots. Wear impervious gloves and/or clothing if needed to prevent contact with the material. Gloves must be inspected prior to use. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. Remove and wash contaminated clothing before re-use.

# Respiratory protection.

In case of inadequate ventilation wear respiratory protection. If exposure limits are exceeded or irritation is experienced, respiratory protection should be worn. Respiratory protection must be provided in accordance with current local regulations.

# 9. Physical and chemical properties.

## Information on basic physical and chemical properties.

Physical state Liquid

Appearance No Information

**Color** Clear

Odor Aromatic Hydrocarbons

Odor ThresholdNo InformationpHNo InformationMelting/freezing point., °C (°F)No InformationFlash Point., °C (°F)4 (39.20)

Boiling point/boiling range., °C (°F) 111 - 218 (231.8 - 424.4) Evaporation rate No Information Available

Explosive properties.No InformationVapor pressure.No InformationVapor density.No Information

Specific Gravity. (g/cm<sup>3</sup>) 0.835

Water solubility.

Partition coefficient.

Autoignition temperature.,°C

Decomposition Temperature °C.

Viscosity, kinematic.

No Information

No Information

No Information

viscosity, kinematic.

< 20 mm2/s

Other information.

Volatile organic compounds (VOC) content. 832 g/L Density, lb/gal 6.950

# 10. Stability and Reactivity

#### Reactivity.

Stable under normal conditions.

# Chemical stability.

Stable under recommended storage conditions.

#### Possibility of hazardous reactions.

None known based on information supplied.

## Conditions to Avoid.

Heat (temperatures above flash point), sparks, ignition points, flames, static electricity. Keep away from heat and sources of ignition. Do not freeze.

#### **Incompatible Materials.**

None known based on information supplied.

## **Hazardous Decomposition Products.**

Thermal decomposition can lead to release of irritating gases and vapours. Possible formation of carbon oxides, nitrogen oxides, and hazardous organic compounds.

# 11. Toxicological Information

# Information on toxicological effects.

Acute toxicity.

**Product Information** 

No Information

The following values are calculated based on chapter 3.1 of the GHS document.

ATEmix (oral) 3,371.5 mg/kg
ATEmix (dermal) 5,479.5 mg/kg
ATEmix (inhalation - dust/mist) 1.64 mg/l

Component Information.

CAS-No.Chemical NameLD50 OralLD50 DermalLC50 Inhalation1330-20-7Xylene3500 mg/kg Rat>4350 mg/kg29.08 mg/L Rat (Vapor)<br/>Rabbit

100-41-4	Ethyl Benzene	3500 mg/kg Rat	15400 mg/kg Rabbit	NA (Dust)
108-88-3	Toluene	2600 mg/kg Rat	12000 mg/kg Rabbit	12.5 mg/L Rat (Vapor)
91-20-3	Naphthalene	1110 mg/kg Rat	2002 mg/kg Rat	N.I.
95-63-6	1,2,4-TRIMETHYLBENZENE	3280 mg/kg Rat	>3160 mg/kg Rabbit	18 mg/L Rat (Vapor)
98-82-8	Benzene, (1-methylethyl)-	1400 mg/kg Rat	1474 mg/kg Rabbit	>3577 ppm Rat (Gas/Mist)
111-84-2	Nonane	N.I.	N.I.	3200 ppm Rat (Gas/Mist)
25551-13-7	Trimethylbenzene, mixed isomers	8970 mg/kg Rat	N.I.	N.I.
71-43-2	Benzene	810 mg/kg Rat	>8200 mg/kg Rabbit	44.66 mg/L Rat (Vapor)

N.I. = No Information

Skin corrosion/irritation.

SKIN IRRITANT.

Eye damage/irritation.

No Information

Respiratory or skin sensitization.

No Information

Ingestion.

May be harmful if swallowed.

Germ cell mutagenicity.

No Information

Carcinogenicity.

No Information

CAS-No.	Chemical Name	<u>IARC</u>	<u>NTP</u>	<u>OSHA</u>
1330-20-7	Xylene	IARC Group 3	-	-
100-41-4	Ethyl Benzene	IARC Group 2B	-	-
108-88-3	Toluene	IARC Group 3	-	-
91-20-3	Naphthalene	Group 2B	NTP Reasonally Anticipated to be Human Carcinogen	-
98-82-8	Benzene, (1-methylethyl)-	IARC Group 2B	NTP Reasonally Anticipated to be Human Carcinogen	-
71-43-2	Benzene	IARC Group 1	NTP Known Human Carcinogen	Present

# Reproductive toxicity.

No Information

Specific target organ systemic toxicity (single exposure).

No Information

Specific target organ systemic toxicity (repeated exposure).

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard.

No Information

Primary Route(s) of Entry

No Information

# 12. Ecological Information

# Toxicity.

0.00% of the mixture consists of ingredient(s) of unknown aquatic toxicity **Ecotoxicity effects.** 

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia and other aquatic invertebrates
Xylene 1330-20-7	-	LC50 96 h Pimephales promelas 13.4 mg/L, LC50 96 h Oncorhynchus mykiss 2.661 - 4.093 mg/L, LC50 96 h Oncorhynchus mykiss 13.5 - 17.3 mg/L, LC50 96 h Lepomis macrochirus 13.1 - 16.5 mg/L, LC50 96 h Lepomis macrochirus 19 mg/L, LC50 96 h Lepomis macrochirus 7.711 - 9.591 mg/L, LC50 96 h Pimephales promelas 23.53 - 29.97 mg/L, LC50 96 h Cyprinus carpio 780 mg/L, LC50 96 h Cyprinus carpio >780 mg/L, LC50 96 h Poecilia reticulata 30.26 - 40.	EC50 48 h water flea 3.82 mg/L, LC50 48 h Gammarus lacustris 0.6 mg/L
Ethyl Benzene 100-41-4	EC50 72 h Pseudokirchneriella subcapitata 4.6 mg/L, EC50 96 h Pseudokirchneriella subcapitata >438 mg/L, EC50 72 h Pseudokirchneriella subcapitata 2.6 - 11.3 mg/L, EC50 96 h Pseudokirchneriella subcapitata 1.7 - 7.6 mg/L	LC50 96 h Oncorhynchus mykiss 11.0 - 18.0 mg/L, LC50 96 h Oncorhynchus mykiss 4.2 mg/L, LC50 96 h Pimephales promelas 7.55 - 11 mg/L, LC50 96 h Lepomis macrochirus 32 mg/L, LC50 96 h Pimephales promelas 9.1 - 15.6 mg/L, LC50 96 h Poecilia reticulata 9.6 mg/L	EC50 48 h Daphnia magna 1.8 - 2.4 mg/L
Toluene 108-88-3	EC50 96 h Pseudokirchneriella subcapitata >433 mg/L, EC50 72 h Pseudokirchneriella subcapitata 12.5 mg/L	LC50 96 h Pimephales promelas 15.22 - 19.05 mg/L, LC50 96 h Pimephales promelas 12.6 mg/L, LC50 96 h Oncorhynchus mykiss 5.89 - 7.81 mg/L, LC50 96 h Oncorhynchus mykiss 14.1 - 17.16 mg/L, LC50 96 h Oncorhynchus mykiss 5.8 mg/L, LC50 96 h Lepomis macrochirus 11.0 - 15.0 mg/L, LC50 96 h Oryzias latipes 54 mg/L, LC50 96 h Poecilia reticulata 28.2 mg/L, LC50 96 h Poecilia reticulata 50.87 - 70.34 mg/L	EC50 48 h Daphnia magna 5.46 9.83 mg/L, EC50 48 h Daphnia magna 11.5 mg/L
Naphthalene 91-20-3	-	0.91 - 2.82 mg/L, LC50 96 h Pimephales promelas 1.99 mg/L, LC50 96 h Lepomis macrochirus 31.0265 mg/L	LC50 48 h Daphnia magna 2.16 mg/L, EC50 48 h Daphnia magna 1.96 mg/L, EC50 48 h Daphnia magna 1.09 - 3.4 mg/L
1,2,4-TRIMETHYLBENZENE 95-63-6	-	LC50 96 h Pimephales promelas 7.19 - 8.28 mg/L	EC50 48 h Daphnia magna 6.14 mg/L
Benzene, (1-methylethyl)- 98-82-8	EC50 72 h Pseudokirchneriella subcapitata 2.6 mg/L	LC50 96 h Pimephales promelas 6.04 - 6.61 mg/L, LC50 96 h Oncorhynchus mykiss 4.8 mg/L, LC50 96 h Oncorhynchus mykiss 2.7 mg/L, LC50 96 h Poecilia reticulata 5.1 mg/L	EC50 48 h Daphnia magna 0.6
Trimethylbenzene, mixed isomers 25551-13-7	-	LC50 96 h Pimephales promelas 7.72 mg/L	-

Benzene 71-43-2	EC50 72 h Pseudokirchneriella subcapitata 29 mg/L	LC50 96 h Pimephales promelas 10.7 - 14.7 mg/L, LC50 96 h Oncorhynchus mykiss 5.3 mg/L, LC50 96 h Lepomis macrochirus 22.49 mg/L, LC50 96 h Poecilia reticulata 28.6 mg/L, LC50 96 h Pimephales promelas 22330 - 41160 μg/L, LC50 96 h Lepomis macrochirus 70000 - 142000 μg/L	
--------------------	--	--	--

## Persistence and degradability.

No data are available on the product itself.

## Bioaccumulative potential.

Discharge into the environment must be avoided.

CAS-No.	Chemical Name	log POW
1330-20-7	Xylene	2.77 - 3.15
100-41-4	Ethyl Benzene	3.2
108-88-3	Toluene	2.7
91-20-3	Naphthalene	3.6
95-63-6	1,2,4-TRIMETHYLBENZENE	3.63
98-82-8	Benzene, (1-methylethyl)-	3.7
71-43-2	Benzene	2.1

# Mobility in soil.

No information

#### Other adverse effects.

No information

# 13. Disposal Considerations

# Waste Disposal Guidance.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Empty containers should be taken to an approved waste handling site for recycling or disposal.

# 14. Transport Information

# **DOT**

Shipping Name: Paint Hazard Class: 3
UN/NA Number: 1263
Packing Group: II

Additional Information: LTD QTY EXCEPTION: This product may be reclassified as "limited quantity" per 49 CFR 173.150

(b)(2) and 49 CFR 172 Special Provision 149 and thus is exempt from labeling requirements when

transported within the U.S. by motor vehicle or rail only.

## **IMDG**

Proper Shipping Name: Paint Hazard Class: 3
UN Number: 1263
Packing Group: II

# **IATA**

Proper Shipping Name: UN1263, Paint

Hazard Class: 3
Packing Group: ||

# 15. Regulatory Information

# International Inventories:

**TSCA** Complies DSL Complies DSL/NDSL Complies **EINECS/ELINCS** Complies **ENCS** Complies **IECSC** Complies **KECI** Complies **PICCS** Complies Complies AICS **NZIoC** Complies

TCSI

TSCA United States Toxic Substances Control Act Section 8(b) Inventory.

**DSL** Canadian Domestic Substances List.

DSL/NDSL Canadian Domestic Substances List/Canadian Non-Domestic Substances List

**EINECS/ELINCS** European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances.

ENCS Japan Existing and New Chemical Substances.

IECSC China Inventory of Existing Chemical Substances.

KECL Korean Existing and Evaluated Chemical Substances

PICCS Philippines Inventory of Chemicals and Chemical Substances.

AICS Australian Inventory of Chemical Substances.

NZIOC New Zealand Inventory of Chemicals.

TCSI Taiwan Chemical Substance Inventory

# U.S. Federal Regulations:

# **SARA SECTION 313:**

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372: .

Chemical Name	<u>CAS-No.</u>	Weight Percent
Xylene	1330-20-7	50-75
Ethyl Benzene	100-41-4	10-25
Toluene	108-88-3	2.5-10
Naphthalene	91-20-3	1.0-2.5
Benzene, (1-methylethyl)-	98-82-8	1.0-2.5
Benzene	71-43-2	0.1-1.0

## **TOXIC SUBSTANCES CONTROL ACT 12(b):**

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:.

Chemical NameCAS-No.Nonane111-84-2

#### ADDITIONAL INFORMATION

Additional Information - Sxn 15: No Information

# **CALIFORNIA PROPOSITION 65 CARCINOGENS**



# WARNING

Warning: The following ingredients present in the product are known to the state of California to cause Cancer:.

Chemical NameCAS-No.Ethyl Benzene100-41-4Naphthalene91-20-3

Benzene, (1-methylethyl)- 98-82-8 Benzene 71-43-2

# **CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS**



# WARNING

Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

 Chemical Name
 CAS-No.

 Toluene
 108-88-3

 Benzene
 71-43-2

# 16. Other Information

Revision Date: 1/18/2022 Supersedes Date: 1/11/2022

**Reason for revision:** Substance and/or Product Properties Changed in Section(s):

01 - Product Information

Revision Statement(s) Changed

Datasheet produced by: Regulatory Department

**HMIS Ratings:** 

Health:	2*	Flammability:	4	Physical Hazard:	0	Personal Protection:	Χ
NFPA Ratings:							
Health:	2	Flammability:	4	Instability:	0	Physical & Chemical:	

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined, N.I. - No Information

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.