

## Print Specifications:

⇔ .125" Bleeds ⇔ .09375" Copy Safty to Trim ⇔ Minimum Point Size For One Color Type, 4-Point ⇔ Tint Match Type ( More than One Color, No Background ) 7-Point

- ➡ Minimum Point Size For Type Reversed Out of 1-Color, 6-Point
  ➡ Minimum Point Size For Type Reversed Out of More than 1-Color, 8-Point
  ➡ UPC Symbols: 3.5 Thousandths Bar Width Reduction No Smaller than 85%

## **Print Specifications:**

- ➡ .125" Bleeds
  ➡ .09375" Copy Safty to Trim
  ➡ Minimum Point Size For One Color Type, 4-Point
  ➡ Tint Match Type ( More than One Color, No Background ) 7-Point

m	<b>&gt;</b>			
m	-			
			↑	
ere <sup>6</sup> , and most foreign cars and light irections or further information. Helps seals. Formulated with high quality oil ied, shrunken and hardened seals. Use oid future leaks. Keeps power steering ipproved power steering fluid. if leak persists after initial use. If leak, ical problem may exist and you should ring due to fluid loss usually means that ignificant amount of fluid. The typical or. refill may not bring your system to steering reservoir to level specified cfill, as system damage may occur. sering fluid. After using product, always and water. twe Harm - www.P65Warnings.ca.gov etroleum oils (mixture), alkoxy sulfolane 8-16-1), zinc compounds (proprietary), I. In case of eye contact: flush thoroughly with soap and water. If irritation develops wallowed: do not induce vomiting. Call a hrough the skin is a medical emergency. ely from under the skin. Seek immediate <b>OF CHILDREN.</b>		120.65mm	126.65mm	
			<u></u>	
			¥	

- ➡ Minimum Point Size For Type Reversed Out of 1-Color, 6-Point
  ➡ Minimum Point Size For Type Reversed Out of More than 1-Color, 8-Point
  ➡ UPC Symbols: 3.5 Thousandths Bar Width Reduction No Smaller than 85%