TRA001

2400W Dual Mode Precision Plunge Router

Powerful 2400W / 3-1/4hp electronically controlled motor. Single spanner 'above table' cutter changing. Automatic shaft lock and power lock-off during cutter change mode. Fast plunge depth adjustment with winder handle and fine depth adjustment with micro winder. Quick switching to conventional plunge mode. Removable plunge spring for easy lifting and adjustment. Effective dust port.



Product Specification

Product Height	12 1/4"
Product Length	7 1/8"
Product Width	11 3/4"
Product Weight	14.33lb
Power	3-1/4hp / 15A
Voltage	110-120V 60Hz
No Load Speed	8000-21000rpm
Speed Maintenance Under Load	8000 - 21,000rpm
Electrical Class	Class II double insulated
Sound Pressure LP	89.8dB
Sound Power LW	100.8dB
Soft Start	Yes
AC or DC Powered	AC
Depth Adjustment	Micro winder
Electronic Speed Maintenance	Yes
General Product Safety QC Question 01	Are there any sharp edges? If yes please give details
General Product Safety QC Question 02	Does the product give you any safety concern? If yes please give details
General Product Safety QC Question 03	Function - Does the product do what it is intended to do? If no please give details
General Product Safety QC Question 04	Size - Is the product size and shape it was specified to be? If no please give details
General Product Safety QC Question 05	Full contents - Are all the parts present? If no, please specify what's missing
What's in the box - 01	1 x Table height winder
What's in the box - 02	1 x Collet 1/2"
What's in the box - 03	1 x Collet 1/4"
What's in the box - 04	1 x Collet wrench
What's in the box - 05	1 x Multi-function fence
Instruction Manual Included	Yes
IP Rating	IPX0
Material - Storage Case	Aluminium
Plunge Range	0 - 2 3/5"
Power On Indicator	Neon
Safety Power Switch	Yes
Weighted Vibration	2.21m/s ²
Compatible With 01	DCA300
Compatible With 02	RTA300
Compatible With 03	FJA300
Compatible With 04	AJA150
Compatible With 05	TGA001
Compatible With 06	TGA250
Compatible With 07	TWX7RT001
Compatible With 08	TRTA001
Thread Size	Base Plate Mounting Bolts = 1/4" UNC, Other Base threads : M6
Included Accessory - 01	Table height winder
Included Accessory - 02	Multi-function fence
Included Accessory - 03	1/4" collet
Included Accessory - 04	1/2" collet
Included Accessory - 05	N/A
Included Accessory - 06	na



Component Specification

Capacitor - Class	N/A
Capacitor - Factory Model Number	N/A
Capacitor - Style	N/A
Capacitor - Type	N/A
Fuse - Class	N/A
Cord - Length	126"
Cord - Factory Model Number	SJ
Cord - Style	UL/CSA
Cord - Type	14/2 AWG
Motor - Windings - Stator	Copper
Motor - Windings - Armature	Copper
Motor - Style	AC110-120V~, 50/60Hz
Motor - Type	AC Series
Plug - Style	UL/CSA
Switch - Factory Model Number	Marquardt GMBH 1935, 1835
Switch - Style	UL/CSA
Switch - Type	110-120V
PCB - Type	130°C
PCB - Style	V-0
PCB - Factory Model Number	KENT PRINTED CIRCUIT BOARD CO., LTD
Speed Control Trigger / Dial - Style	Dial
Speed Control Trigger / Dial - Type	Dial
Spindle / Shank Type	MOF Type Collet
Vendor Model Number	68101
Factory Model Number	68101