

KOHLER® Roughing-In

K-1224, K-1224-L, K-1224-R
MARIPOSA®
BATH WHIRLPOOL

Product Information

Applicable product:	
Bath whirlpool – drop-in	K-1224
Bath whirlpool with integral flange and left drain – 3-wall alcove	K-1224-L
Bath whirlpool with integral flange and right drain – 3-wall alcove	K-1224-R

Fixture*:	
Bathing well:	
Basin area, bottom	48" (1219 mm) x 24" (610 mm)
Basin area, top	59" (1499 mm) x 30" (762 mm)
Weight	110 lbs (49.9 kg)
To overflow:	
Water depth	14" (356 mm)
Capacity	67 gal (253.6 L)
* Approximate measurements for comparison only.	

Drop-in cutout:	64" (1626 mm) x 34" (864 mm)
-----------------	------------------------------

Pump:	V	Hz	A
1-speed	120	60	7.5

Required Electrical Service

Dedicated circuit required, protected with a Class A Ground-Fault Circuit-Interrupter (GFCI).	
Pump/control	120 V, 15A, 60 Hz
Locate the outlet behind the whirlpool and within 24" (610 mm) of the pump	

Installation Notes

Install this product according to the installation guide.

Floor support under whirlpool must provide for a minimum of 48 lbs/square foot (232 kg/square meter).

If installing a rim-mount faucet, make sure there is no interference with the drain overflow and circulating system before drilling any holes. If installing a spout on the faucet deck, consult local and national codes for minimum air gap requirements.

The apron must be installed before the finished floor and wall materials are installed.

Fixture conforms to CSA B45.5/IAPMO Z124. All dimensions are nominal.

