SHANNON 6030

STUDIO COLLECTION



PVC SYSTEMS INCLUDE:

- 6 Fully directional adjustable PVC jets
- Anti-vortex safety suction
- Color matched system trim
- Rigid PVC piping
- Self draining pump and system
- Air switch control
- 1.25 HP single speed pump
- Requires 120 V 15 Amp Dedicated GFCI



OPTIONS: (MORE INFORMATION AVAILABLE ON OUR WEBSITE)

- Custom Jet and Pump Location
- Hydro Coat
- Hydro Express Quick Ship
- HydrOzone System

- In-line Heater
- Jet Plating
- Tile Flanges
- Cable Waste & Overflow
- Integral Waste & Overflow

STANDARD ELECTRICAL REQUIREMENTS:

- Whirlpool System | One 20 Amp Dedicated Circuit
- Thermal Air System I One 15 Amp Dedicated Circuit
- In-line Heater (600 or 1500 Watts) | One 15 Amp Dedicated Circuit

All electrical components come standard at 115 volts

All electrical circuits must be GFCI protected



SHANNON 6030

STUDIO COLLECTION



As Shown:

Whirlpool option with standard jet location

FEATURES SHOWN:

- Jets
- Overflow location

ALSO AVAILABLE:

- Soaking tub only
- Whirlpool
- Thermal Air

WATER CAPACITY:

70 Gallons

WEIGHT:

120-160 Pounds

3-Wall Installation Dimensions:


Opening (L)ength - 60" Opening (W)idth - 30"

Top of Ledger- 20.75"



ACRYLIC TUB

- Model comes with integral tile flange and skirt
- Extra thick reinforced fiberglass
- Pre-wired pump on pump platform (standard pump location only)
- Integral E-Z level platform facilitates installation
- Tub must be set in a mortar base



CODES AND COMPLIANCES

Massachusetts code File no: P1-0614-491











Back of tile flange to center of overflow 15" RIGHT HAND ONLY

19.75

30 18

15.25



