



Organic Concrete Cleaner

AN ORGANIC ACID REPLACEMENT CLEANER – ZERO VOC



COVERAGE:

1 gallon (3.8 Liters) covers approximately 250 sq. ft. to 400 sq.ft. depending on surface

PACKAGING:

Available in 1 gallon jugs, 5 gallon pails and 55 gallon drums.

STORAGE:

1. Store in a cool, dry location.
2. Store out of direct sunlight.
3. Protect pails and jugs from weather and other damage.
4. Store at a temperature between 40°F (4°C) and 90°F (32°C).

SHELF LIFE:

10 years

COLOR:

Green

Visit us online:
ClassicCoatingsSystems.com

See Our Website Gallery to
 Get Inspired and
 View How-to Videos & SDS

DESCRIPTION

Classic Organic Concrete Cleaner is made with our state-of-the-art acid replacement technology that contains Zero VOC and a low pH salt that is used to replace traditional acid. Organic Concrete Cleaner makes your job easier by removing the hassle of neutralizing before applying. It is four to ten times more effective than citric and glycolic acid and four to five times more effective than phosphoric acid when dissolving calcium carbonate. It is classified as a mild skin irritant and non-corrosive to skin and mild steel. It has a refreshingly mild citrus scent and is approved by the US EPA as a non-food inert ingredient in bio-degradable applications. For use on pool decks, concrete, stone, brick, grout joints and more. It may be used for interior or exterior applications in high traffic areas within a wide range of climates. It is environmentally safe and cleans up easily with water. **New concrete must cure for 28 days.**

ADVANTAGES

Non-Hazardous and Non-Corrosive
Waterborne – Zero VOC
Non-Corrosive to skin and mild steel
Bio-Degradable & Environmentally safe
Safe to use around lawn and plants
Etch concrete and rinses easily
No need for sandblasting
Removes grout haze cement residue, grease, oil, and efflorescence
Leaves a sandblasted finished look

LIMITATIONS

Keep container closed at all times when not in use
Application temperature should be between 45° F and 100° F
Must rinse well with water
Not freeze thaw

* We highly recommended testing a small area before use

TYPICAL USAGE

- Pool Decks
- Driveways
- Garage Floors
- Work Shops
- Restoration projects
- Concrete floors
- Bricks
- Stone
- New and old concrete side walks

REVISED: January 2021

Classic Coatings Systems • 255 Citation Circle, Corona, CA 92878

© 2015 Classic Coatings Systems Inc. All rights reserved.



Organic Concrete Cleaner

AN ORGANIC ACID REPLACEMENT CLEANER - ZERO VOC

PREPARATION

- ✓ **READ SDS BEFORE HANDLING & APPLICATION**
- ✓ Highly recommended to test a small inconspicuous area first.
- ✓ **TURN OFF SPRINKLERS FOR TWO DAYS PRIOR TO AND AFTER.**
- ✓ Always protect neighboring surfaces including wood, carpet, metal, landscaping and other non-masonry surfaces.
- ✓ **Caution: Surface is slippery when wet.**
- ✓ New concrete must cure for 28 days before sealer is apply.

INSTALLATION

1. Prepare surface by carefully and thoroughly removing any laitance, grease, and foreign matter.
2. Apply the first coat with a saturated brush , mop, or a low pressure garden type sprayer.
3. Power wash with 2,700 psi and rinse well with water.

NOTE: It is **HIGHLY** recommended that on-site samples and mock-ups be made by the applicator. Representative test sections must be produced for the Owner's approval in writing and to ensure applicators are familiar with the product and installation procedures.

PHYSICAL CHARACTERISTICS & TECHNICAL DATA

PRODUCT AVAILABILITY AND TECHNICAL ASSISTANCE

Technical assistance and information is available by calling:

(951) 279-2600

www.classiccoatingsystems.com

Disclaimer: The information and recommendations contained herein are based upon data believed to be correct; however, no guarantee or warranty of any kind, express or implied is made with respect to the accuracy of the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects, which may be caused by exposure to our products. Customers and users of this product must comply with all applicable health and safety laws, regulations and orders.

HANDLING PRECAUTIONS:

Use only with adequate ventilation. An appropriate cartridge type respirator must be used during application in confined areas. Avoid contact with skin. Protective gloves, eyewear and clothing are recommended.

PROP 65 WARNING:

Classic Coatings, as a blender of processed material in the State of California, is required by Proposition 65 to warn that one or more of the components contained in the product contain chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. The State of California (Proposition 65) requires this warning in the absence of definitive testing to prove that the defined risks do not exist. We believe this product complies with all other applicable state and federal laws and regulations governing manufacturing, distribution and intended use. User is solely responsible for the legal disposal of this container and/or its contents.

WARRANTY:

Classic Coatings products are warranted for one year after date of purchase. Please refer to the Limited Material warranty for additional clarification. **NOTICE TO BUYER: DISCLAIMER OF WARRANTIES AND LIMITATIONS ON OUR LIABILITY.** We warrant that our products are manufactured to strict quality assurance specifications and that the information supplied by us is accurate to the best of our knowledge. Such information supplied about our products is not a representation or a warranty. It is supplied on the condition that you shall make your own tests to determine the suitability of our product for your particular purpose. Any use or application other than recommended herein is the sole responsibility of the user. Listed physical properties are typical and should not be construed as specifications. **NO WARRANTY IS MADE, EXPRESSED OR IMPLIED, REGARDING SUCH OTHER INFORMATION, THE DATA ON WHICH IT IS BASED, OR THE RESULTS YOU WILL OBTAIN FROM ITS USE. NO WARRANTY IS MADE, EXPRESSED OR IMPLIED, THAT OUR PRODUCT SHALL BE MERCHANTABLE OR THAT OUR PRODUCT SHALL BE FIT FOR ANY PARTICULAR PURPOSE. NO WARRANTY IS MADE**

THAT THE USE OF SUCH INFORMATION OR OUR PRODUCT WILL NOT INFRINGE UPON ANY PATENT. We shall have no liability for incidental or consequential damages, direct or indirect. Our liability is limited to the net selling price of our product or the replacement of our product, at our option. Acceptance of delivery of our product means that you have accepted the terms of this warranty whether or not purchase orders or other documents state terms that vary from this warranty. No representative is authorized to make any representation or warranty or assume any other liability on our behalf with any sale of our products. Our products contain chemicals that may CAUSE SERIOUS PHYSICAL INJURY. BEFORE USING, READ THE MATERIAL SAFETY DATA SHEET & FOLLOW ALL PRECAUTIONS TO PREVENT BODILY HARM.



Strip Away

A ZERO VOC, ENVIRONMENTALLY SAFE PAINT AND SEALER REMOVER



DESCRIPTION

Classic Strip Away is the premium solution for indoor and outdoor coating removal, crafted with sustainability and efficiency in mind. It excels in removing a wide range of industrial coatings, including tough acrylics, paints, lacquer sealers, latex paints, and oil-based enamels. Classic Strip Away showcases unmatched effectiveness across a diverse array of substrates, including concrete, masonry, wood, steel, aluminum, and metal alloys. It is free from methylene chloride, caustics, and other harmful chemicals. Our biodegradable formula ensures a safe working environment without compromising on performance. Unlike competing products, Classic Strip Away is VOC compliant across all 50 states and poses no threat to air quality or ozone depletion. No more having to deal with the mess and hassle of soy-based strippers, as our non-sticky formula streamlines operations and minimizes labor-intensive mechanical stripping methods. You must clean your surface with Classic Organic Concrete Cleaner (CW300) to ensure a ready and open surface post-stripping.

COVERAGE:

1 Gallon: 100-175 sq. ft. depending on application method, coating being removed, and surface conditions.

PACKAGING:

- 1 Gallon
- 5 Gallons
- 55 Gallons

STORAGE:

1. Store in a cool, dry area.
2. Store out of direct sunlight.
3. Protect pails and jugs from freezing weather and other damage.
4. Store at a temperature between 40°F and 90°F.

SHELF LIFE:

3 years (unopened)

Visit our Youtube channel for How-to Videos and our Instagram for inspiration!



@ClassicCoatingSystems



@ClassicCoatingsSystems
@SimpleStains

ADVANTAGES

Environmentally friendly
Doesn't contain caustics or toxic chemicals
Zero VOC - Compliant in all 50 states
Can be used on interior and exterior surfaces
Affordable alternative to mechanical stripping
Non-Flammable & Non-hazardous
Easy to use and cost effective

LIMITATIONS

After using Strip Away, you must clean the surface using (CW300) Organic Concrete Cleaner to degrease and prep your surface
Harmful to vinyl tile, linoleum, synthetics, and PVC pipes
Do not use on asphalt, plastics, or rubber
Highly recommended to test a small area before use
Will not remove silicone based natural penetrating sealers, acid stain, epoxy, or 2 part sealers

TYPICAL USAGE

Classic Strip away is safe for both indoor and outdoor use, which includes, but isn't limited to:

- Concrete
- Masonry
- Paint
- Latex
- Tile Sealers
- Water-based Stains
- Lacquers
- Enamel Paint
- Graffiti Paint
- Acrylics

REVISED: June 18th, 2024

Classic Coatings Systems • 255 Citation Circle, Corona, CA 92878
© 2015 Classic Coatings Systems Inc. All rights reserved.



Strip Away

A ZERO VOC, ENVIRONMENTALLY SAFE PAINT AND SEALER REMOVER

SURFACE PREPARATION

- ✓ **READ SDS BEFORE HANDLING & APPLICATION**
- ✓ Highly recommended to test a small inconspicuous area first.
- ✓ **TURN OFF SPRINKLERS FOR TWO DAYS PRIOR TO AND AFTER.**
- ✓ Always protect neighboring surfaces including wood, carpet, metal, landscaping & other non-masonry surfaces.
- ✓ **Caution:** Surface is slippery when wet.
- ✓ Before you start, wear rubber gloves & safety glasses.
- ✓ New concrete must cure for 28 days before application.

COVERAGE

The approximate coverage for Strip Away is 100-175 sq. ft. per gallon (1 application) depending on surface condition, coating being removed, and application method.

APPLICATION

Classic Strip Away is a ready to use product that's easy to apply using a roller or brush (do not dilute). The product should be applied twice as thick as the coating that is being removed. Do not let Strip Away dry out after application. The coating normally works within 4-6 minutes, but it can be significantly longer for coatings with multiple layers. After stripping, the coating can be removed using a scraper, dry rag, steel wool, Shop Vacuum, or Power Washer. Some floors may require two applications. Wash with a minimum of 3,100 psi pressure washer. After using Strip Away, you must degrease the surface with CW300 Classic Organic Concrete Cleaner then power wash it off with a minimum of 2700 psi. Rinse the surface with a water hose. Coverage rate will vary depending on the substrate and coating thickness. Use caution when walking on the floor as it will be slippery. Allow the surface to dry for 24-48 hours before applying a stain or a sealer.

TECHNICAL SUPPORT

(951) 279-2600

Technical support is available Monday through Friday from 8:00am to 4:00pm PST.

Data sheets are available at:

www.ClassicCoatingsSystems.com

How To Apply videos can be found on our website and on our YouTube channel:

www.youtube.com/@simplestain

HANDLING PRECAUTIONS:

Use only with adequate ventilation. An appropriate cartridge type respirator must be used during application in confined areas. Avoid contact with skin. Protective gloves, eyewear and clothing are recommended.

PROP 65 WARNING:

Classic Coatings Systems, as a blender of processed material in the State of California, is required by Proposition 65 to warn that one or more of the components contained in the product contain chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. The State of California (Proposition 65) requires this warning in the absence of definitive testing to prove that the defined risks do not exist. We believe this product complies with all other applicable state and federal laws and regulations governing manufacturing, distribution and intended use. User is solely responsible for the legal disposal of this container and/or its contents.

WARRANTY:

Classic Coatings Systems products are warranted for one year after date of purchase. Please refer to the Limited Material warranty for additional clarification. **NOTICE TO BUYER: DISCLAIMER OF WARRANTIES AND LIMITATIONS ON OUR LIABILITY.** We warrant that our products are manufactured to strict quality assurance specifications and that the information supplied by us is accurate to the best of our knowledge. Such information supplied about our products is not a representation or a warranty. It is supplied on the condition that you shall make your own tests to determine the suitability of our product for your particular purpose. Any use or application other than recommended herein is the sole responsibility of the user. Listed physical properties are typical and should not be construed as specifications. **NO WARRANTY IS MADE, EXPRESSED OR IMPLIED, REGARDING SUCH OTHER INFORMATION, THE DATA ON WHICH IT IS BASED, OR THE RESULTS YOU WILL OBTAIN FROM ITS USE. NO WARRANTY IS MADE, EXPRESSED OR IMPLIED, THAT OUR PRODUCT SHALL BE MERCHANTABLE OR THAT OUR PRODUCT SHALL BE FIT FOR ANY PARTICULAR PURPOSE. NO WARRANTY IS MADE THAT THE USE**

OF SUCH INFORMATION OR OUR PRODUCT WILL NOT INFRINGE UPON ANY PATENT. We shall have no liability for incidental or consequential damages, direct or indirect. Our liability is limited to the net selling price of our product or the replacement of our product, at our option. Acceptance of delivery of our product means that you have accepted the terms of this warranty whether or not purchase orders or other documents state terms that vary from this warranty. No representative is authorized to make any representation or warranty or assume any other liability on our behalf with any sale of our products. Our products contain chemicals that may CAUSE SERIOUS PHYSICAL INJURY. **BEFORE USING, READ THE MATERIAL SAFETY DATA SHEET & FOLLOW ALL PRECAUTIONS TO PREVENT BODILY HARM.**

Technical assistance and info. is available by calling: (951) 279-2600
www.ClassicCoatingsSystems.com



Matte Water Based Sealer

A FAST DRYING LOW SHEEN WATER BASED ACRYLIC SEALER



DESCRIPTION

Classic Matte Sealer is a clear, single component, water based sealer that is designed to be used over all Classic Stains, polymer modified cement toppings, masonry, pavers, natural flagstone, and brick. It is a waterborne acrylic with low VOC and high solids. It may be used for interior or exterior applications in a wide range of climates. It works as an excellent water repellent, UV stabilizer, and will not yellow. Matte Sealer is formulated primarily as a clear seal for applications over concrete restoration projects and pool deck coatings, but may also be applied as a sand joint stabilizer provided the surface is properly prepared. It is ideal for where a low maintenance and easily cleanable surface is desired. Matte Water Based Sealer is environmentally safe and cleans up easily with soap and water. **Caution: Surface is slippery when wet. New concrete must cure for 28 days.**

COVERAGE:

1 gallon (3.8 Liters) covers approximately 300 sq. ft. to 400 sq. ft. depending on application method and surface conditions

PACKAGING:

1 gallon
5 gallon
55 gallons

STORAGE:

1. Store in a cool, dry location.
2. Store out of direct sunlight.
3. Protect pails and jugs from weather and other damage.
4. Store at a temperature between 40°F (4°C) and 90°F (32°C).

SHELF LIFE:

2 years

COLOR:

Milky white - Dries Clear

Visit us online:

ClassicCoatingsSystems.com

Visit our Youtube channel for How-to Videos and our Instagram for inspiration!



@classiccoatingsystems /classiccoatingsystems @simplestains

ADVANTAGES

Repels water within 24 hours at 77°F
Waterborne: Low VOC <50 g/l, no fumes and low odors
Fast drying & color enhancer Cross-Link & High UV stability
Excellent hot tire pick-up after 7 days
Excellent adhesion and durability
Low cost, easy installation, and low maintenance
Easy to clean with soap and water

LIMITATIONS

May reflect working cracks in substrate
Recommended application temperature should be between 55° F and 95° F
Must be installed over a clean and dry surface
Not freeze thaw. Not for use under water
Surface must not contain any moisture and efflorescence
Never apply adhesives over stained or sealed surfaces as it may cause damage
If using high performance tires we recommend using a 2 part polyurethane sealer

TYPICAL USAGE

- Pool Decks
- Driveways
- Walkways
- Over stained concrete
- Restoration projects
- Architectural toppings
- Concrete floors
- Block walls
- Patios
- Masonry
- Spanish Tile
- Stucco
- Natural Stone

REVISED: March 11th, 2024

Classic Coatings Systems • 255 Citation Circle, Corona, CA 92878

© 2015 Classic Coatings Systems Inc. All rights reserved.



Matte Water Based Sealer

A FAST DRYING LOW SHEEN WATER BASED ACRYLIC SEALER

PREPARATION

- ✓ **READ SDS BEFORE HANDLING & APPLICATION**
- ✓ Highly recommended to test a small inconspicuous area first.
- ✓ **TURN OFF SPRINKLERS FOR TWO DAYS PRIOR TO AND AFTER.**
- ✓ Always protect neighboring surfaces including wood, carpet, metal, landscaping and other non-masonry surfaces.
- ✓ **Caution: Surface is slippery when wet.**
- ✓ New concrete must cure for 28 days before sealer is apply.

INSTALLATION

1. Prepare surface by carefully and thoroughly removing all trace of any foreign matter.
2. Apply 1st coat of sealer by brush, roller, or pump sprayer.
NOTE: System thickness 2-3 wet mils. per coat.
3. After 1- 2 hours, repeat step (2) for the 2nd coat.
4. A 3rd application may be required in high traffic areas. Cure Time at 77°F: Dry to touch in 30 minutes, allow light foot traffic after 12 hours, and full cure in 7 days.

MAINTENANCE

Over time, the sealer may wear down, particularly in areas with high traffic. It is advisable to reapply the sealer to areas where the sealer has worn down.

For interior only: Apply two coats of sealer to protect the undercoat of the sealed surface. May be buffed with a sky blue pad. No more than 3 coats. Use annually if needed.

For exterior only: Clean with water. Improper maintenance will result in wearing out your surface. If this occurs, use Classic Strip Away to remove sealers and stains in order to re-apply desired stain and sealer. Note that Classic Strip Away will remove any coats of sealers and stains on your surface.

PHYSICAL CHARACTERISTICS & TECHNICAL DATA

- Coverage per liquid gallon 300-400 sq ft per gallon
- Abrasion - Excellent
- VOC <50 g/l
- Degree of Gloss – Matte, Low Sheen
- Solids content by weight: 29.40%
- Solids content by volume: 26.40 %

It is HIGHLY recommended that on-site samples and mock-ups be made by the applicator. Representative test sections must be produced for the owner's approval in writing and to ensure that applicators are familiar with the product and installation procedures.

Disclaimer: The information and recommendations contained herein are based upon data believed to be correct; however, no guarantee or warranty of any kind, expressed or implied, is made with respect to the accuracy of the information contained here-in. We accept no responsibility and disclaim all liability for any harmful effects, which may be caused by exposure to our products. Customers and users of this product must comply with all applicable health laws, safety laws, and regulations.

CONTACT INFORMATION

Technical assistance and information is available by calling:

(951) 279-2600

www.classiccoatingsystems.com

HANDLING PRECAUTIONS:

Use only with adequate ventilation. An appropriate cartridge type respirator must be used during application in confined areas. Avoid contact with skin. Protective gloves, eyewear and clothing are recommended.

PROP 65 WARNING:

Classic Coatings, as a blender of processed material in the State of California, is required by Proposition 65 to warn that one or more of the components contained in the product contain chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. The State of California (Proposition 65) requires this warning in the absence of definitive testing to prove that the defined risks do not exist. We believe this product complies with all other applicable state and federal laws and regulations governing manufacturing, distribution and intended use. User is solely responsible for the legal disposal of this container and/or its contents.

WARRANTY:

Classic Coatings products are warranted for one year after date of purchase. Please refer to the Limited Material warranty for additional clarification. NOTICE TO BUYER: DISCLAIMER OF WARRANTIES AND LIMITATIONS ON OUR LIABILITY. We warrant that our products are manufactured to strict quality assurance specifications and that the information supplied by us is accurate to the best of our knowledge. Such information supplied about our products is not a representation or a warranty. It is supplied on the condition that you shall make your own tests to determine the suitability of our product for your particular purpose. Any use or application other than recommended herein is the sole responsibility of the user. Listed physical properties are typical and should not be construed as specifications. NO WARRANTY IS MADE, EXPRESSED OR IMPLIED, REGARDING SUCH OTHER INFORMATION, THE DATA ON WHICH IT IS BASED, OR THE RESULTS YOU WILL OBTAIN FROM ITS USE. NO WARRANTY IS MADE, EXPRESSED OR IMPLIED, THAT OUR PRODUCT SHALL BE MERCHANTABLE OR THAT OUR PRODUCT SHALL BE FIT FOR ANY PARTICULAR PURPOSE. NO WARRANTY IS MADE

THAT THE USE OF SUCH INFORMATION OR OUR PRODUCT WILL NOT INFRINGE UPON ANY PATENT. We shall have no liability for incidental or consequential damages, direct or indirect. Our liability is limited to the net selling price of our product or the replacement of our product, at our option. Acceptance of delivery of our product means that you have accepted the terms of this warranty whether or not purchase orders or other documents state terms that vary from this warranty. No representative is authorized to make any representation or warranty or assume any other liability on our behalf with any sale of our products. Our products contain chemicals that may CAUSE SERIOUS PHYSICAL INJURY. BEFORE USING, READ THE MATERIAL SAFETY DATA SHEET & FOLLOW ALL PRECAUTIONS TO PREVENT BODILY HARM.