

9813, 9814, 9815

INSTALLATION INSTRUCTIONS

Please read carefully and save these instructions as you may need them a later date.

CAUTION

Turn off the main power at the circuit breaker before installing the fixture in order to prevent possible shock.

GENERAL

All electrical connections must be in accordance with local and National Electrical Code (N. E. C) standards. If you are unfamiliar with proper electrical wiring connections obtain the services of a qualified electrician.

Remove the fixture and the mounting package from the box and make sure that no parts are missing by referencing the illustration.

ASSEMBLY AND INSTALLATION

1. Attached the mounting plate to the outlet box, make marks on wall through the key holes of mounting plate
2. Drill holes in marks in the wall, insert plastic anchors into the holes
3. Attach the mounting plate to the Outlet Box secured with outlet box screws, then, use woodscrew tight the mounting plate tight against on wall
3. Make wire connections with wire nuts:

-Smooth wire (w/markings) or black wire from the light to black wire from power source.

-Ribbed wire (w/o marking) or white wire from the light to white wire from power source

-Attach the ground wire to the cross bar with a green ground screw. Carefully tuck wire back into the OUTLET BOX

4. Align the face plate to the mounting plate screws, then secure it with the ball nuts.

5. Unscrew the socket rings from sockets. Set glass shades onto each socket and secure with socket rings by socket ring spacer tool.

6. Install bulbs: (bulbs not included) Don't exceed the maximum capacity recommended on the Sockets.

INSTALLATION IS NOW COMPLETED

