



Seals everything that goes

# Through the ROOF!



**Seals Leaks that Asphalt Can't!**

**WARNING: VAPOR HARMFUL.  
FLAMMABLE. IRRITANT.**  
Read cautions on back panel.

**1 Gallon (3.79 L)**

### CLEAR Waterproof Sealant

- Apply down to 0°F (-18°C)
- Easy brush-on formula
- Lasts 20x longer than roof cement

**A**ctual customer reviews: "5 year old leak gone!", "Solved my problem", "This stuff is awesome". Through the Roof!® will immediately seal your nagging roof leaks even if it rains before, during or after application. It dries crystal clear, seals a variety of surfaces that come together on roofs and forms a highly-elastic, permanent seal.

- Stops leaks immediately
- Works in standing water
- Apply in temperatures down to 0°F (-18°C)
- Sticks to most surfaces\* – even wet
- Expands & contracts with temperature changes
- Won't dry hard or crack

#### Use Through The Roof!® to repair & seal:

- Galvanized metal & aluminum flashing
- Chimneys, brick, block, mortar
- Asphalt roof cement, acrylic roof coatings
- Gutters & downspouts
- Cement, slate & other roof tiles
- Shingles, shakes, tiles
- PVC & ABS vent pipe
- Ductwork & vents
- Skylights

...And much more!

#### DIRECTIONS FOR USE

1. Close ventilation intakes on roof until solvent dissipates (approx. 12 hours).
2. Surfaces must be clean & free of frost. Remove any silicone.
3. Use a foam or coarse bristle utility brush & apply product 1/8" to 1/4" thick. Due to flammability, do not apply over 1/4" thick.

NOTE: Flammable during early cure (approx. 24-48 hours). Fully cured in 1-2 weeks. Paintable after 1 week.

\* Applying on thin rubber membranes, such as EPDM, may cause warping. Test in an inconspicuous area prior to use.

#### CLEAN-UP & STORAGE

- Clean tools & unwanted surface spills with mineral spirits.
- Clean hands with citrus-based hand cleaners.
- Wipe off excess product from container neck & replace lid tightly.

**WARNING: VAPOR HARMFUL.  
FLAMMABLE. EYE & SKIN IRRITANT.** Do not breathe fumes. Do not swallow. Do not use near heat, sparks or flames. Do not smoke. Do not get in eyes. Do not get on skin or clothing. **KEEP OUT OF REACH OF CHILDREN.** Wear safety glasses & chemical resistant gloves. Use only in a well-ventilated area.

Contains: 4-Chlorotrifluorotoluene & toluene.

**FIRST AID TREATMENT:** If swallowed, call a Poison Control Center or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for 15 minutes. If on skin, rinse well with water. If breathed in, move person into fresh air.

**⚠ WARNING:** This product can expose you to toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

VOC: <300 g/L, <30% by wt.

#### LIMITED LIFETIME WARRANTY

For a detailed description of the warranty & exclusions, visit [www.sashco.com](http://www.sashco.com).



©2017 Sashco Inc.  
10300 E. 107th Place • Brighton, CO 80601  
800-767-5656 • [www.sashco.com](http://www.sashco.com)  
Made in U.S.A.

TRFVOCGAL12-17

