


This authorizes the application of the Certification Mark(s) shown below to the models described in the Product(s) Covered section when made in accordance with the conditions set forth in the Certification Agreement and Listing Report. This authorization also applies to multiple listee model(s) identified on the correlation page of the Listing Report.

This document is the property of Intertek Testing Services and is not transferable. The certification mark(s) may be applied only at the location of the Party Authorized To Apply Mark.

Applicant:	Zhongshan KEBASHI Electric Appliance Co., Ltd.	Manufacturer:	Zhongshan KEBASHI Electric Appliance Co., Ltd.
Address:	2 of Fifth Floor, No.10 Yong yi 1st Road, Yong Xing Industrial Park, Henglan Town, Zhongshan City, Guangdong Province 528478	Address:	2 of Fifth Floor, No.10 Yong yi 1st Road, Yong Xing Industrial Park, Henglan Town, Zhongshan City, Guangdong Province 528478
Country:	China	Country:	China
Party Authorized To Apply Mark:	Same as Manufacturer		
Report Issuing Office:	Intertek Testing Services Hong Kong Limited		
Control Number:	<u>5012922</u>	Authorized by:	 for L. Matthew Snyder, Certification Manager



This document supersedes all previous Authorizations to Mark for the noted Report Number.

This Authorization to Mark is for the exclusive use of Intertek's Client and is provided pursuant to the Certification agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Authorization to Mark. Only the Client is authorized to permit copying or distribution of this Authorization to Mark and then only in its entirety. Use of Intertek's Certification mark is restricted to the conditions laid out in the agreement and in this Authorization to Mark. Any further use of the Intertek name for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. Initial Factory Assessments and Follow up Services are for the purpose of assuring appropriate usage of the Certification mark in accordance with the agreement, they are not for the purposes of production quality control and do not relieve the Client of their obligations in this respect.

Intertek Testing Services NA Inc.
545 East Algonquin Road, Arlington Heights, IL 60005
Telephone 800-345-3851 or 847-439-5667 Fax 312-283-1672

Standard(s):	Electric Fans [UL 507:2017 Ed.10+R:27May2020]
	Fans and Ventilators [CSA C22.2#113:2015 Ed.10+U1]
Product:	Ceiling Fan Lights
Brand Name:	Zhongshan KEBASHI Electric Appliance Co., Ltd, Mirage Lighting.

Models:

KBS-Y4216, KBS-Y4295, KBS-Y4298, KBS-Y4240, KBS-Y4299, KBS-Y4297, KBS-Y4274, KBS-Y4294, KBS-Y4296, KBS-Y4203, KBS-5270, JYL9705A, JYL9704A, JYL9702A, JYL9706A, JYL9707A, JYL9606A, JYL9608A, KBS-4256, KBS-4810, KBS-5219, KBS-5294, KBS-5293, KBS-5282, KBS-5274, KBS-5271, KBS-5261, KBS-5234, KBS-4822, KBS-4814, KBS-4222, KBS-5218Z, KBS-5255, KBS-5257, KBS-5269, KBS-5250, KBS-5273, KBS-5272, KBS-5275, KBS-5277, KBS-5278, KBS-5286, KBS-5289, KBS-5287, KBS-5285, KBS-5290, KBS-5291, KBS-5292, KBS-5296, KBS-5279, KBS-5262, KBS-5238, KBS-5266, KBS-5267, KBS-5263, KBS-5262, KBS-5256, KBS-5299, KBS-5245, KBS-5246, KBS-5249, KBS-5232, KBS-4841, KBS-4813, KBS-4217, KBS-4223, KBS-5218, KBS-4228, KBS-5239, KBS-5248, KBS-5216, KBS-5228, KBS-4808C, KBS-5225C, KBS-52010, KBS-42002, KBS-4205, KBS-4213, KBS-4216, KBS-4224, KBS-4816, KBS-4802, KBS-5224, CLF1008A, CLF1010A, CLF1014A, CLF1016A, CLF1009A, CLF1013A, CLF1015A, CLF1011A, CLF1012A, CLF1017A, KBS-5295, KBS-4704, KBS-5284, KBS-5264, KBS-5225D, KBS-5225-8, KBS-5225, KBS-4824, KBS-52137, LT-02-004, KBS-4844, KBS-52151, KBS-6008, KBS-5226, KBS-4401, KBS-4701, KBS-5101, KBS-5101B, KBS-5101C, KBS-5252, KBS-5605, KBS-4836, KBS-5236, KBS-5236-3, KBS-5233, KBS-5207B, KBS-5247, KBS-5209F, KBS-5209G, KBS-5209S, KBS-52100, KBS-838, KBS-52006, KBS-851, KBS-848, KBS-4280, KBS-4218, KBS-5222, KBS-6001, KBS-5603, KBS-5604, KBS-5268, KBS-5284, KBS-4817, KBS-4262, KBS-5227, KBS-5227-9, KBS-5209-2, KBS-5209-3, KBS-5209-5, KBS-5209K, KBS-5209H, KBS-5209, KBS-5247-2, KBS-5240, KBS-5221, KBS-4858, KBS-4203, KBS-6004, KBS-6003, JYL9600A, JYL9601A, JYL9602A, JYL9603A, JYL9604A, JYL9605A, JYL9607A, CLF1018A, CLF1019A, CLF1020A, CLF1021A, CLF1022A, KBS-4703, KBS-4705, KBS-4241, KBS-4239, KBS-4236, KBS-3606, KBS-52101, KBS-52109, KBS-52112, KBS-52113, KBS-52147C, KBS-52104, KBS-52130, KBS-52133, KBS-52134, KBS-52135, KBS-52136, KBS-52138, KBS-52141, KBS-52142, KBS-52143, KBS-52144, KBS-52149, JYL9600A, JYL9601A, JYL9602A, JYL9603A, JYL9604A, JYL9605A, JYL9607A, F304, F405, F305, F306, F307, F406, F407, CLF1018A, CLF1019A, CLF1020A, CLF1021A, CLF1022A, KBS-4824, KBS-52137, LT-02-004, KBS-5295, KBS-4844, KBS-4703, KBS-4704, KBS-4705, KBS-4241, KBS-4239, KBS-4236, KBS-3606, KBS-5284, KBS-5264, KBS-5225D, KBS-5225-8, KBS-5225, KBS-52101, KBS-52109, KBS-52112, KBS-52113, KBS-52147C, KBS-52104, KBS-52130, KBS-52133, KBS-52134, KBS-52135, KBS-52136, KBS-52138, KBS-52141, KBS-52142, KBS-52143, KBS-52144, KBS-52149, KBS-52151, KBS-6008, KBS-6005, KBS-5219, JYL9709A, JYL9710A, JYL9711A, JYL9611A, JYL9614A, JYL9618A, 72924, 72925, 72926, 72927, 72928, 72929, 72930, 72931, CF2108A, CF2109A, CF2110A, CF2111A, KBS-52185, KBS-52185-1, 3550112, 3550113, KBS-52183, SFN-C11, SFN-C11-1, SFN-C11-2, SFN-C12, SFN-C13, JYL9714A, JYL9714B, JYL9714C, JYL9714D, JYL9715A, JYL9715B, JYL9715C, JYL9715D, JYL9715E, JYL9716A, JYL9716B, JYL9717A, JYL9717B, JYL9717C, JYL9717D, JYL9717E, JYL9717F, JYL9718A, JYL9718B, JYL9718C, JYL9718D, JYL9719A, JYL9719B, JYL9719C, JYL9720A, JYL9720B, JYL9720C, JYL9721A, JYL9721B, JYL9721C, JYL9618B, CLF1023A, CLF1023B, CLF1025A, CLF1026A, CLF1027A, CLF1028A, CLF1029A, 9633-01-BLK, 9633-01-SNWH, 9503-01-MBRN, 9503-01-MBKWH, 9083-00BLK, 9173-015-SN, 9173-015-BLK-WH, 9464-01-WHWD, KBS-6003, KBS-6005-1, KBS-52245, KBS-52235, KBS-52K020, KBS-52K012, KBS-52K003, KBS-52233, KBS-52232, KBS-52219, KBS-52250, KBS-52251, KBS-52262, KBS-52198, KBS-52196, KBS-52187, KBS-52186, KBS-66K001, KBS-19003, KBS-19001, KBS-56K001, KBS-52266, KBS-66K001, KBS-52217, KBS-52223, KBS-52134, 52K027, 52K028, 52K033, 52K034, 52K006, 52K007, KBS-52K012, 55VRS-MF/MWH, 55VRS-MF/MBK, 9083-MBK, 60WDRN-MBK/BK, 60WDRN-MWH/WH, 60WDRN-MBK/WAL, 60WDRN-

MBK/WOK, CE-CFN147US-BK, CE-CFN352US-NK, CE-CFN452US-NK, KBS-52K087, KBS-52K085, KBS-52K088, KBS-52K074, KBS-60K004, JYL9712A, JYL9712B, JYL9712C, JYL9713A, JYL9713B, JYL9722A, JYL9722B, JYL9723A, JYL9723B, JYL9725A, KBS-52K098, KBS-52236, KBS-52K068, KBS-52K074, KBS-52237, KBS-52238, KBS-52252, KBS-52267, KBS-44K001, KBS-44K002, KBS-44K003, KBS-44K005, KBS-44K006, KBS-48K001, KBS-48K002, KBS-48K003, KBS-48K005, KBS-48K006, KBS-48K007, KBS-48K008, KBS-50K001, KBS-52K001, KBS-52K004, KBS-52K005, KBS-52K008, KBS-52K009, KBS-52K010, KBS-52K013, KBS-52K053, KBS-52K128, KBS-52K070, KBS-52K129, KBS-42K009, KBS-Y42203, KBS-52K030-AC-BK, KBS-24K005-DC-WH, KBS-Y42202, KBS-32K001, KBS-52K096, KBS-76K001, KBS-66K002, KBS-54K002, KBS-54K001, KBS-52K077, KBS-52K076, KBS-52K073, KBS-52K068, KBS-52K037, KBS-52K036, KBS-52159, KBS-48K006, KBS-29K001, KBS-23K001, KBS-22K001, KBS-20K002B, KBS-20K001, KBS-42K002, KBS-38K009, KBS-66K005, KBS-66K004, KBS-52K136, KBS-48K010, KBS-52K139, KBS-52153, KBS-48K022, KBS-42K043, KBS-22K011, KBS-48K015, KBS-20K002B, KBS-52K131, KBS-52K142, KBS-52K146, KBS-52K088, KBS-52K046, KBS-52K158, KBS-10K002, KBS-52K065, KBS-52K074, KBS-48K020, KBS-4808-D, KBS-Y48019, KBS-Y48021, KBS-24K007, KBS-20K026, KBS-38K010, KBS-32K001, KBS-16K002, KBS-52K015, KBS-52K103, KBS-52K109, KBS-52K059, CF301, CF401.

USE AND CARE GUIDE

KBS-23k001



Please scan the below QR code to get the video for easy installation.



Questions or Support?

Email:sofucor_service@163.com
Email:sofucorceilingfan@163.com
www.sofucorfan.com

01 Table of Contents

Safety Information	01
Warranty	02
Ceiling installation	03
Accessory drawing	04
Installation procedure	05

Remote control manual	10
Match code	11
Fans Balance	12
Care and cleaning	13
Trouble shooting	13

02 Safety Information

READ ALL SAFETY INFORMATION AND INSTALLATION INSTRUCTIONS BEFORE YOU BEGIN INSTALLING THE FAN AND SANE INSTRUCTIONS.



Warning:
Kindly turn off the power
when connecting cables.

1. To reduce the risk of electric shock, ensure the electricity has been turned off at the circuit breaker or fuse box before you begin.
2. All wiring must be in accordance with the National Electrical Code ANSI/NFPA 70-1999 and local electrical codes. Electrical installation should be performed by a qualified licensed electrician.
3. The outlet box and support structure must be securely mounted and capable of reliably supporting 35 lbs. (15.9 kg) Use only UL Listed outlet boxes marked "Acceptable for Fan Support of 35 lbs. (15.9 kg) or less".
4. The fan must be mounted with a minimum of 7 ft. (2.1 m) clearance from the trailing edge of the blades to the floor.
5. Do not place objects in the path of the blades.
6. To avoid personal injury or damage to the fan and other items, use caution when working around or cleaning the fan
7. Electrical diagrams are for reference only. Light kits that are not packed with the fan must be UL-listed and marked suitable for use with the model fan you are installing. Switches must be UL General Use Switches. Refer to the instructions packaged with the light kits and switches for proper assembly.
8. After making electrical connections, spliced conductors should be turned upward and pushed carefully up into the outlet box. The wires should be spread apart with the grounded conductor and the equipment-grounding conductor on one side of the outlet box.
9. All setscrews must be checked and re-tightened where necessary before installation.



WARNING: To reduce the risk of personal injury, do not bend the blade brackets (also referred to as flanges) during assembly or after installation. Do not insert objects in the path of the blades.



WARNING: To reduce the risk of fire or electric shock, this fan is NOT suitable for use with solid-state speed controls.



WARNING: To avoid possible electrical shock, make sure that the electricity is turned off at the main power box before starting work. If you feel you do not have enough electrical wiring knowledge or experience, contact a licensed electrician.



WARNING: Electrical diagrams are for reference only. Optional use of any light kit shall be UL-listed and marked suitable for use with this fan



WARNING: To reduce the risk of fire, electrical shock or personal injury, ensure that the fan mounting bracket is supported directly from the building structure or the outlet box marked "Acceptable for Fan Support of 35 lbs. (15.9 kg) or less". Use only the screws provided with the outlet box.



WARNING: Do not test the fan before affixing the blades. The DC motor needs a load to rotate properly. Affixing blades and then testing the fans.

03 Warranty

The supplier warrants the fan motor to be free from defects in workmanship and material present at time of shipment from the factory for a lifetime after the date of purchase by the original purchaser. The supplier also warrants that all other fan parts, excluding any glass or acrylic blades, to be free from defects in workmanship and material at the time.

of shipment from the factory for a period of two years after the date of purchase by the original purchaser. We agree to correct such defects without charge or at our option replace with a comparable or superior model if the product is returned.

To obtain warranty service, you must present a copy of the receipt as proof of purchase. All costs of removing and re-installing the product are your responsibility. Damage to any part such as by accident, misuse, improper installation, or by affixing any accessories, is not covered by this warranty.


Because of varying climatic conditions this warranty does not cover any changes in brass finish, including rusting, pitting, corroding, tarnishing, or peeling. Brass finishes of this type give their longest useful life when protected from varying weather conditions. A certain amount of “wobble” is normal and should not be considered a defect.

Servicing performed by unauthorized persons shall render the warranty invalid. There is no other express warranty. Sofucor hereby disclaims any and all warranties, including but not limited to those of merchant ability and fitness for a particular purpose to the extent permitted by law. The duration of any implied warranty which cannot be disclaimed is limited to the time period as specified in the express warranty. Some states do not allow a limitation on how long an implied warranty lasts, so the above limitation may not apply to you.


The retailer shall not be liable for incidental, consequential, or special damages arising out of or in connection with product use or performance except as may otherwise be accorded by law. Some states do not allow the exclusion of incidental or consequential damages, so the above exclusion or limitation may not apply to you. This warranty gives specific legal rights, and you may also have other rights which vary from state to state. This warranty supersedes all prior warranties. Shipping costs for any return of product as part of a claim on the warranty must be paid by the customer.

04 Three ceiling installation methods


Concrete Ceiling Mounting Bracket




Hanger for Junction Box Mounting Bracket



Wooden ceiling Mounting Bracket



05 Accessory drawing



06 Installation procedure

1. Remove the non-slotted canopy mounting screws, and loosen the slotted canopy mounting screws.




2. Remove the ceiling bracket from the canopy and take out the handle.



3. Remove the six blade screws on the motor



4. Remove the first light kit screw and loosen the two light kit screws pre-locked on the motor (They will be needed later.)



06 Installation procedure


5. Install and tighten the blades using 6 screws



6. Feed the wire plugs through the center hole. Wrap keyhole slots around the screws and twist clockwise



7. Insert the third light kit screw, and then tighten all three light kit screws



8. Connect the light source with the wires from the motor




06 Installation procedure

9. Place the wick tray in place



10. Tighten the screws to secure the hanger



11. Loosen the screws



12. Hook the wire into the hook of the ceiling plate. Tighten the rope. Tighten the screw.




06 Installation procedure



WARNING: Turn off the electric power during installation and making wire connection.

1. Connect the wire which from ceiling fan into the receiver.
2. Connect the wire from receiver with the wire from house.



13. Use wire connecting nuts to connect the two ground wires (green) coming from the receiver and hanging bracket



14. Connect the fan live wire (red) to your house live wire; Connect the fan neutral wire (blue) to your house neutral wire



06 Installation procedure

15. Lift the canopy into place and wrap keyhole slots around the screws




16. Secure the canopy to the mounting bracket with the four canopy mounting screws



17. Install the lampshade and rotate it to lock



07 Remote control manual



- ① Turn off the light and fan at the same time
- ② Light on/off
Light color temperature switch (Press twice with an interval of 2 seconds to switch a color temperature after turning on the light.)
- ③ 6 Wind Speeds
- ④ Fan off
- ⑤ 3 Kinds of Timing
Turning off the light and the fan when the time is over
- ⑥ Fan Reverse Mode
- ⑦ Natural Wind Mode


Note: the remote control must match the same code receiver

 **When the reversible button is pressed, the fan slowly slows down to a stop and then begins to reverse.**

08 Match code



if it does not work



1. Turn on the main switch.




2. Pressing and holding this key for 5 seconds.




3. If the code is successful, you need to manually press the light switch to test whether it is successful.


09 Fans Balance



Slide the balancing clip on the trailing edge of any blade, halfway between the holder and tip. Run the fan to check the wobble. If the wobble persists, repeat with each blade, noting which one most reduced the wobble.



Slide the clip in small increments away from the center of that blade. Move the clip, operate the fan, then move it again until you eliminate as much wobble as possible.



Stick the adhesive-backed balancing weight on the top center of the blade directly in line with the balancing clip. Add more weight if needed to get a smooth-running fan.

10 Care and Cleaning



WARNING: Make sure the power is off before cleaning your fan.

- Because of the fan's natural movement, some connections may become loose. Check the support connections, brackets, and blade attachments twice a year. Make sure they are secure. It is not necessary to remove the fan from the ceiling.
- Clean your fan periodically to help maintain its new appearance over the years. Do not use water when cleaning, as this could damage the motor, or the wood, or possibly cause an electrical shock. Use only a soft brush or lint-free cloth to avoid scratching the finish. The plating is sealed with a lacquer to minimize discoloration or tarnishing.
- You can apply a light coat of furniture polish to the wood for additional protection and enhanced beauty. Cover small scratches with a light application of shoe polish.
- You do not need to oil your fan. The motor has permanently-lubricated sealed ball bearings.

11 Trouble shooting

Problem	Solution
The fan will not start.	□ Check the main and branch circuit fuses or breakers. □ Check the line wire connections to the fan and switch wire connections in the switch housing.
The fan is noisy.	□ Ensure all motor housing screws are snug. □ Ensure the screws that attach the fan blade bracket to the motor hub are tight. □ Ensure the wire nut connections are not rattling against each other or the interior wall of the switch housing. □ Allow a 24-hour "breaking in" period. Most noises associated with a new fan disappear during this time. □ If you are using the Ceiling Fan light kit, ensure the screws securing the glassware are tight. Check that the light bulbs are also secure. □ Ensure the canopy is a short distance from the ceiling. It should not touch the ceiling. □ Ensure your outlet box is secure and rubber isolator pads were used between the mounting plate and outlet box.
The fan wobbles.	□ Please check and follow the instructions: Chapitre No.12 Fan balance on page 13.

If you have any questions, please contact us. We will help you solve any problem.

Email: sofucor_service@163.com

Email: sofucor ceilingfan@163.com

www.sofucorfan.com





Register for Extended
2 Years Warranty+2 Year Warranty
Within the First 7 days
Scan QR code with your phone