

Product Information

Applicable products:	
5' bath whirlpool – left drain	K-723-H2
5' bath whirlpool – right drain	K-724-H2
ADA compliant when installed per Section 607 of the Act.	ADA

Fixture*:			
Bathing well:	athing well:		
Basin area, bottom	45" (1143 mm) x 23" (584 mm)		
Basin area, top	54" (1372 mm) x 25" (635 mm)		
Weight	390 lbs (176.9 kg)		
To overflow:			
Water depth	11-5/8" (295 mm)		
Capacity	52 gal (196.8 L)		
* Approximate measurements for comparison only.			

	Pump	kW	V	A*
		1.5	240	11
* Approximate measurements for comparison only.				

Minimum access panel (required):

Pump/control	30" (762 mm) W x 15" (381 mm) H				
Required accessories:					
Jet trim kit		K-9696			

Required Electrical Service

Dedicated circuit required, protected with Class A
Ground-Fault Circuit-Interrupter (GFCI) or Residual
Current Device (RCD):

Pump/control 208-240 V, 20 A, 50/60 Hz

Installation Notes

NOTE: Pump protrusion beyond rim.

Install this product according to the installation guide.

Floor support under whirlpool must provide for a minimum of 61 lbs/square foot (295 kg/square meter) loading.

Fixtures conforms to ASME A112.19.1/CSA B45.2. All dimensions are nominal.



