


JOB NAME:		  	
CONTRACTOR:			
PAPER STRIP COLLATION FOR FRAMING NAILS			
TYPES	D-Clipped Head	  	Smooth
			Ring
	Offset Round Head	  	Smooth
			Ring
FUNCTION		For general construction framing, sub-flooring, roof sheathing, deck, and fence building Fits most 30°-34° framing nailers	
FEATURES		Collated Fasteners meet or exceed the ASTM F1667 Standard (if applicable) Smooth Shanks provide lower withdrawal strength when compared to ring shanks Ring Shanks are deformed to have repeated ridges to increase withdrawal strength	
CORROSION		Hot Dip Galvanized (HDG) in accordance with ASTM A153 Class D standards 300-series Stainless Steel is suitable for all marine applications	
CAUTION 		Proper personal protection equipment (PPE), i.e. safety glasses, must be worn during installation of any fastener All materials and finish options shall be used in accordance with the recommendation of the treated lumber manufacturer	

TECHNICAL	Length x Dia (inch)	Penny Length	Gauge (W&M)	Head Diameter	Ring Shank Length, MIN	Nails per Strip	ASTM F1667 Bend Yield*
	2 x .113	6d	11.5	Ø 0.266 in	1.13 in	40	100,000 psi
	2-1/4 x .120	7d	11	Ø 0.266 in	1.13 in	40	100,000 psi
	2-3/8 x .113	-	11.5	Ø 0.281 in	1.25 in	34 or 40	100,000 psi
	2-1/2 x .131	8d	10.25	Ø 0.266 in	1.25 in	34 or 40	100,000 psi
	2-3/4 x .131	9d	10.25	Ø 0.281 in	1.25 in	40	100,000 psi
	3 x .120	10d	11	Ø 0.266 in	1.50 in	34 or 40	100,000 psi
	3 x .131	10d	10.25	Ø 0.281 in	1.50 in	34 or 40	100,000 psi
	3-1/4 x .120	12d	11	Ø 0.266 in	1.50 in	40	100,000 psi
	3-1/4 x .131	12d	10.25	Ø 0.281 in	1.50 in	34 or 40	100,000 psi
	3-1/2 x .131	16d	10.25	Ø 0.281 in	1.50 in	40	100,000 psi

* ASTM F1667 Bend Yield is a minimum average value appropriate for non-hardened products only

PAPER STRIP COLLATION FOR FRAMING NAILS

PROFIT



TYPES

D-Clipped
Head



Smooth


Ring

PRODUCT

	Size	Box Count QTY	Brite sku	EG sku	HDG sku	305 SS sku	316 SS sku
Smooth	2 x .113	2000	600132	-	-	-	-
Smooth	2-1/4 x .120	1000	600141	-	600241	-	-
Smooth	2-3/8 x .113	1000	-	-	-	605251	-
Smooth		2000	600152	-	608152	-	-
Smooth		5000	600150	-	-	-	-
Smooth	2-1/2 x .131	3000	-	-	601155	-	-
Smooth	3 x .120	2500	600171	-	-	-	-
Smooth	3 x .131	1000	-	-	-	605170	-
Smooth		2000	-	-	607175	-	-
Smooth		2500	600170	-	-	-	-
Smooth	3-1/4 x .120	2000	-	-	608192	-	-
Smooth		2500	600191	-	-	-	-
Smooth	3-1/4 x .131	2000	-	-	607195	-	-
Smooth		2500	600190	-	-	-	-
Smooth	3-1/2 x .131	2000	-	-	601204	-	-
Smooth		2500	600200	-	-	-	-
Ring	2 x .113	2000	602132	-	607132	-	-
Ring	2-3/8 x .113	1000	-	-	-	605250	-
Ring		2000	602152	-	601152	-	-
Ring		5000	602150	-	-	-	-
Ring	2-3/4 x .131	2500	600160	-	600260	-	-
Ring	3 x .120	1000	-	-	-	605171	-
Ring		2000	-	-	601172	-	-
Ring		2500	602172	-	-	-	-
Ring	3 x .131	1000	-	-	-	605270	-
Ring	3-1/4 x .120	2000	-	-	601192	-	-
Ring		2500	602192	-	-	-	-
Ring	3-1/4 x .131	1000	-	-	-	605290	-
Ring	3-1/2 x .131	2000	-	-	601205	-	-
Ring		2500	600205	-	-	-	-

TYPES

Offset
Round Head



Smooth

Ring

PRODUCT

	Size	Box Count QTY	Brite sku	EG sku	HDG sku	305 SS sku	316 SS sku
Smooth	2-3/8 x .113	2000	600251	-	600452	-	-
Smooth		5000	600250	-	600350	-	-
Smooth	2-1/2 x .131	2500	600340	-	-	-	-
Smooth	3 x .120	2500	600271	-	600370	-	-
Smooth	3 x .131	2500	600270	-	-	-	-
Smooth	3-1/4 x .131	2500	600290	-	600391	-	-
Ring	2-3/8 x .113	2000	600362	-	600352	-	-
Ring		5000	600360	-	600351	-	-
Ring	3 x .120	2500	-	-	600371	-	-