

TRANSLUCENT TRANSLUCIDA



PHENOSEAL®

VINYL ADHESIVE CAULK

*Masilla Adhesiva
de Vinilo*

does it all!®

Bonds•Caulks•Seals

LIFETIME GUARANTEE
GARANTIA DE POR VIDA

- INTERIOR/EXTERIOR USE
- KITCHEN & BATH
- WINDOW, DOOR & TRIM
- FAST-DRYING
- CURED CAULK IS MILDEW RESISTANT
- PAINTABLE
- EASY WATER CLEAN-UP

Phenoseal® Vinyl Adhesive Caulk is a premium-grade, all-purpose caulk ideal for **BONDING, CAULKING & SEALING** a variety of building materials.

FOR BEST RESULTS: Apply in temperatures above 40°F. Do not apply when rain/freezing temperatures are forecasted before full cure can occur. Do not use for filling butt joints, surface defects, tuck-pointing or continuous underwater use. Not for use between two non-porous surfaces or with mirrors. Joint size should not exceed 1/4" wide x 1/4" deep. If depth exceeds 1/4", use foam backer rod. Store away from extreme heat/cold.

INSTRUCTIONS: 1. Surface must be clean, dry & free of old caulk. 2. Cut nozzle at 45° angle to desired bead size. 3. Load into caulk gun. 4. Apply caulk to surface. 5. Smooth bead if necessary. 6. Clean up excess uncured caulk with damp sponge before it skins over. Cured caulk must be cut or scraped away. 7. Allow caulk to dry at least 2 hours (longer in cool/humid conditions) before painting with latex or oil-based paints. 8. Caulk will cure in 12 to 48 hours depending on joint depth, temp. & humidity.

COVERAGE: 55 linear ft at 3/16" diameter bead

Contains propylene glycol. Use in well-ventilated area. Do not get in eye or on skin. Do not ingest. Use gloves and safety glasses. In an emergency, call your poison control center at 1-800-222-1222. See Safety Data Sheet (SDS) for additional information. For an SDS, contact your supplier or visit **phenoseal.com**. **KEEP OUT OF REACH OF CHILDREN.**

⚠ WARNING Cancer and Reproductive Harm – www.P65warnings.ca.gov

NCCS Calif. ARB VOC
<1.5 wt/wt% (VOC 126 g/L)



Contiene Propilenglicol. Úselo sólo con la ventilación adecuada. Evite el contacto con los ojos y la piel. No lo ingiere. Utilice guantes y gafas de seguridad.

En caso de emergencia, llame a un centro de control de envenenamiento al 1-800-222-1222. Refiérase a la Hoja de datos de seguridad (SDS) para más información. Para obtener una SDS, comuníquese con su proveedor o visite **phenoseal.com**. **MANTENGA FUERA DEL ALCANCE DE LOS NIÑOS.**

⚠ ADVERTENCIA Cáncer y Daños al Sistema Reproductivo – www.P65warnings.ca.gov

LIFETIME GUARANTEE: When applied as directed within one year of date of purchase, PHENOMENAL BRANDS warrants this product for sealant purposes during the lifetime of your home. If product fails to perform, return container and receipt to PHENOMENAL BRANDS, Technical Customer Service, 2400 Boston Street, Suite 200, Baltimore, MD 21224 for product replacement or sales price refund. Warranty does not extend to commercial use. Manufacturer is not liable for incidental or consequential damages.

Para obtener las instrucciones y garantía en español, llame al 1-888-327-8477 o visite phenoseal.com.

QUESTIONS? ¿PREGUNTAS? Call 1-888-327-8477 or visit **phenoseal.com** & click on "Ask the Expert."

PHENOMENAL BRANDS, Phenoseal Products, A div. of **DAP Products Inc.** Baltimore, MD 21224

Made in the USA with U.S. and globally sourced materials.

Read back panel for cautions.

Lea las precauciones en el panel posterior.

10 fl oz (296 mL)