

NATURAL SEAL PLUS

DESCRIPTION

EAGLE NATURAL SEAL PLUS is a water-based fluoropolymer reactive penetrating sealer formulated for use on surfaces such as brick, block, pre-cast or poured-in-place concrete. EAGLE NATURAL SEAL PLUS will result in little to no difference in the appearance of the treated surface and can be used on lightweight or pervious concrete and mortar joints. Application of the material will add water and oil resistant properties to the substrate.

TOOLS & MATERIALS REQUIRED

- ★ EAGLE CLEANER DEGREASER & NEUTRALIZER
- ★ EAGLE ETCH & CLEAN
- ★ Pump-up sprayer
- ★ Medium/short nap roller or paint brush (dependent upon surface)

SURFACE PREPARATION

Concrete should be cured for at least 7 days. Clean dirt, wax, grease, oil and other contaminants from the surface. Be sure to remove any foreign coating unless previous coating is same or similar water-based sealer. Make sure the surface is clean, dry and sound. Clean oily concrete with Clemons' EAGLE DEGREASER NEUTRALIZER. Use a bristle brush for heavily oiled spots. If surface is slick, etch with Clemons' EAGLE ETCH & CLEAN. Rinse well with a pressure washer. Allow 24 hours to dry. Apply only when surface and air temperatures are above 50° F and below 90° F. Do not apply to excessively hot surfaces as rapid drying may cause streaking to form.

APPLICATION

EAGLE NATURAL SEAL PLUS should be applied with a pump-up sprayer. Cross-rolling is recommended for even application. Spray vertical surfaces from the bottom up. Two applications may be required for more porous surfaces. If multiple coats are applied, they must be "wet-on-wet". Clean overspray from surfaces with a damp cloth before it dries. Surface temp should be above 40 F. Do not apply if rain is expected within 12 hours. Do not thin.

NET COVERAGE RATE

Coverage rate is approximately 200ft² per gallon depending on the porosity of the substrate.

DRY TIME: Suitable for foot traffic in 4 hours and vehicle traffic in 72 hours. Full properties will develop 5 to 7 days after application.

TECHNICAL DATA

VOC: <50g/L Flash Point: N/A

CLEANUP

Clean up tools with water

MAINTENANCE

Clean sealed surface with water only. Reseal when surface no longer causes water to bead.

PRECAUTIONS:

Always test a small area for compatibility before proceeding. Do not use on surface that has been previously sealed. If white film forms, wash away with water. If it persists, scrub with brush and water. Protect from freezing. If frozen, stir until melted.

CAUTION

KEEP OUT OF REACH OF CHILDREN. Avoid contact with eyes and prolonged contact with skin. Do not ingest. First Aid: If in eyes, flush thoroughly with water. If irritation persists, get medical attention. If on skin, wash with soap and water. If swallowed, do not induce vomiting. Call a poison center or doctor immediately for treatment advice.

DISCLAIMER: Since manufacturer has no control over handling, use or storage; no guarantee expressed or implied, is offered. Eagle IFP warrants the product to be free of defects and will replace or refund the purchase price of said products proven defective. Labor cost and/or other consequential damages are not covered by this warranty. Responsibility for claims of any kind is strictly limited to the purchase price of the product. The suitability of the product for any extended use shall be solely up to the user.