

slipDoctors®
LEADERS IN FLOOR SAFETY

PRO GRIP

***ANTI-SLIP WATERBASED
RUBBERIZED COATING***

FOR USE ON:

Metal • Wood • Steel

Fiberglass • Concrete

Coverage up to 45 sq ft

ONE GALLON / 3.78 LITERS

Warning! - May cause skin irritation and serious eye damage.

SlipDoctors® PRO-GRIP is a one-part acrylic rubber coating that forms a tough elastic surface that provides sure-footed safety, cushioning comfort and sound-deadening properties. PRO-GRIP is non-conductive and safe for barefoot walking. This unique coating can be applied to most walking surfaces, including metal, wood, fiberglass, aluminum, steel, blacktop and concrete. Provides anti-slip protection on patios, decks, boats and marine areas.

Read label instructions thoroughly prior to application.

SURFACE PREPARATION

- Application surface must be clean and free of any dust, oil, grease or any other contaminants.
- If the surface is not primed, we suggest light sanding to promote adhesion.
- **DO NOT** apply on surfaces that have been sealed with a permanent type of form oil, curing compound or release agent.
- Concrete, Fiberglass and Metal surfaces should be primed before the application of Pro Grip.
- New wood decks should not be treated until exposed to the elements for at least 6 months. Sand or power wash before application. Priming is recommended.
- Composite wood decking should be lightly sanded, and residue removed.

MIXING

1. **BEFORE MIXING:** remove and discard any sediment from the SIDES of the container.
Important: If the hardened coating is mixed into the formula, it will clog spraying apparatus.
2. Coating must be stirred with a drill mixer attachment thoroughly for 3 - 5 minutes to ensure the rubber particles are evenly distributed.
3. Once opened and frequently during application, scrape down the sides of the container to prevent the material from solidifying on the sides. To prevent clogs in the spraying apparatus, carefully scrape off and dispose of hardened sediment. **DURING APPLICATION, KEEP CONTAINER CLOSED.** Important: During application, keep the container tightly closed.

APPLICATION METHODS

- Once thoroughly stirred, the coating can be applied by spraying or by using a hopper gun.
- The most ideal results will be achieved by applying two coats using a drywall hopper gun connected to a compressor capable of handling a minimum of 6.2 CFM, at an air setting of between 60-65 PSI, and by using the 3/16-inch tip on the gun.
- When applying outdoors, surface temperature should be above 45°F (12°C). If above 80°F (27°C), concrete and wood surfaces can be dampened to enhance coverage.
- A dry coating of 25-45 mils thickness (applied in two coats) will achieve excellent electrical resistance and walking durability.

DRY TIME

- Allow product to dry for 2-3 hours before applying additional coats.
- Depending upon climate conditions Pro Grip fully dries in 5 - 8 hours. The thicker the coating, the longer the cure time.
- Maximum strength and adhesion will be achieved in 4 - 7 days.

REAPPLICATION / TOUCH UPS

- If reapplication of the coating becomes necessary, thoroughly clean the worn areas.
- Reapply as previously instructed.
- PRO-GRIP adheres to itself, and any thickness can be obtained by applying in layered sequences of thickness, with time allotted for each layer to cure.

COVERAGE

Coverage per gallon (3.78 liters) is approximately 30-45 square feet (two coats sprayed), depending upon the texture of the surface and method of application.

CLEAN UP

Clean equipment by flushing with water as soon as job is complete. Cleaning spray guns and lines occasionally with mineral spirits or paint thinner is recommended to prevent buildup of material.

MAINTENANCE

Surface can be cleaned by low-pressure power washing or lightly scrubbing with a deck brush and rinsing thoroughly.

STORAGE / DISPOSAL

PROTECT FROM FREEZING. Store at 50° - 80°F (10° - 27°C). Keep lid tightly closed. Dispose of contents in accordance with all local, state, and national regulations.

PRECAUTIONS

Please read product label, Technical Data Sheet and Safety Data Sheet before application. These technical documents can be downloaded by scanning the QR code or visiting our website. Use of Neoprene gloves and eye protection with side shields is recommended. Do not breathe vapors, mist or gas. Use in a well-ventilated area or wear appropriate respiratory protection equipment. Inhalation of vapor or mist can cause headache, nausea, irritation of throat, nose and lungs. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Keep container tightly closed. **KEEP OUT OF REACH OF CHILDREN.**

FIRST AID

GENERAL: In all areas of doubt, seek medical attention. **INHALATION:** Move subject to fresh air. **EYES:** Flush eyes with water. Consult a physician if irritation persists. **SKIN:** Wash affected skin areas thoroughly with soap and water. Consult a physician if irritation persists. **INGESTION:** If swallowed, give two glasses of water to drink. Never give anything by mouth to an unconscious person. Seek medical attention if necessary.

Find more anti-slip products at www.slipdoctors.com. Need technical assistance? Call 888-436-5404 or email us at support@slipdoctors.com.

DISCLAIMER: SlipDoctors cannot guarantee results or assume any obligation or liability in connection with the use of this product. Testing is recommended prior to full application. Responsibility remains with the Buyer for proper application. Buyer shall determine the suitability of the product for application and assumes all responsibilities in connection therewith. Buyer assumes all risks and responsibility for disposal. SlipDoctors cannot eliminate all possibilities of slip-and-fall accidents



Scan for
instructions



WARNING



MADE IN USA

slipDoctors®
LEADERS IN FLOOR SAFETY

PRO GRIP

***ANTI-SLIP WATERBASED
RUBBERIZED COATING***

***FOR USE ON:
Metal • Wood • Steel
Fiberglass • Concrete***

Coverage up to 225 sq ft

FIVE GALLON / 18.9 LITERS

Warning! - May cause skin irritation and serious eye damage.

SlipDoctors® PRO-GRIP is a one-part acrylic rubber coating that forms a tough elastic surface that provides sure-footed safety, cushioning comfort and sound-deadening properties. PRO-GRIP is non-conductive and safe for barefoot walking. This unique coating can be applied to most walking surfaces, including metal, wood, fiberglass, aluminum, steel, blacktop and concrete. Provides anti-slip protection on patios, decks, boats and marine areas.

Read label instructions thoroughly prior to application.

SURFACE PREPARATION

- Application surface must be clean and free of any dust, oil, grease or any other contaminants.
- If the surface is not primed, we suggest light sanding to promote adhesion.
- **DO NOT** apply on surfaces that have been sealed with a permanent type of form oil, curing compound or release agent.
- Concrete, Fiberglass and Metal surfaces should be primed before the application of Pro Grip.
- New wood decks should not be treated until exposed to the elements for at least 6 months. Sand or power wash before application. Priming is recommended.
- Composite wood decking should be lightly sanded, and residue removed.

MIXING

1. **BEFORE MIXING:** remove and discard any sediment from the SIDES of the container.
Important: If the hardened coating is mixed into the formula, it will clog spraying apparatus.
2. Coating must be stirred with a drill mixer attachment thoroughly for 3 - 5 minutes to ensure the rubber particles are evenly distributed.
3. Once opened and frequently during application, scrape down the sides of the container to prevent the material from solidifying on the sides. To prevent clogs in the spraying apparatus, carefully scrape off and dispose of hardened sediment. **DURING APPLICATION, KEEP CONTAINER CLOSED.** Important: During application, keep the container tightly closed.

APPLICATION METHODS

- Once thoroughly stirred, the coating can be applied by spraying or by using a hopper gun.
- The most ideal results will be achieved by applying two coats using a drywall hopper gun connected to a compressor capable of handling a minimum of 6.2 CFM, at an air setting of between 60-65 PSI, and by using the 3/16-inch tip on the gun.
- When applying outdoors, surface temperature should be above 45°F (12°C). If above 80°F (27°C), concrete and wood surfaces can be dampened to enhance coverage.
- A dry coating of 25-45 mils thickness (applied in two coats) will achieve excellent electrical resistance and walking durability.

DRY TIME

- Allow product to dry for 2-3 hours before applying additional coats.
- Depending upon climate conditions Pro Grip fully dries in 5 - 8 hours. The thicker the coating, the longer the cure time.
- Maximum strength and adhesion will be achieved in 4 - 7 days.

REAPPLICATION / TOUCH UPS

- If reapplication of the coating becomes necessary, thoroughly clean the worn areas.
- Reapply as previously instructed.
- PRO-GRIP adheres to itself, and any thickness can be obtained by applying in layered sequences of thickness, with time allotted for each layer to cure.

COVERAGE

Coverage per gallon (3.78 liters) is approximately 30-45 square feet (two coats sprayed), depending upon the texture of the surface and method of application.

CLEAN UP

Clean equipment by flushing with water as soon as job is complete. Cleaning spray guns and lines occasionally with mineral spirits or paint thinner is recommended to prevent buildup of material.

MAINTENANCE

Surface can be cleaned by low-pressure power washing or lightly scrubbing with a deck brush and rinsing thoroughly.

STORAGE / DISPOSAL

PROTECT FROM FREEZING. Store at 50° - 80°F (10° - 27°C). Keep lid tightly closed. Dispose of contents in accordance with all local, state, and national regulations.

PRECAUTIONS

Please read product label, Technical Data Sheet and Safety Data Sheet before application. These technical documents can be downloaded by scanning the QR code or visiting our website. Use of Neoprene gloves and eye protection with side shields is recommended. Do not breathe vapors, mist or gas. Use in a well-ventilated area or wear appropriate respiratory protection equipment. Inhalation of vapor or mist can cause headache, nausea, irritation of throat, nose and lungs. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Keep container tightly closed. **KEEP OUT OF REACH OF CHILDREN.**

FIRST AID

GENERAL: In all areas of doubt, seek medical attention. **INHALATION:** Move subject to fresh air. **EYES:** Flush eyes with water. Consult a physician if irritation persists. **SKIN:** Wash affected skin areas thoroughly with soap and water. Consult a physician if irritation persists. **INGESTION:** If swallowed, give two glasses of water to drink. Never give anything by mouth to an unconscious person. Seek medical attention if necessary.

Find more anti-slip products at www.slipdoctors.com. Need technical assistance? Call 888-436-5404 or email us at support@slipdoctors.com.

DISCLAIMER: SlipDoctors cannot guarantee results or assume any obligation or liability in connection with the use of this product. Testing is recommended prior to full application. Responsibility remains with the Buyer for proper application. Buyer shall determine the suitability of the product for application and assumes all responsibilities in connection therewith. Buyer assumes all risks and responsibility for disposal. SlipDoctors cannot eliminate all possibilities of slip-and-fall accidents



Scan for
instructions



WARNING



MADE IN USA