

INSTALLATION INSTRUCTION

HANGING THE FIXTURE (Fig. 1)

1. Shut off power at the fuse box or circuit breaker box and remove the old fixture including the mounting hardware.
2. Carefully unpack your new fixture and lay out all the parts in a clear area. Take care not to misplace any small parts necessary for installation.
3. Unscrew screws (E) separate support ring (H) from fixture (D).
4. Unscrew screws (C) separate mounting plate (A) from fixture (D).
5. Attach mounting plate (A) to junction box (not included) with mounting screws (B). The side of mounting plate (A) marked “GND” must face out.

CONNECTING THE WIRES (Fig. 2)

6. Connect the electrical wires as shown in Fig. 2, making sure that all wire connectors(K) are secured. If your junction box has a ground wire (green or bare copper), connect the fixture’s ground wire to it. Otherwise, connect the fixture’s ground wire directly to the mounting plate (A) using the green screw provided. After the wires are connected, tuck them carefully inside the junction box.

COMPLETING THE INSTALLATION (Fig. 1)

7. Place fixture (D) over mounting plate (A) and secure with screws (C) provided.
8. Install (2) two medium base bulbs (F) up to 60 watts each or CFL or LED equivalent (not included) in accordance with the fixture specification—**DO NOT EXCEED THE MAXIMUM WATTAGE RATING! (NE PAS DEPASSER LA PUISSANCE NOMINALE MAXIMALE!)**.
9. Put the glass shade (G) in the support ring (H), then secure support ring (H) to fixture (D) with screws (E).

Your installation is now complete. Return power to the junction box and test the fixture.

