

WORKS WITH LOCKING LAMINATED WOOD, HYBRID RESILIENT AND ENGINEERED HARDWOOD FLOATING FLOORS SOLD AT LOWE'S.*



3 mm

100 SQ FT = 4 FT x 25 FT

ALL LOCKING FLOORS REQUIRE UNDERLAYMENT.



PREMIUM UNDERLAYMENT + MOISTURE BARRIER

PERGO Gold®

FOR LOCKING LAMINATED WOOD, HYBRID RESILIENT
AND ENGINEERED HARDWOOD FLOATING FLOORS



Dry

More than 10 times the moisture transmission protection of basic underlayment.**



Comfort

Enhanced thermal insulation ensures the ideal floor temperature year round.



Quiet

Reduces in-room noise and transmission of noise to rooms below.



Stable

Superior compression strength means stronger joints, more stable floors and longer life.



PERGO Gold*

- Eliminates the need to purchase a moisture barrier
- Increases thermal and sound insulation
- Enhances the performance of floors with attached pad*
- Smooths minor subfloor imperfections

www.pergo.com | 1-800-33-PERGO



EASY TO INSTALL
fan fold

Easy to install!

Ensure that all foam seams without the overlapping lip tape are sealed with underlayment seam tape. (Sold separately)



EASY TO CUT
with a grid pattern



EASY TO SEAL
with pretaped sides

SPECIFICATIONS:

Dimensions:

3 mm thick x 4 ft wide x 25 ft long

Moisture Protection:

0.01 pounds/24 h/1,000 sq ft

Impact Sound Insulation:

IIC 71/STC 66/Delta 21
(on a 6" slab with drop ceiling)

IIC 75/STC 66/Delta 21
(on a 8" slab with drop ceiling)

Thermal Insulation:

R-Value 0.59

Smoothing: 2.5 mm

Compression Strength:

> 15 PSI

Safety:

Odorless, non-toxic, 100% recyclable



* Not suitable for Luxury Vinyl Tile. Flooring warranties provided by flooring manufacturers.

** The WVTR performance claim is based on test results of ASTM E96 of both basic underlayment and Pergo Gold underlayment under the same conditions in the same test facility. The results showed that the Pergo Gold underlayment had 10 times (ten) the protection rating than that of the basic underlayment used. These results are also subject to the installation being completed according to the laminate flooring manufacturer's instructions and the sub-floor conforming to accepted standards at time of installation.