



# tetraGRIP™

STUDLESS SIDING SYSTEM



**INSTALLS 20% FASTER ON AVERAGE\***

**NO MARKING STUDS > FEWER CUTS > LESS WASTE**

---

**SECURELY FASTENS FIBER CEMENT SIDING DIRECTLY TO  
OSB SHEATHING, FASTENING TO STUD NOT REQUIRED**

# tetraGRIP™

## STUDLESS SIDING SYSTEM

Save an average of 20%\* by eliminating the time needed to locate and mark studs, and to measure and cut planks to land on studs. Fastening fiber cement siding directly to OSB with the patented 1-1/8" fastener helps prevent unintended damage to utilities behind sheathing and more importantly may increase your crew's productivity allowing you to take on more jobs per year.

- NO MARKING AND HITTING STUDS
- LESS MEASURING
- LESS CUTTING
- LESS WASTE
- LESS RISK OF CALLBACKS

## WHY IT WORKS BETTER



### ROTATION BONDS NAIL TO WOOD

Mechanically bonds with the wood fibers for superior holding power.

### STRONG NON-DESTRUCTIVE WOOD INTERACTION

Efficient rotation helps eliminate wood destruction common in standard ring shank nails.

### SUPERIOR WITHDRAWAL RESISTANCE

The barbed helix-to-wood engagement creates a high load capacity and does not require a nail-to-stud interaction.

# tetraGRIP™

## STUDLESS SIDING SYSTEM

### FASTENER SPECIFICATIONS

**Part Number:** 650964

**Fastener Finish:** Galvanized Steel

**Shank Diameter:** 0.117"

**Length:** 1-1/8"

**Head Size:** Full Round Head - 0.300"

**Collation Media:** Plastic Coil

**Shank Type:** Barbed Helix

**Nails Per Coil:** 120

**Nails Per Box:** 3,600

### TOOL SPECIFICATIONS

**Part Number:** 515400

**Model Number:** TG100CSN

**Weight:** 4.9lbs (2.2kg)

**Height:** 11.5"

**Length:** 12.25"

**Width:** 6"

**Magazine Type:** Coil

**Nail Capacity:** 120 Nails/Coil

**Operating Pressure P.S.I. Bar:** 90 - 120 PSI



**Paslode®**

REPUTATION IS EVERYTHING™

PASLODE.COM

PASLODE® | GLENVIEW, IL 60025 | #50086



Manufactured  
using ITW's  
WERCS™ Tooling



Designed and  
Made in the USA