

UNTREATED WOOD END GRAIN

SEALED WITH IPE SEAL®



Hardwood End Grain Sealer

PROTECT YOUR WOOD WITH IPE SEAL®

Ipe Seal® is a wax emulsion sealer proven to increase the structural integrity of hardwood decking. Once applied to freshly cut, exposed wood end grain, Ipe Seal® creates a bond that extends the life of each deck board while also preventing splits (end checking) and unsightly cracks.



1 quart per 500 sq ft. of lumber.

APPLICATION

Always clean dirty wood end grain before applying Ipe Seal*. Apply a liberal even coating to the end grain of the wood. Brush from the bottom upwards on deck boards and apply liberally on log ends. Thorough, complete coverage of the end grain will maximize the benefits for your lumber.



1 QUART

5 GALLONS

FINISH STRONG WITH IPE OIL®

Easy Application, Exceptional Results - Easy As 1,2,3
SHAKE. STIR & MIX WELL • Ouestions/Comments: www.DeckWise.com







1. SCRUB CLEAN & LET DRY

2. APPLY IPE OIL®

3. WIPE OFF EXCESS

Exclusive products of DeckWise*, The Ipe Clip* Fastener Co. LLC.

LOCAL: 941.896.9851 TOLL FREE: 1.866.427.2547

