

说明书

版式设计要求：

1. 字体：标题为Myriad Pro SemiBold，内容为 Myriad Pro light；
2. 上下页边距为9mm，左右边距为8mm；；
3. 标注说明书长宽尺寸，单位mm。

140mm

Installation instructions

Faucet water filter

A replacement for the following water filter:

PUR® faucet filter

Filter life: 3 months or 300 gallons, whichever comes first will vary based on water condition.



Tested and Certified by NSF International against **NSF/ANSI Standard 42** in model ECF-7008S for the reduction of the claims specified on the Performance Data Sheet, and to **NSF/ANSI 372 (≤0.25% lead)**.

Filter features:


- Economical alternative to expensive substitutes.
- Easy installation and operation.
- Provides cleaner, fresher water by reducing impurities.
- Designed to provide up to 3 months of life or 300 gallons.
- Does not remove minerals which may be beneficial to health.

Installation instructions

1. Twist top cover off.





Horizontal System




Vertical System

2. Insert filter into the device. (Don't worry, the filter will fit lossely.)



3. Replace top cover.



Filter change light:

Appropriate light will flash 6 times as you begin to use the filter.

Replacement of filter cartridge resets the light.

- Green light means the filter is working.
- Yellow light means the filter should be changed soon.
- Red light means it's time to change your filter.

The filter change light contains a non-replaceable battery. After 2-3 years of use, the battery will eventually stop working but the filter is still functional.

Storage and maintenance:

- Replace your filter every 3 months or 300 gallons to prevent bacteria and fungus growth in your filter, supply lines, and storage tank.
- Keep your unused filters in a cool, dark, and dry place until you need them.
- If you do not use your water dispenser for more than four days, run two gallons of water before using it to prevent bad tasting water.

Frequently asked questions:

Q: Do I need to remove the filter prior to descaling equipment?

A: Yes, remove filter prior to descaling and inspect for integrity if needing to replace it with a new filter.

Q: Why are there black specks in the water or why does my water taste funny?

A: Water filters are made from the purest carbon blocks. When the filter ships, it bounces around and knocks carbon granules loose from the block. These little carbon granules are called fines. All of the quality filters in the market place require a preliminary flushing to remove the carbon fines. Some systems may need to be flushed more than once. This is especially true if you have scale or lime water. If you go on vacation and do not use your filtered water for several days, flush the systems again to remove any stagnant water.

Q: Must the filter be changed every 3 months?

A: Yes, you must replace the filter every 3 months or sooner if water flow is reduced or if there is heavy sediment / rust present. Over-used filters will degrade the filtration performance.

7008A-42

210mm

⚠ Warning:

To reduce the risk of property damage due to water leakage, this filter **MUST** be installed in accordance with the manufacturer's specifications and instructions. This filter unit must be replaced every 300 gallons or 3 months. Failure to follow instructions and operating specifications will void your warranty. Further, manufacturer assumes no responsibility or liability for damages arising out of misuse of the product.

PUR® is a registered trademark of Helen of Troy Limited.

PUR® is used for reference purposes only.

*The service life mentioned above is subject to chlorine reduction.

Actual result varies according to the local water quality.

Performance data sheet

System Model: **ECF-7008S**

Operating specifications:

Operating Temperature: 33 -100°F/0.6 - 38°C

Working Pressure: 20 -100 psi/140 - 689 kPa

Rated Capacity: 300 gallons/1,137 litres

Flow Rate: 0.5 gpm/1.9 lpm

Substance reduction:

The system has been tested and certified by the NSF International according to NSF/ANSI Standard 42 and NSF/ANSI Standards 372. The concentration of the indicated substances in water entering the system was reduced to a concentration less than or equal to the permissible limit for the water leaving the system, as specified by NSF/ANSI Standard 42. While testing was performed under standard laboratory conditions, actual performance may vary.

Substance	Inf.Average	NSF Specified Challenge Concentration	Ave. % Reduction	Average Product Water Concentration	Max Permissible Product Water Concentration	NSF Reduction Requirements	NSF Test Report
Chlorine Taste and Odor	2.0 mg/L	2.0 mg/L ± 10%	96.5%	0.05 mg/L	N/A	≥50%	J-00341213



Do not use with water that is microbiologically unsafe or of unknown water quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used with disinfected water that may contain filterable cysts.

* Testing was performed under standard laboratory conditions, actual performance may vary.


Manufacturer Technical Support

Tel: 1-888-352-3558 (U.S.)

E-mail: service@water-filter.com



Made in China V041
Qingdao Ecopure Filter Co., Ltd.



印刷品技术要求

1. 工艺要求 ☒ 覆光膜 ☐ 覆亚膜 ☐ UV油 ☐ 吸塑油 ☐ 过油 ☐ 丝印 ☐ 镭射
2. 材质要求 80g双胶纸，双面印刷
3. 颜色要求 单黑印刷
4. 版面要求 印刷品文字线条印迹清晰、无重影;印刷品套印准确无偏色、溢墨、指痕等;印刷品上光层均匀、光亮、牢固无粘连;覆膜表面平整、无褶皱、光泽度好;纸张材质正确，切边整齐、压线深浅适中、洁净、无斑点和条痕。



图像颜色请依据数码稿印刷

请不要擅自变更来稿件，如须修改，请联系伊可普做有关决定



青岛伊可普电器有限公司包装设计图纸

品牌		工厂型号	ECF-7008
物料编码	03070007008A	版本号	V041
包材文件名称	03070007008A ECF-7008A-42-说明书-V041		
尺寸规格	210*140mm	页数	4P
设计负责人	张鑫龙	审核日期	2022.07.04

DCR变更

(变更日期+变更描述)

2022.07.01：适配型号改为Replacement for PUR®Faucet Filter