FRIGIDAIRE.

24" Panel Ready Built-In Dishwasher

Dishwasher

Available Products: FDSR4501AP

Available Colors: Panel

Version: 03/24

Product Specifications

Dishwasher

Automatic Temperature Control	Yes
Detergent Dispenser	Yes
Filter Material	Stainless Steel
Filter Trap	Removable
Filtered Water	100 %
Hard Food Disposer or Filtration	Yes
Motor Speeds	Multi-Speed
Place Setting Capacity	14
Rinse Aid Dispenser	Yes
Smart Soil Sensor	Yes
Lower Spray Arm	Blade
Middle Spray Arm	Bi-Beam
Upper Spray Arm	Spray Arm
Tub Color	Stainless Steel
Tub Design	Tall Tub
Tub Material	Stainless Steel
Wash Levels	5
Wash System	Direct Feed
Water Pressure	120 psi

Dishwasher Options

Dry - Air	Yes
Dry - Heat	Yes
Dry - Max	No
Drying System	Even Dry
High Temperature	No
Start/Cancel	Yes
Washing Temperature - High	Yes
Washing Temperature - Normal	Yes
Washing Temperature - Sanitize	Yes

Upper Rack

Cup Shelf	Yes
Rack Coating	Nylon
Rack Type	Deluxe
Stemware Holder	Yes
Targeted Wash Zone	No

Controls

Control Location	Top
Delay Start Hours	1-24 Hours
Digital Display	No

Dishwasher Cycles

China Crystal	Yes
Energy Saver	Yes
Heavy	Yes
Normal	Yes
Number of Cycles	5
Rinse Only	Yes

Lower Rack

Number of Silverware Basket	1
Number of Silverware Basket Lids	2
Rack Coating	Nylon
Rack Type	Deluxe

Third Level Rack

Third Level Rack	Yes

Exterior

Panel Ready	Yes

Electrical Specifications

Amps @ 120 Volts	15 Amps
Voltage Rating	120 V

General Specifications

Sound Level	49 dBA
Annual Energy	240 kWh
Prop 65 Label	No
Warranty - Labor	1 Year
Warranty - Parts	1 Year

Performance Certifications and Approvals

CEE Tier	Tier 1
ENERGY STAR Certified	Yes

Dimensions and Volume

Minimum Height	33 3/4"
Maximum Height	35 3/4"
Width	24"
Depth	24 1/4"
Depth With Door Open	50 1/4"

Installation

Number of Leveling Legs	3

Certifications and Approvals

ADA Compliant	No

Safety Certifications and Approvals

UL Listed	Yes
ETL Listed	Yes
NSF Certified	Yes

Installation Diagram

23¾"(60,3 cm)

33 3/4"
(86 cm) *
adjustable
to
34 3/4"
(88,5 cm) **

23 7/8"
(60,6 cm)

50¼"(127,6 cm)

22½"(57,1 cm)

27¾"(70,4 cm)

Open door
to 90°

90°   90°

34" (86 cm)
min. to 34 3/4"
(88,5 cm)
máx.**

Electrical, water,
and drain lines
must be confined
to shaded area.

Preferred
Drain Areas

24" (60,96 cm)
mín.

3" (7,6 cm)

3"
(7,6 cm)

18" (45,7 cm)

3" (7,6 cm)

**NOTE:
35¾" (90,8 cm) max. height for
standard cabinetry cutout.
(5/16" [0,8 cm] mín.
clearance
required from unit to
underside of countertop.)

3½" (8,89 cm) mín.to
4½"(11,43 cm) máx.

1¼" (3,1 cm)

2¼"
(5,7 cm)

1" (2,5 cm)

2¼"
(5,7 cm)

24" (61 cm)