

DESCRIPTION

• Metal construction with various finishes identified by suffix Flexible supply lines with 3/8" compression fittings Includes non-metal push-down waste assembly Includes optional 3 hole deck plate (escutcheon)

OPERATION

- \cdot Lever style handle
- Temperature controlled by 100° arc of handle travel

FLOW

- Water usage is limited to these maximum flow rates as indicated by the corresponding product markings
- 1.2 gpm max (4.5L/min) at 60 psi

CARTRIDGE

• Ceramic disc technology Non-metallic, non-ferrous, and brass materials Single body construction for easy replacement

STANDARDS

- Third party certified to WaterSense,[®] ASME A112.18.1/CSA B125.1, and all applicable requirements referenced therein Certified to NSF 61/9 & 372
- Products marked with 1.2 gpm are compliant with California water efficiency regulations
- Complies with California Proposition 65 and with the Federal Safe Drinking Water Act

WARRANTY

- Lifetime limited warranty against material or manufacturing defects to the original homeowner
- 10 year limited warranty when used in a multifamily installation 5 year limited warranty when used in a commercial installation Visit www.moen.com/support for complete details and limitations





Karis™

One-Handle Lavatory Faucet

MODELS: 84346 SERIES

NOTE: THIS FAUCET INSTALLS THROUGH 1 HOLE, 1-1/8" (28mm) MIN. DIA.

ers

