



Vista Pivot™ II

Framed pivot shower door

1505D-36

Features

- Framed, 1/8" (3 mm) thick tempered glass.
- Tempered glass ensures maximum safety and durability.
- 7" (178 mm) inline panel 5/32" (4 mm) thick.

Material

- Anodized aluminum prevents rust and corrosion.

Installation

- Out-of-plumb adjustability simplifies installation.
- Not for use in hospitality.
- For residential use only.

Recommended Products/Accessories

K-23723 Faucet cleaner

Included Components

Additional Components:

Hardware kit



Codes/Standards

ANSI Z97.1

CPSC 16CFR 1201

STERLING® Warranty - Bath and Shower Doors

See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.

Color	Code	Description
-------	------	-------------



N	Nickel
N	Nickel
N	Nickel
N	Nickel
S	Silver

Available Glass Options

Code	Description
------	-------------


	Brownstone™
	Frosted
	Pebbled
	Rain
	Tangle™

1-800-STERLING (1-800-783-7546)

Kohler Co. reserves the right to make revisions without notice to product specifications.

For the most current Specification Sheet, go to www.sterlingplumbing.com.

5-29-2021 15:45 - US//CA



Technical Information

All product dimensions are nominal.

Installation type:	For shower base installation
Opening Width - Min:	31-1/4" (794 mm)
Opening Width - Max:	36" (914 mm)
Walk-through - Min:	20-5/16" (516 mm)
Walk-through - Max:	25-1/16" (637 mm)
Base-To-Wall	3/8" (10 mm)
Radius - Max:	
Glass thickness:	1/8" (3 mm)

Notes

Install this product according to the installation guide.

The vertical opening should be a minimum of 67" (1702 mm) to allow for installation clearance.