




S3698TRM
Shower/Hand Shower Trim
Specification Submittal

Location:



Model Numbers

- S3698TRM**
Shower/Hand Shower System Trim

Valve Options:

- S262 Series Temptrol Shower Valve with TRM modifiers
- S162 Series Temptrol Shower Valve requires TC modifier

Feature Highlights

- Duro Shower/Hand Shower Trim
- Requires Temptrol® Pressure Balancing Tub/Shower Valve
- Integral diverter.
- Metal lever handle.
- 30" slide bar for hand shower wand.
- Dual checks for backflow protection.
- 60" flexible metal hose.
- Single mode hand shower wand with NPSO.
- Single mode showerhead.
- 2.0 gpm (7.6 L/min) flow restrictors.
- Components shall be metal and nonmetal construction, plated in standard polished chrome finish.

Compliance

- ASME A112.18.1/CSA B125.1
- WaterSense 1.5 gpm (5.7 L/min) 1.75 gpm(6.6 L/min) 2.0 gpm (7.6 L/min)
- Lever handle meets ADA requirements for operation



Options/ Modifications

- 15** 1.5 gpm (5.7 L/min) flow restrictor
- STN** Satin Nickel finish
- MB** Matte Black finish
- BBZ** Brushed Bronze finish
- L1** Less showerhead
- L2** Less hand shower wand
- L3** Less showerhead & hand shower (head and wand only)
- L4** Less head, arm and flange
- L5** Less hand shower system
- L7** Less handle
- TC** Test Cap Trim (includes TA-10&T-12A) *used with S162 series Temptrol Valve*

Warranty

Limited Lifetime - to the original end purchaser in consumer/residential installations.

10 Years - for commercial/industrial installations. Refer to www.symmons.com/warranty for complete warranty information.



SKU Builder

Series	Finish	Modifier	Flow Rate	Trim (required)	Test Cap	Final SKU
S3698	STN		1.5	TRM		S3698STN15TRM
S3698	MB	L3		TRM	TC	S3698MBL3TRMTC

Note: No more than two modifiers (L1-L7) and modifier order will follow numerical order.

Architectural/ Engineering Specification

Symmons Duro Shower and Hand Shower Trim _____ Includes Duro Shower and Hand Shower Trim powered by Temptrol® Pressure Balancing Shower Valve. Features integral diverter, metal lever handle, 30" slide bar for hand shower wand, dual checks for backflow protection, 60" flexible metal hose, single mode hand shower wand with NPSO, single mode showerhead, and standard 2.0 gpm (7.6 L/min) flow restrictors. Components shall be metal and nonmetallic construction, plated in standard polished chrome finish. 10 Year Commercial Warranty. Lever handle meets ADA requirements for operation. ASME A112.18.1/CSA B125.1, WaterSense 1.5 gpm (5.7 L/min), 1.75 gpm (6.6 L/min), and 2.0 gpm (7.6 L/min) compliant. Available options: "15 - 1.5 gpm (5.7 L/min) flow restrictor", "175 - 1.75 gpm (6.6 L/min) flow restrictor", "STN - Satin Nickel finish", "MB - Matte Black finish", "BBZ - Brushed Bronze finish", "L1 - Less showerhead", "L2 - Less hand shower wand", "L3 - Less showerhead & hand shower (head and wand only)", "L4 - Less head, arm and flange", "L5 - Less hand shower system", "L7 - Less handle", and "TC - Test Cap Trim".

