## Ice maker Outlet Box MIP

## **DYCONN**

Ice maker stop valves with SS water hammer arrestor

## The easiest way to make a water supply control fit in refrigerator.

- Works with PEX, CPVC or Copper piping systems
- Inlet: <sup>1</sup>/<sub>2</sub>" MIP/ Sweat Outlet: <sup>3</sup>/<sub>4</sub>" MNH
- Constructed with leadfree brass & 304 Stainless steel
- Ball valve designed with 1/4 turn
- Snap on faceplate to fix up to 3/4" thick drywall

- Integrated with stainless steel hammer arrestor for water shock wave prevention
- Great for both remodel & new construction application
- Can be mounted left or right side of the stud.
- Maximum pressure: 250 PSI Temperature range: 33-180F

## Installation instruction:

- 1. Shut off the main water supply line
- 2. Secure the box to the stud or any framing.
- Connect the cold water line to the ½ MIP/Sweat Valve (Green handle Valve). Make sure the water supply line is secured to the stud to prevent movement.
- 4. Push the faceplate into place once the drywall is completed
- 5. Attach to ice maker water line to the valve and turn on the valve

@2019 Dyconn Faucet. All rights reserved. Dyconn Faucet and they Dyconn Faucet logo are registered trademarks of Dyconn Faucet. All other trademarks are the property of their respective owners.



Made in China



This Product May Contain A Chemical Known to California to cause cancer, or birth defects or other reproductive harm. www.P65Warnings.ca.gov