

Butyl Sealant Kit

For use with Part No. 102392, 102639, 102640, 102641



WARNING!

Harmful if swallowed. Avoid prolonged skin contact. Wear gloves while handling product. Keep out of reach of children and pets.

Butyl sealant is an all-weather, rubber-based compound that provides a reliable, long-lasting seal between riser components. Designed for easy application and consistent performance in wastewater environments.

Specifications:

Service Temperature: -40°F to 250°F

Application Temperature: 20°F to 120°F

Storage Temperature: <120°F

Meets or Exceeds Following Standards:

ASTM C990 - Specification for Joints for Concrete Pipe, Manholes, and Precast Box Sections Using Preformed Flexible Joint Sealants; Section 6.2 Butyl Rubber Sealants

AASHTO M 198 - Joints for Circular Concrete Sewer and Culvert Pipe Using Flexible Watertight Gaskets

ASTM C972 - 00(2011) - Standard Test Method for Compression Recovery of Tape Sealant

ASTM C765 - 97(2015) - Standard Test Method for Low Temperature Flexibility of Preformed Tape Sealants

DIRECTIONS

Surface must be dry and clean of debris

1. Remove the roll from packaging and keep it clean and free of debris.
2. Place the exposed sealant surface down onto the intended application surface.
3. Apply the sealant in a continuous motion around the joint.
4. Cut off any excess sealant and form a clean butt joint.
5. Knead the ends together to complete the sealant joint.
6. Remove the protective paper from the sealant.
7. Assemble the joint, ensuring the mating surfaces make full contact with the butyl sealant.