

QC CL-3100 RF QuietCool Original Classic Line

QC CL-3100 RF Specifications

| | | |
|--|--|--|
| Airflow | Hi: 3,126 CFM / Low: 2,847 CFM | |
| HVI-916 Airflow (for CA Title 24 New Construction) | Hi: 2,380 CFM / Low: 2,160 CFM | |
| Recommended SQFT Coverage @ 2-3 CFM per SQFT | Covers 1,072 SQFT to 1,608 SQFT | |
| Energy Use | Hi: 299 Watts / Low: 256 Watts | |
| Amps | Hi: 2.58 / Low: 2.20 | |
| Motor Voltage | 120 VAC, 60 Hz | |
| # of Speeds | 2 | |
| dBA | Hi: 49.4 / Low: 46.8 | |
| Minimum Attic Clearance | 34" | |
| Duct Diameter | 16" | |
| Duct Length | 6 feet | |
| Motor Head Diameter | 16 1/2" | |
| Motor Head Length | 13 1/2" | |
| Dampers | Barometric Pressurized R5 Dampers | |
| Controls | Included IT-36003 QuietCool Wireless RF Control Kit with Glass Wireless RF Switch | |
| Warranty | 10 Years | |
| Framing | None Required | |
| Joist Cutting | None Required; fits 16" or 24" on center | |
| Minimum Suggested Attic Venting | 4.17 SQ FT net free area | |
| Ceiling Rough Opening | 14 1/4" x 22 1/4" | |
| Removable Grille Outside Dimension | 16" x 24" | |
| Shipping Weight | 56 lbs. | |
| Box Dimensions | 27" x 20" x 38" | |
| In The Box | <div> -QC CL-3100 Motorhead -Ceiling Grille -Cut-out Template -Window Locks </div> <div> -Damper Box -6 Foot Duct -Accessory Bag -Wireless RF Control Kit </div> | |



For more information, visit our website at:
QUIETCOOLSYSTEMS.COM