

Asciutto, 24" Built-In / Freestanding Dry Aging Cabinet

Model: FFSDA6833-24



KEY FEATURES

- Efficient Cooling: Uses compressor inverter. The compressor inverter ensures energy efficiency, quiet operation, and precise temperature control for optimal performance.
- Effective Air Circulation: Professional dual evaporator and dual airflow system ensure thorough air circulation, keeping the air fresh inside.
- Sterilization: Intelligent UVC sterilization system with 254nm UVC light kills bacteria effectively, including resistant strains.
- Automatic defrosting for hassle-free maintenance.
- Stainless steel 304 interior for durability and corrosion protection.
- LED light strip for better visibility.
- Activated charcoal filter for odor control.
- Door alarm for security.
- Door lock for added safety.
- Touch control panel for easy operation.
- UV door film protection.

Included Accessories:

- 4 Adjustable stainless steel shelves.
- 3 Stainless steel hooks.
- 1 Stainless steel hanger

SPECIFICATION

Temperature Range	2-14°C
Humidity Control	50%-85%
Zone	Single Zone
Capacity	14.6 Cu.ft.
Volts:	115
Frequency:	60HZ
Amperage	0.8A
Power Cord Length:	1.5M
Power cord	Nema 5-15P
Refrigerant:	R600a
Product Dims WxDxH(in)	26 27/32 x 32 13/32 x 73 13/32
Net Weight	289 lbs 131 kg
Packaging Weight	319 lbs 144.69 kg
Certification	SGS Listed
Standards	ANSI/UL 60335-2-24, CAN/CSA C22.2 No. 60335-1:16 CAN/CSA C22.2 No. 60335-2-24:22, 3 CAN/CSA-C22.2 No. 60335-2-89, UL 60335-1, 6th Ed., UL 60335-2-89, 2nd Edition

