

Warranty beginning on the date of installation. ClarkDietrich tape-on beads and trims are manufactured to the highest of quality standards and are warranted not to edge crack for 30 years, provided the products are installed on a sound structure on a stable foundation using the following industry standard installation practices.

- Gypsum wallboard must be clean and dry and must be installed as per the manufacturer's recommendations
- The steel backing must completely cover all gaps present in the drywall
- A gap of ¼" is left between the base of the bead and the floor
- A full layer of all-purpose joint compound is applied, and the bead is firmly embedded in the compound
- The initial coat of joint compound must be completely dry before subsequent finishing coats are applied

ClarkDietrich Building Systems liability is strictly limited to replacement of the product or a refund of the purchase price, at our option. ClarkDietrich Building Systems shall not be liable for incidental and consequential damages, nor for any loss caused by misuse or misapplication of our products.

Any claim shall be deemed waived unless made in writing to us within 30 days from when the cracking was or reasonably should have been discovered. All claims must be accompanied by a sales receipt or invoice stating the date of installation.

Exclusions

- Products exposed to water and/or damaged during transit, storage, or installation are excluded from coverage
- Nail-On profiles, L-Trims, and Reveals are not covered
- Products not installed to the manufacturer's installation instructions shall not be covered
- Horizontally installed, offset, inside corners are excluded. This includes junctions in vaulted ceilings, or similar applications
- Abuse, improper maintenance, or catastrophic acts of nature are excluded from coverage

Submittal Data

All ClarkDietrich Building Systems Tape-On paper-faced beads and trims meet or exceed ASTM C1047 Standard Specification for accessories for Gypsum Wallboard.

- ClarkDietrich's paper enhances compound, texture, and paint adhesion and is resistant to scuffing, fluffing and damages caused by sanding and by drywall knives
- Fewer callbacks for repairs
- Easy-to-adjust during application to ensure a clean, precise corner that is long-lasting
- ClarkDietrich Tape-On beads and trims are easily installed using joint compound to prevent nail popping