

# Prestone®

Quality Since 1927

## DOT 3 HIGH TEMPERATURE SYNTHETIC BRAKE FLUID

DOT 3 460° F Dry Boil Point for Extended  
Fluid Life and Added Margin of Safety



**WARNING:** CAUSES SEVERE EYE IRRITATION.  
CAUSES SKIN IRRITATION. HARMFUL IF SWALLOWED.  
Read carefully other cautions on back panel.

32 FL. OZ. (1 QT) 946 mL

**DOT 3 HIGH TEMPERATURE SYNTHETIC BRAKE FLUID** Complies With Federal Motor Vehicle Safety Standard 116 and SAE J1703. Minimum Wet Boiling Point 284°F (140°C). High boiling point synthetic brake fluid gives an extra margin of safety. Designed for safe operation of today's modern high powered vehicles. Suitable for all ABS, Disc and Drum brake systems. Safe to mix with any DOT 3 brake fluid.

**CAUTION:** Do not refill container and do not use for other liquids. Avoid spilling fluid on car finish or brake lining.

**NOTE: 1.** FOLLOW VEHICLE MANUFACTURER'S RECOMMENDATIONS WHEN ADDING BRAKE FLUID. **2.** KEEP BRAKE FLUID CLEAN AND DRY. Contamination with dirt, water, petroleum products or other materials may result in brake failure or costly repairs. **3.** STORE BRAKE FLUID ONLY IN ITS ORIGINAL CONTAINER. KEEP CONTAINER CLEAN AND TIGHTLY CLOSED TO PREVENT ABSORPTION OF MOISTURE.

**DIRECTIONS:** Clean all dirt from around cover on master cylinder before removing. Fill unit to level specified by manufacturer. Replace cover. Check fluid level once a month.

**WARNING:** Contains triethylene glycol monobutyl ether (143-22-6), diethylene glycol (111-46-6), tetraethylene glycol monobutyl ether (1559-34-8), polyethylene glycol monobutyl ether (9004-77-7) and other glycols and glycol ethers. **PRECAUTIONARY MEASURES:** Prevent contact with eyes. Avoid contact with skin and clothing. Wash thoroughly after handling. Do not swallow or breathe vapors. Avoid prolonged exposure. Use in a well-ventilated area. **FIRST AID:** If in **eyes**, flush thoroughly with water for at least 20 minutes, seek immediate medical attention. If on **skin**, remove contaminated clothing and wash exposed skin thoroughly with soap and water. If irritation develops and persists, contact a doctor. If **breathing** is affected, move person into fresh air. If **swallowed**, do NOT induce vomiting. IMMEDIATELY call a local poison control center or hospital emergency department.  
**KEEP OUT OF THE REACH OF CHILDREN.**

 **WARNING:** Cancer - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

PRESTONE PRODUCTS CORPORATION  
69 Eagle Road, Danbury, CT 06810  
Questions? Comments? Call 1-888-269-0750  
[www.prestone.com](http://www.prestone.com)  
AS-401Y P-6403 SDS 042  
Made in the U.S.A. with domestic  
and imported materials

