

Homax Popcorn Ceiling Texture is a non-asbestos spray-on ceiling texture that is easy to mix and safe to apply. Decorates, while concealing minor surface cracks and imperfections.

Surface Preparation: Surface should be sound, clean, dry and free of dust and oil. Temperature should be maintained at 55° (13° C) or higher throughout the finishing process.

- Prime new drywall surfaces using a good quality white drywall primer.
- Glossy or painted surfaces should be sanded to a dull finish.
- Metal surfaces should be prepared with a rust-inhibitive primer.
- New concrete should be aged 60 days, top-coated with joint compound and primed.

Mixing: Place 1¼ gallon (4.73 L) of water in a clean 5-gallon bucket. Slowly add texture and mix thoroughly (drill-type mixer is recommended). Allow material to soak for 15 minutes. Remix texture before use, adding more water if thinning is desired. Test on scrap drywall to ensure that consistency is adequate for the type of sprayer being used.

Application: Before spraying, mask off floors, windows, and doors to protect from overspray. Use spray equipment such as Homax Manual Spray Texture Gun, or compressor operated Pneumatic II Texture Gun and 3 Liter Hopper. Most standard hopper-type applicator guns may be used. Apply to ceiling evenly using a slow, sweeping motion. Take care not to apply too heavy, or sagging may occur. When application is complete, ensure adequate ventilation by opening doors and windows to promote drying.

Clean up: Use warm water to clean up any overspray or spills while texture is still wet. Wipe down or rinse equipment with a wet cloth after use. Store dry excess texture material in a tightly closed bag in a dry place.

Coverage:

Light application - up to 250 sq. ft. per box (23 m²)

Heavy application - up to 150 sq. ft. per box (14 m²)



POUR / VIERTA



MIX / MEZCLE



SPRAY / AEROSOL



8560-30_31312

0411

