MAXIMUM BAND WIDTH 155MM

Seals everything that goes 10.5 WARNING: FLAMMABLE, Read cautions on surfaces 0**Z**. Easy to gun back panel (310 mL) **Seals Leaks That Asphalt Can't!**

↑ ctual customer reviews: "Worked like a charm", "Yes, it is the best", "Would buy again & again". I A Through the Roof!® will immediately seal your nagging roof leaks even if it rains before, during or after application. You can apply it to wet surfaces & in freezing temperatures. It dries crystal clear & remains highly elastic for a permanent seal.

· Meets FHA requirements & ASTM C794

· Asphalt roof cement, acrylic roof coatings

· Chimneys, brick, block, mortar

· Shingles, shakes, tiles

- Expands & contracts with temperature changes Excellent UV resistance
- · Stays elastic, won't dry hard or crack

Through The Roof! sticks to most surfaces Galvanized metal & aluminum flashing

- · PVC, ABS vent pipe, skylights
- · Gutters & downspouts, ductwork & vents
- I . Cement, slate & other roof tile

I Through the Roof! is also available in brush-grade quarts & gallons.

* Applying on thin rubber membranes, such as EPDM, may cause warping. Test in an inconspicuous

APPLICATION RANGE: Surface temperatures of 0° to 120°F (-18° to 49°C)

SERVICE RANGE: -25° to 180°F (-34° to 82°C)

I DIRECTIONS FOR USE

- 1. Close ventilation intakes on roof until solvent dissipates (approx. 12 hours).
- I 2. Surfaces must be clean & free of frost, loose materials, dust, etc. Remove any silicone with a silicone caulk remover
- 3. Insert backer rod into joints deeper than 1/2" to provide proper sealant depth & a stronger, longer-lasting seal.
- 4. Cut tip at 45° angle. Puncture inner seal. Use caulk gun.
- 5. Tool for a smoother bead using a caulking tool or soapy finger & a light, skimming touch.
- NOTE: Flammable during early cure (approx. 24-48 hours).

Fully cured in 1-2 weeks. Paintable after 1 week.

I CLEAN-UP & STORAGE

I . Clean tools & unwanted surface spills with mineral spirits. Clean hands with citrus-based hand cleaners. I • To store, wrap nozzle tightly with plastic wrap & a rubber band

WARNING: FLAMMABLE. Do not use near heat, sparks or flames. Do not smoke. KEEP OUT OF REACH OF CHILDREN. Use only in a wellventilated area

FIRST AID: If swallowed, call a Poison Control Center or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for 15 minutes. If on skin, rinse well with water. If breathed in, move person into fresh air.

▲ WARNING: This product can expose you to Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to - www.P65Warnings.ca.gov.

VOC: 300 g/L, <32% by wt.

LIMITED LIFETIME WARRANTY: For a detailed description of the warranty & exclusions, visit www.sashco.com



©2018 Sashco Inc. 10300 E. 107th Place Brighton, CO 80601 800-767-5656 www.sashco.com

 ϵ

CHBACH

ARTWORK

SPE

CIFICATIONS

MAXIMUM TEXT

Qο

GRAPHICS WIDTH 146MM

MAXIMUM GRAPHICS HEIGHT 185MM