Model WT41 UL Listed Wire Combinations Strip Wires 1/2 in.

UL File Number E5238

Copper to Copper wire only (do not use on aluminum)





For use with solid or stranded combinations

600	Volt	Maximum
-----	------	---------

600 voit iviaximum			
1 to 3 #10	4 #20 w/1 or 2 #18, #16 or #14	2 #16 w/1 to 3 #12 or #14	1 #12 w/1 #8
4 #12 solid	1 #16 stranded	3 #16 w/1 or 2 #12 or #10	2 #12 w/1 #10
1 to 3 #12	1 #18 w/1 to 4 #16, #14 or #12	4 #16 w/1 or 2 #14 or #12	1 #10 w/1 #8
1 to 5 #14	1 #18 w/1 or 2 #10	4 #16 w/ 1 #10	1 #22 w/1 #18 w/1 #16
2 to 6 #20, #18, or #16	2 #18 w/1 to 4 #16 or #14	5 #16 w/1 #14	1 #22 w/1 #20 w/1 or 2 #16
3 to 6 #22	2 #18 w/1 to 3 #12	5 #16 solid w/1 #10 solid	1 #16 w/ 1 or 2 #14 w/1 #12 or #10
1 #22 solid w/1 #20 solid	2 #18 w/1 or 2 #10	1 #14 solid w/1 to 3 #12	1 #16 w/1 #12 w/1 #10
1 #22 w/2 to 5 #20	3 #18 w/1 to 3 #16, #14 or #12	1 #14 w/1 or 2 #10	2 #16 w/1 #14 w/1 or 2 #12
1 #22 w/1 to 5 #18, #16	3 #18 w/1 or 2 #10	2 #14 w/1 or 2#12	2 #16 w/2 #14 w/1 #12
2 #22 w/1 to 4 #20, #18 or #16	4 #18 w/1 or 2 #16, #14 or #12	2 #14 w/ 1 or 2 #12	2 #16 w/1 #12 w/1 #10
3 #22 w/1 to 3 #20, #18 or #16	4 #18 w/1 #10	2 #14 w/ 1 #8	3 #16 w/1 #14 w/1 #12 or #10
4 #22 w/1 or 2 #2, #18 or #16	5 #18 w/1 #16 or #14	3 #14 w/1 #12 or #10	4 #16 w/1 #12 w/1 #10
1 #20 w/1 to 4 #18, #16 or #14	1 #16 w/1 to 4 #14 or #12	3 #14 w/2 #12	1 #14 w/1 or 2 #12 w/1 #10
2 #20 w/1 to 3 #18, #16 or #14	1 #16 w/1 or 2 #10	4 #14 w/1 #12 or #10	2 #14 w/1 #12 w/1 #10
3 #20 w/1 or 2 #18, #16 or #14	2 #16 w/1 to 4 #14	1 #12 w/1 or 2#10	