



Onemount™ #10215 Instruction Sheet


Disclaimer: The ratings of the Onemount™ System are intended to represent the capability of the product and in no way reflect the ratings or capacity of the towing system it is being used with. You, the consumer or operator, are strongly advised to learn the ratings of the various components of the towing system and never exceed the limits of the lowest rated component being used.

This 2-5/16" Pintle Hook Accessory is rated for 20,000lbs capacity

WARNING: Do not exceed vehicle's towing capacity or receiver hitch capacity, whichever is less. See your Vehicle Owners Manual to determine Vehicle Tow Rating.

1. Install the platform mount into the 2-1/2" receiver hitch of your vehicle and secure with the included hitch pin and clip. Always secure the hitch pin with a cotter pin unless a locking device is being used.
2. Raise or lower the Pintle Hook Accessory to the desired height and insert the supplied pins through the holes that line up with the holes in the platform. Secure the pins with the included cotter pins.

A patented pre-installed rubber bumper is installed in the pintle accessory to help prevent excessive rattles. During installation, some force may be required to push the pintle accessory into position to allow the clevis pins to mate correctly.



Note: The supplied pins are specifically engineered for the Onemount™ System. If replacement pins are needed, they must be replaced with original factory Onemount™ pins. **WARNING:** Use of any pin other than of Onemount™ manufacture could fail during towing, be a serious safety hazard and will void the warranty.

3. Prior to towing, check to make sure that the pins are secured into place with the included cotter pins.
4. Never hook up trailer safety chains to the Onemount™ System.

Warning: Please ensure that the safety chains operate freely around the Onemount™ System and don't become entangled in the Platform or Pintle Hook Accessory.