



## Safety Data Sheet

Copyright,2016,3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document Group:</b>	22-4028-1	<b>Version Number:</b>	11.00
<b>Issue Date:</b>	02/24/16	<b>Supersedes Date:</b>	11/12/14

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ Hi-Strength Spray Adhesive 90

#### Product Identification Numbers

70-0050-2398-4, 70-0050-2407-3

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Adhesive, Hi-Strength Aerosol Adhesive

#### 1.3. Supplier's details

<b>MANUFACTURER:</b>	3M
<b>DIVISION:</b>	Construction and Home Improvement Markets
<b>ADDRESS:</b>	3M Center, St. Paul, MN 55144-1000, USA
<b>Telephone:</b>	1-888-3M HELPS (1-888-364-3577)

#### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

### SECTION 2: Hazard identification

The label elements below were prepared in accordance with OSHA Hazard Communication Standard, 29 CFR 1910.1200. This information may be different from the actual product label information for labels regulated by other agencies.

#### 2.1. Hazard classification

Flammable Aerosol: Category 1.

Gas Under Pressure: Liquefied gas.  
Serious Eye Damage/Irritation: Category 2B.  
Simple Asphyxiant.  
Specific Target Organ Toxicity (single exposure): Category 1.  
Specific Target Organ Toxicity (central nervous system): Category 3.  
Specific Target Organ Toxicity (respiratory irritation): Category 3.

## 2.2. Label elements

### Signal word

Danger

### Symbols

Flame | Gas cylinder | Exclamation mark | Health Hazard |

### Pictograms



### Hazard Statements

Extremely flammable aerosol.  
Contains gas under pressure; may explode if heated.

Causes eye irritation.  
May cause respiratory irritation.  
May cause drowsiness or dizziness.  
May displace oxygen and cause rapid suffocation.

Causes damage to organs:  
cardiovascular system |

### Precautionary Statements

#### General:

Keep out of reach of children.

#### Prevention:

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
Do not spray on an open flame or other ignition source.  
Pressurized container: Do not pierce or burn, even after use.  
Do not breathe dust/fume/gas/mist/vapors/spray.  
Use only outdoors or in a well-ventilated area.  
Do not eat, drink or smoke when using this product.  
Wash thoroughly after handling.

#### Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
If eye irritation persists: Get medical advice/attention.  
IF exposed: Call a POISON CENTER or doctor/physician.  
Specific treatment (see Notes to Physician on this label).

**Storage:**

Protect from sunlight. Do not expose to temperatures exceeding 50C/122F.  
Store in a well-ventilated place. Keep container tightly closed.  
Store locked up.

**Disposal:**

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

**Notes to Physician:**

Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

**2.3. Hazards not otherwise classified**

None.

41% of the mixture consists of ingredients of unknown acute oral toxicity.

53% of the mixture consists of ingredients of unknown acute dermal toxicity.

56% of the mixture consists of ingredients of unknown acute inhalation toxicity.

**SECTION 3: Composition/information on ingredients**

Ingredient	C.A.S. No.	% by Wt
Dimethyl Ether	115-10-6	35 - 45 Trade Secret *
Methyl Acetate	79-20-9	25 - 35 Trade Secret *
N.J.T.S. Registry No. 0449960-6448P	Trade Secret*	10 - 20 Trade Secret *
Cyclohexane	110-82-7	7 - 13 Trade Secret *
1,1-Difluoroethane	75-37-6	1 - 5 Trade Secret *
Pentane	109-66-0	1 - 5 Trade Secret *

\*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

**SECTION 4: First aid measures****4.1. Description of first aid measures****Inhalation:**

Remove person to fresh air. Get medical attention.

**Skin Contact:**

Wash with soap and water. If signs/symptoms develop, get medical attention.

**Eye Contact:**

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

**If Swallowed:**

Rinse mouth. If you feel unwell, get medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**

See Section 11.1. Information on toxicological effects.

#### 4.3. Indication of any immediate medical attention and special treatment required

Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

## SECTION 5: Fire-fighting measures

### 5.1. Suitable extinguishing media

Use a fire fighting agent suitable for the surrounding fire.

### 5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

### Hazardous Decomposition or By-Products

#### Substance

Carbon monoxide  
Carbon dioxide  
Irritant Vapors or Gases

#### Condition

During Combustion  
During Combustion  
During Combustion

### 5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

If possible, seal leaking container. Place leaking containers in a well-ventilated area, preferably an operating exhaust hood, or if necessary outdoors on an impermeable surface until appropriate packaging for the leaking container or its contents is available. Close cylinder. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Dispose of collected material as soon as possible.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Do not use in a confined area with minimal air exchange. Keep out of reach of children. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

### 7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 50C/122F. Store away from heat. Store away from acids. Store away from oxidizing agents.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Pentane	109-66-0	ACGIH	TWA:1000 ppm	
Pentane	109-66-0	OSHA	TWA:2950 mg/m3(1000 ppm)	
Cyclohexane	110-82-7	ACGIH	TWA:100 ppm	
Cyclohexane	110-82-7	OSHA	TWA:1050 mg/m3(300 ppm)	
Dimethyl Ether	115-10-6	AIHA	TWA:1880 mg/m3(1000 ppm)	
Dimethyl Ether	115-10-6	CMRG	TWA:1000 ppm	
1,1-Difluoroethane	75-37-6	AIHA	TWA:2700 mg/m3(1000 ppm)	
1,1-Difluoroethane	75-37-6	CMRG	TWA:1000 ppm	
Methyl Acetate	79-20-9	ACGIH	TWA:200 ppm;STEL:250 ppm	
Methyl Acetate	79-20-9	OSHA	TWA:610 mg/m3(200 ppm)	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

### 8.2. Exposure controls

#### 8.2.1. Engineering controls

Do not remain in area where available oxygen may be reduced. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

#### 8.2.2. Personal protective equipment (PPE)

##### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect Vented Goggles

##### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Nitrile Rubber

**Respiratory protection**

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece supplied-air respirator

Organic vapor respirators may have short service life.

For questions about suitability for a specific application, consult with your respirator manufacturer.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

<b>General Physical Form:</b>	Gas
<b>Specific Physical Form:</b>	Aerosol
<b>Odor, Color, Grade:</b>	Clear sweet fruity odor
<b>Odor threshold</b>	<i>No Data Available</i>
<b>pH</b>	<i>No Data Available</i>
<b>Melting point</b>	<i>Not Applicable</i>
<b>Boiling Point</b>	<i>Not Applicable</i>
<b>Flash Point</b>	-42.00 °F [ <i>Test Method:</i> Tagliabue Closed Cup]
<b>Evaporation rate</b>	1.9 [ <i>Ref Std:</i> ETHER=1]
<b>Flammability (solid, gas)</b>	Flammable Aerosol: Category 1.
<b>Flammable Limits(LEL)</b>	<i>No Data Available</i>
<b>Flammable Limits(UEL)</b>	<i>No Data Available</i>
<b>Vapor Pressure</b>	<i>No Data Available</i>
<b>Vapor Density</b>	2.97 [ <i>Ref Std:</i> AIR=1]
<b>Density</b>	0.726 g/ml
<b>Specific Gravity</b>	0.726 [ <i>Ref Std:</i> WATER=1]
<b>Solubility in Water</b>	Nil
<b>Solubility- non-water</b>	<i>No Data Available</i>
<b>Partition coefficient: n-octanol/ water</b>	<i>No Data Available</i>
<b>Autoignition temperature</b>	<i>No Data Available</i>
<b>Decomposition temperature</b>	<i>Not Applicable</i>
<b>Viscosity</b>	<i>Not Applicable</i>
<b>Average particle size</b>	<i>No Data Available</i>
<b>Bulk density</b>	<i>No Data Available</i>
<b>Hazardous Air Pollutants</b>	0 % weight [ <i>Test Method:</i> Calculated]
<b>Molecular weight</b>	<i>No Data Available</i>
<b>Volatile Organic Compounds</b>	<=55 % [ <i>Test Method:</i> calculated per CARB title 2]
<b>Percent volatile</b>	<=75 % weight
<b>Softening point</b>	<i>No Data Available</i>
<b>VOC Less H2O &amp; Exempt Solvents</b>	398 g/l [ <i>Test Method:</i> calculated SCAQMD rule 443.1]

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

Heat

### 10.5. Incompatible materials

Strong oxidizing agents

Strong acids

### 10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1. Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation:

May be harmful if inhaled.

Intentional concentration and inhalation may be harmful or fatal.

Simple Asphyxiation: Signs/symptoms may include increased heart rate, rapid respirations, drowsiness, headache, incoordination, altered judgement, nausea, vomiting, lethargy, seizures, coma, and may be fatal.

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

**Skin Contact:**

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

**Eye Contact:**

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

**Ingestion:**

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

**Additional Health Effects:**

**Single exposure may cause target organ effects:**

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Cardiac Sensitization: Signs/symptoms may include irregular heartbeat (arrhythmia), faintness, chest pain, and may be fatal.

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE > 5,000 mg/kg
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE 20 - 50 mg/l
Overall product	Ingestion		No data available; calculated ATE > 5,000 mg/kg
Dimethyl Ether	Inhalation-Gas (4 hours)	Rat	LC50 164,000 ppm
Methyl Acetate	Dermal	Rat	LD50 > 2,000 mg/kg
Methyl Acetate	Inhalation-Vapor (4 hours)	Rat	LC50 > 49 mg/l
Methyl Acetate	Ingestion	Rat	LD50 > 5,000 mg/kg
Cyclohexane	Dermal	Rat	LD50 > 2,000 mg/kg
Cyclohexane	Inhalation-Vapor (4 hours)	Rat	LC50 > 32.9 mg/l
Cyclohexane	Ingestion	Rat	LD50 6,200 mg/kg
N.J.T.S. Registry No. 0449960-6448P	Dermal		LD50 estimated to be > 5,000 mg/kg
N.J.T.S. Registry No. 0449960-6448P	Ingestion	Rat	LD50 > 34,000 mg/kg
Pentane	Dermal	Rabbit	LD50 3,000 mg/kg
Pentane	Inhalation-Vapor (4 hours)	Rat	LC50 > 18 mg/l
Pentane	Ingestion	Rat	LD50 > 2,000 mg/kg
1,1-Difluoroethane	Inhalation-Gas (4 hours)	Rat	LC50 > 437,000 ppm
1,1-Difluoroethane	Ingestion	Rat	LD50 > 1,500 mg/kg

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
Methyl Acetate	Rabbit	No significant irritation
Cyclohexane	Rabbit	Mild irritant
Pentane	Rabbit	Minimal irritation

**Serious Eye Damage/Irritation**

Name	Species	Value
Methyl Acetate	Rabbit	Moderate irritant
Cyclohexane	Rabbit	Mild irritant
Pentane	Rabbit	Mild irritant

**Skin Sensitization**

Name	Species	Value
Methyl Acetate	Human	Not sensitizing
Pentane	Guinea pig	Not sensitizing

**Respiratory Sensitization**

For the component/components, either no data are currently available or the data are not sufficient for classification.

### Germ Cell Mutagenicity

Name	Route	Value
Dimethyl Ether	In Vitro	Not mutagenic
Dimethyl Ether	In vivo	Not mutagenic
Methyl Acetate	In Vitro	Not mutagenic
Methyl Acetate	In vivo	Not mutagenic
Cyclohexane	In Vitro	Not mutagenic
Cyclohexane	In vivo	Some positive data exist, but the data are not sufficient for classification
Pentane	In vivo	Not mutagenic
Pentane	In Vitro	Some positive data exist, but the data are not sufficient for classification
1,1-Difluoroethane	In Vitro	Some positive data exist, but the data are not sufficient for classification
1,1-Difluoroethane	In vivo	Some positive data exist, but the data are not sufficient for classification

### Carcinogenicity

Name	Route	Species	Value
Dimethyl Ether	Inhalation	Rat	Not carcinogenic
1,1-Difluoroethane	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification

### Reproductive Toxicity

#### Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
Dimethyl Ether	Inhalation	Not toxic to development	Rat	NOAEL 40,000 ppm	during organogenesis
Cyclohexane	Inhalation	Not toxic to female reproduction	Rat	NOAEL 24 mg/l	2 generation
Cyclohexane	Inhalation	Not toxic to male reproduction	Rat	NOAEL 24 mg/l	2 generation
Cyclohexane	Inhalation	Some positive developmental data exist, but the data are not sufficient for classification	Rat	NOAEL 6.9 mg/l	2 generation
Pentane	Ingestion	Not toxic to development	Rat	NOAEL 1,000 mg/kg/day	during organogenesis
Pentane	Inhalation	Not toxic to development	Rat	NOAEL 30 mg/l	during organogenesis
1,1-Difluoroethane	Inhalation	Not toxic to development	Rat	NOAEL 50,000 ppm	during organogenesis

### Target Organ(s)

#### Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
------	-------	-----------------	-------	---------	-------------	-------------------

Dimethyl Ether	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Rat	LOAEL 10,000 ppm	30 minutes
Dimethyl Ether	Inhalation	cardiac sensitization	Some positive data exist, but the data are not sufficient for classification	Dog	NOAEL 100,000 ppm	5 minutes
Methyl Acetate	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Methyl Acetate	Inhalation	respiratory irritation	May cause respiratory irritation	Human and animal	NOAEL Not available	
Methyl Acetate	Inhalation	blindness	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Methyl Acetate	Ingestion	central nervous system depression	May cause drowsiness or dizziness		NOAEL Not available	
Cyclohexane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Cyclohexane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human and animal	NOAEL Not available	
Cyclohexane	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgment	NOAEL Not available	
Pentane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Multiple animal species	NOAEL Not available	not available
Pentane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Not available	NOAEL Not available	not available
Pentane	Inhalation	cardiac sensitization	Some positive data exist, but the data are not sufficient for classification	Dog	NOAEL Not available	not available
Pentane	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgment	NOAEL Not available	not available
1,1-Difluoroethane	Inhalation	cardiac sensitization	Causes damage to organs	Human and animal	NOAEL Not available	poisoning and/or abuse
1,1-Difluoroethane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL 100,000 ppm	
1,1-Difluoroethane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Not available	NOAEL Not available	not available

### Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Dimethyl Ether	Inhalation	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 25,000 ppm	2 years
Dimethyl Ether	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 20,000 ppm	30 weeks
Methyl Acetate	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.1 mg/l	28 days
Methyl Acetate	Inhalation	endocrine system   hematopoietic system   liver   immune system   kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 6.1 mg/l	28 days

Cyclohexane	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 24 mg/l	90 days
Cyclohexane	Inhalation	auditory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.7 mg/l	90 days
Cyclohexane	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rabbit	NOAEL 2.7 mg/l	10 weeks
Cyclohexane	Inhalation	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 24 mg/l	14 weeks
Cyclohexane	Inhalation	peripheral nervous system	All data are negative	Rat	NOAEL 8.6 mg/l	30 weeks
Pentane	Inhalation	peripheral nervous system	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Pentane	Inhalation	heart   skin   endocrine system   bone, teeth, nails, and/or hair   hematopoietic system   liver   immune system   muscles   nervous system   eyes   kidney and/or bladder   respiratory system	All data are negative	Rat	NOAEL 20 mg/l	13 weeks
Pentane	Ingestion	kidney and/or bladder	All data are negative	Rat	NOAEL 2,000 mg/kg/day	28 days
1,1-Difluoroethane	Inhalation	hematopoietic system   kidney and/or bladder   respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 25,000 ppm	2 years

### Aspiration Hazard

Name	Value
Cyclohexane	Aspiration hazard
Pentane	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

## SECTION 12: Ecological information

### Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

### Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate uncured product in a permitted waste incineration facility. Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. Facility must be capable of handling aerosol cans. If no other disposal options are available, waste product that has been completely cured or polymerized may be placed in a landfill properly designed for industrial waste. The facility should be equipped to handle gaseous waste. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): D001 (Ignitable)

## SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

## SECTION 15: Regulatory information

### 15.1. US Federal Regulations

Contact 3M for more information.

#### 311/312 Hazard Categories:

Fire Hazard - Yes    Pressure Hazard - Yes    Reactivity Hazard - No    Immediate Hazard - Yes    Delayed Hazard - No

#### Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

<u>Ingredient</u>	<u>C.A.S. No</u>	<u>% by Wt</u>
Cyclohexane	110-82-7	Trade Secret 7 - 13

### 15.2. State Regulations

Contact 3M for more information.

### 15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact 3M for more information.

### 15.4. International Regulations

Contact 3M for more information.

**This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.**

## SECTION 16: Other information

### NFPA Hazard Classification

**Health: 2 Flammability: 4 Instability: 0 Special Hazards: None**

**Aerosol Storage Code: 3**

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

<b>Document Group:</b>	22-4028-1	<b>Version Number:</b>	11.00
<b>Issue Date:</b>	02/24/16	<b>Supersedes Date:</b>	11/12/14

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness

or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

**3M USA SDSs are available at [www.3M.com](http://www.3M.com)**