

H.B. Fuller | Royal Adhesives & Sealants Canada Ltd  
266 Humberline Drive, Toronto, ON, M9W 5X1  
P: +1 416-649-5676 | F: +1 416-679-0511  
[hbfuller.com](http://hbfuller.com) | [Fast2K.com](http://Fast2K.com)

---

**FAST 2K™**

Expanding Backfill Composite

**PRODUCT DESCRIPTION**

Fast 2K™ is a more convenient and faster alternative than concrete for setting posts, fences, signs and much more. Fast 2K™ is a two-part proprietary polymer that expands to fill the peripheral void between the post and the hole, using the same technology applied by H.B. Fuller to set utility poles for over 20 years. Because of its expanding nature, one bag of Fast 2K™ replaces up to 2 x 50 lb (25 kg) bags of concrete. Fast 2K™ expands immediately after mixing and secures the post in the desired position within 3-5 minutes. Fences can be installed in 15-30 minutes after Fast 2K™ finishes expanding.

Fast 2K™ does not require water and becomes waterproof after fully cured.

In addition to setting all types of fence posts (wood, vinyl, chain link and ornamental), here are some other examples where Fast 2K™ can be used:

- Bollards
- Pergolas
- Mailboxes
- Signs
- Flagpoles
- Gate Posts
- Garden Light Post
- Clotheslines
- Posts for sport/athletic applications such as Basketball, Soccer, Volleyball and Tennis
- Other light weight pillar foundation applications

**USE & HANDLING INSTRUCTIONS**

Before using this product and prior to removing outer black clip and mixing contents, read and understand full instructions and warnings listed on the label to avoid injury and property damage. Improper use may be dangerous. Bag may rupture and contents may spray out if bag is not cut open within one minute after removing outer black clip. Immediately open the bag if any expansion in the bag is noticed. Part A and Part B is packaged in a unique and convenient divided bag. The bag is divided in the middle by an outer clip. (continued)

**FEATURES**

- A 2 lb (1 kg) bag replaces up to 2 x 50 lb (25 kg) of concrete
- Sets a post in only 15-30 minutes
- Mixes in only 30 seconds
- No water required
- Waterproof after fully cured
- Allows for narrower hole compared to concrete
- Can be applied at temperatures below freezing (provided bags stored at ambient temperature before application)
- Sets all types of posts (wood, vinyl, chain link or ornamental)

---

**PACKAGING**

Available in two bag sizes:

**18 fl oz (530 mL)** (10 kits/case)

- Replaces 50 lbs (25 kg) bag of concrete
- Order # **254-9.4**

**32.8 fl oz (970 mL)** - (10 kits/case)

- Replaces 2 x 50 lbs (25 kg) bags of concrete
- Order # **255-32**

**STORAGE AND USE**

Shelf life is 24 months from date of manufacture. Although there have been no changes in properties of Fast 2K™ bags after 30 days at 5°F (-15°C), we cannot guarantee the performance of the product if bags have not been protected from freezing. It is also important to keep in mind that while Fast 2K™ can be used when ambient temperatures range from -5°F - 105°F (-20°C - 40°C), it is ideal to condition Fast 2K™ bags to 65 °F - 80°F (18°C - 27 °C) prior to use, to provide optimal mixing and cure rate performance.

(continued)

## TECHNICAL DATA SHEET

### 1. MIX

Release the clip that separates the two halves of the bag and rub the bag with force from end to end along any hard surface that has no sharp edges. Mix for 25 to 30 seconds by forcing material inside the bag from one end to the other with each stroke ("shoe shining" technique).

### 2. POUR

Empty the bag into the hole. To provide a more uniform appearance and increase the moisture protection for the post, pour the foam around all sides of the post at ground level.

### 3. SET

Expansion will finish in approximately 3-5 minutes. In approximately 15-30 minutes Fast 2K™ will already be quite hard. Wait for approximately 30 minutes for the product to completely set before installing the fence or gate.

For more detailed installation instructions, consult the Fast 2K™ Instructions on the bag or contact an H.B. Fuller representative.

## TECHNICAL DATA

### Physical Properties @ 77°F (25°C)

Colour: Part A	Grey
Part B	Dark Brown
Mixed	Light Grey
Mix time	30 seconds
Expansion Onset	1.0 – 1.5 minutes
Set time	3 – 5 minutes
Full strength	30 minutes
Weather resistance (cold, hot or wet)	Excellent

## CUSTOMER SERVICE

[Fast2K@hbfuller.com](mailto:Fast2K@hbfuller.com) T: +1 416-679-5676  
[Fast2K.com](http://Fast2K.com) F: +1 416-679-0511

## FAST 2K™

Expanding Backfill Composite



The conditions of your use and application of our products, technical assistance and information (whether verbal, written or by way of production evaluations), including any suggested method of application and recommendations, are beyond our control. Therefore, it is imperative that you test our products, technical assistance and information to determine to your own satisfaction whether they are suitable for your intended uses and applications. This application-specific analysis must at least include testing to determine suitability from a technical as well as health, safety, and environmental standpoint. Such testing has not necessarily been done at H B Fuller/Royal Adhesives & Sealants Canada Ltd. All technical assistance and information provided with respect to H B Fuller/Royal Adhesives & Sealants Canada Ltd.'s products are subject to H B Fuller/Royal Adhesives & Sealants Canada Ltd.'s Terms and Conditions, including the limited warranty therein. H B Fuller/Royal Adhesives & Sealants Canada Ltd.'s Terms and Conditions appear on H B Fuller/Royal Adhesives & Sealants Canada Ltd.'s credit applications and invoices and are available upon your request. Except as expressly provided in the Terms and Conditions, H B Fuller/Royal Adhesives & Sealants Canada Ltd. excludes all express and implied warranties, representations, conditions and objections, whether statutory or otherwise, concerning the quality of the products of H B Fuller/Royal Adhesives & Sealants Canada Ltd. or their fitness for any particular purpose. It is expressly understood and agreed that the customer assumes and hereby expressly releases H B Fuller/Royal Adhesives & Sealants Canada Ltd. from all liability, in tort, contract, or otherwise, incurred in connection with the use of our products, technical assistance and information. Any statement or recommendation not contained herein is unauthorized and shall not bind H B Fuller/Royal Adhesives & Sealants Canada Ltd. Nothing herein shall be construed as a recommendation to use any product in conflict with patents covering any material or its use. No license is implied or in fact granted under the claims of any patent.