





For more Information scan the QR Code www.greatstuff.com

BATH & KITCHEN TECHNICAL DATA SHEET

CLEAR - 99BATH3004 / WHITE - 99BATH3005 / GRAY - 99BATH3031 SANDSTONE - 99BATH3032

PRODUCT DESCRIPTION

GREAT STUFF[™] Bath & Kitchen Silicone is a high performance, moisture curing, 100% RTV acetoxy silicone. It is high in strength, flexible and mildew resistant. Some common applications are sealing and filling around tubs, tiles, sinks counter tops and more. Conforms to EN 15651 - 25 LM. Can be used in areas around water exposure. Reusable nozzle with cap Low odor 12 minute set time / 30 minute dry time. Strong adhesion and durability.

PROPERTIES

- 100% Acetoxy RTV Silicone Sealant Caulk
- Mildew resistant
- Reusable nozzle with cap
- Low odor
- 12 minute set time / 30 minute dry time
- · Strong adhesion and durability
- Interior & Exterior
- UV resistant
- Lifetime Product Warranty
- Non-paintable
- Non Paintable For Interior & Exterior Use

CLEAR

100% RTV Silicone

Nildew

Resistant

ligh Strength Solvent Free

() Non Paintable

etime Product Warrantv

).1 fl. oz. (300 mL)

GLEAR

CLEAR



GREAT STUFF™ is a trademark or registered trademark of affiliates of DuPont de Nemours, Inc. used under license by National Adhesive Inc.

NATIONAL ADHESIVE INC. 8280 WILLOW OAKS CORPORATE DRIVE, SUITE 600, FAIRFAX, VA 22031, U.S.A +1 (855) 674-4583 I greatstuff@nationaladhesive.com I www.nationaladhesive.com





For more Information scan the QR Code www.greatstuff.com

BATH & KITCHEN TECHNICAL DATA SHEET

TECHNICAL INFORMATION

Chemical Base: Specific gravity: Tack free time (77°F/25°C and 50% R.H): Cure Rate (1 day) (77°F/25°C and 50% R.H): Modulus at 100% (MPa): Tensile Strength: Elongation at Break: Shore Hardness: Acetoxy silicone 1.02 ± 0.03 gr/cm³ 12 Minutes 0.08 inch/2mm ≈0.3 Mpa ≈1.50 Mpa > 500% 15 ± 3 Shore A

APPLICATION DETAILS

Application Temperature: Temperature Resistance: 41°F to 104°F (5°C to 40°C) -40°F to 302°F (-40°C to 150°C)

- For best results, the surface must be clean, dry and free of dust, oil and grease, to ensure a clean and strong adherence between the sealant and the surface.
- Cut off the cartridge tip, screw on the removable nozzle and cut tip to your desired bead size.
- Insert cartridge into caulking dispenser.
- Hold at a 45° angle and apply ahead of nozzle to achieve a smooth seal.
- Sealant normally dries to touch in 30 minutes and cures & bonds on average 24 hours.
- Uncured product can be cleaned with a solvent.
- Once cured, the product can be removed mechanically.

PACKAGING

Cartridge

COLORS Clear, White, Gray & Sandstone

NATIONAL ADHESIVE

GREAT STUFF™ is a trademark or registered trademark of affiliates of DuPont de Nemours, Inc. used under license by National Adhesive Inc.





For more Information scan the QR Code www.greatstuff.com

BATH & KITCHEN TECHNICAL DATA SHEET

SHELF LIFE

- 12 months from manufactured date when unopened.
- Store the product in a cool and dry place.
- Do not store in extreme cold, direct sunlight, and temperatures above 122°F/50°C.

CAUTION

Avoid contact with eyes and skin. Do not breathe vapors. Do not take internally. In case of eye contact, flush thoroughly with water. In case of skin contact, flush thoroughly with water. If breathed in, move person into fresh air. If swallowed, do not induce vomiting. Call a physician immediately.

HEALTH AND SAFETY

For more information, please refer to the most recent Safety Data Sheet found at www.greatstuff.com.

