



IPA2-1244-C	12,000 BTU	Heat & Cool
IPAC12-KS	12,000 BTU	IPAH12-KS.....12,000 BTU
IPAC14-LS	14,000 BTU	IPAH14-KS.....14,000 BTU



IPA2-1244-C	12,000 BTU	Heat & Cool
IPAC12-KS	12,000 BTU	IPAH12-KS.....12,000 BTU
IPAC14-LS	14,000 BTU	IPAH14-KS.....14,000 BTU

Portable Air Conditioner

3-IN-1
COOL
FAN
DEHUMIDIFY



IPAC14-LS



PROGRAMMABLE 24 HOUR DELAY	Save energy by running your AC only when you need it
AUTOMATIC AIR DIRECTION	Electronic air flow up or down
ELECTRONIC/DIGITAL CONTROL	Easily regulate Mode and temperature settings on AC unit as desired
LARGE CASTERS	Enables easy maneuverability from room to room
WASHABLE FILTER	Enables easy maintenance for the unit
3 COOLING SPEEDS, 3 FAN SPEEDS	Reduce noise level and save money with lowered cooling and fan settings
AUTO RESTART	Restores AC to previous settings in case of power outage
REMOTE CONTROL WITH DISPLAY	Adjust and control settings at a glance
SLEEP MODE	Automatically resume previous settings when turning the unit back on
PMTS	Senses the temperature from where the remote control is located
WHISPER QUIET OPERATION	Enjoy comfortable noise levels with our preferred units' whisper quiet operation



Model		IPA2-1244-C	IPAC12-KS	IPAC14-LS	IPAH12-KS	IPAH14-KS
Performance	Cooling Capacity (BTU/hr)	12,000	12,000	14,000	12,000	14,000
	Heating Capacity (BTU/hr)	-	-	-	11,000	11,000
	Application area (sq. Feet)	350	350	450	350	450
	EER	8.9	8.9	8.9	8.9	8.9
Electrical Ratings	Voltage	115	115	115	115	115
	Watts (cooling/heating)	1355	1355	1575	1355/1240	1580/1240
	amps (cooling/heating)	11.8	11.8	13.8	11.8/10.8	13.8/10.8
	Cord Length (Ft.)	7.5	7.5	7.5	7.5	7.5
	Plug Type	5-15P	5-15P	5-15P	5-15P	5-15P
	Warranty	2 Years Parts & Labor	2 Years Parts & Labor	1 Years Parts & Labor	2 Years Parts & Labor	2 Years Parts & Labor
Dimensions	Exhaust Hose Length (in.)	59	59	59	59	59
	Window Panel Maximum Width (in.)	48	48	48	48	48
	Unit - Width/Depth/Hight (in.)	18.3/18.8/30.1	18.4/15.6/30.1	18/14.4/30.5	18.4/15.6/30.1	18.4/15.6/30.1
	Carton - Width/Depth/Hight (in.)	23/23.25/36	20.3/17.2/34	20.35/17.8/34.5	20.3/17.2/34	20.3/17.2/34
	Weight - lbs. (Net/Gross)	74/86	70.55/78.26	73/84	71.65/79.36	73.85/82.67
Loading Quantity	Pallet	8	12	12	12	12
	UPC code	810941021145	810941018442	810941022661	810941018459	810941018473



ECO-FRIENDLY
R-410A
REFRIGERANT

1-2 YEAR
Parts & Labor
Limited Warranty