

ITAC08-KS21
8,000 BTU

ITAC-10KSB
10,000 BTU

ITAC12-KSB21
12,000 BTU

ITAC10-KSA21
10,000 BTU

ITAC12-KSA21
12,000 BTU

ITAC14-KS
14,000 BTU



THROUGH THE WALL ROOM AIR CONDITIONER



Remote Control



Eco-Friendly
Refrigerant



Energy Saver
Function



Sleep
Mode



24 Hour
Timer



Clean Filter
Indicator



LED
Display



Auto Restart



3 Cooling Speeds
3 Fan-Only Speeds



ITAC08-KS21
8,000 BTU

ITAC-10KSB
10,000 BTU

ITAC12-KSB21
12,000 BTU

ITAC10-KSA21
10,000 BTU

ITAC12-KSA21
12,000 BTU

ITAC14-KS
14,000 BTU

QUALITY PERFORMANCE

Save money and stay cool with the Impecca Through The Wall Room Air Conditioning Unit. Its 8K-14K Cooling BTU/h, operating using energy-efficient technology, will easily cool a room with up to 250-700 square feet. Guide the air flow as you like with four-way air direction. In the case of a power outage, the Impecca Preferred air conditioner will memorize and resume at your temperature settings when power is restored.

SPECS

Model		ITAC08-KS21	ITAC10-KSA21	ITAC-10KSB	ITAC12-KSA21	ITAC12-KSB21	ITAC-14KS
Performance	Cooling Capacity (BTU/hr)	8000	10000	10000/9800	12000/11700	12000	14000/13600
	Application area (Sq. Feet)	250-350	350-450	350-450	450-550	450-550	550-700
	EER (Btu/h.W)	9.8	9.8	9.4	9.8	9.8	8.5
	Energy Star	Yes	Yes		Yes	Yes	No
Electrical Ratings	Voltage	115	115	230/208	115	230/208	230/208
	Watts	816	1020	1060/1045	1200	1224/1194	1647/1600
	Amps	7.8	9.8	5.1/5.3	11.5	5.5/5.9	7.4/8.3
	Plug Type	5-15P	5-15P	6-15P	5-15P	6-15P	6-15P
	Cord Length (Ft.)	7	7	7	7	7	7
Features	Dry Mode	Yes	Yes	Yes	Yes	Yes	Yes
	Electronic Control / LED Display	Yes	Yes	Yes	Yes	Yes	Yes
	Remote Control	Yes	Yes	Yes	Yes	Yes	Yes
	Cool / Fan Speeds	3/3	3/3	3/3	3/3	3/3	3/3
	Auto Restart	Yes	Yes	Yes	Yes	Yes	Yes
	Timer	Yes - 24 Hour	Yes - 24 Hour	Yes - 24 Hour	Yes - 24 Hour	Yes - 24 Hour	Yes - 24 Hour
	Clean Filter Indicator	Yes	Yes	Yes	Yes	Yes	Yes
	Energy Saver Mode	Yes	Yes	Yes	Yes	Yes	Yes
	Sleep Mode	Yes	Yes	Yes	Yes	Yes	Yes
	Air Direction	4	4	4	4	4	4
	Moisture Removal (L/hr)	0.9	1.1	1.1	1.2	1.2	1.2
	Indoor noise level dB(A) (Low)	51.8	53.1	55.4	56.5	56.5	57.7
	Refrigerant type	R410A	R410A	R410A	R410A	R410A	R410A
Dimensions	Unit Width	24.2"	24.2"	24.2"	24.2"	24.2"	24.2"
	Unit Depth	20.3"	20.3"	20.3"	20.3"	20.3"	20.3"
	Unit Height	14.5"	14.5"	14.5"	14.5"	14.5"	14.5"
	Carton Width	28"	28"	28"	28"	28"	28"
	Carton Depth	26.6"	26.6"	26.6"	26.6"	26.6"	26.6"
	Carton Height	16.9"	16.9"	16.9"	16.9"	16.9"	16.9"
Weight	Net / Gross (Lbs.)	65/76	66/76	60.62 / 68.34	74.8/85.8	78.1/89.1	67.24 / 78.26
Loading Quantity	Pallet	10	10	10	10	10	10
	Container (40'HQ)	306	306	306	306	306	306



2 YEAR
PARTS & LABOR
LIMITED WARRANTY

TRIM KIT INCLUDED
To fit most wall sleeves